



REVISION HISTORY			
ECO	REV	DESCRIPTION	APPR
—	1	PRODUCTION	VICTOR K.
			10-15-2014

NOTES: UNLESS OTHERWISE SPECIFIED

1. WORKMANSHIP SHALL BE IN ACCORDANCE WITH IPC-A-610.
2. ASSEMBLY PROCESS SHALL INCLUDE: REFLOW SOLDER TOP SIDE SMD. MAXIMUM SOLDER TEMPERATURE IS 240 DEGREES CELSIUS.
3. PARTS TO OMIT WILL BE SPECIFIED ON THE BILL OF MATERIALS. LOCATIONS OF OMITTED PARTS SHALL BE FREE OF SOLDER. MASK THE SOLDER STENCIL WHERE SMT PARTS ARE OMITTED.
4. INSTALL SHUNTS AS SHOWN ON ASSY DRAWING.
5. DEPANELIZE BOARDS AFTER ASSEMBLY AND ROUTE-OUT THE BREAKOUT TABS ON FOUR SIDES OF THE BOARD EDGE.
6. DO NOT APPLY ANY KIND OF ASSEMBLY STAMP OR QA STAMP TO ANY BOARD.



APPROVALS		LINEAR TECHNOLOGY		1630 MCCARTHY BLVD MILFORD, CT 06460 PH: (408) 432-1900 WWW.LINEAR.COM LTC CONFIDENTIAL - FOR CUSTOMER USE ONLY	
PCB DES.	HZ	TITLE: TOP ASSEMBLY DRAWING		PROTECTED MOSFET DRIVER AND LOAD SWITCH	
APP ENG.	VICTOR K.	SIZE		IC NO. LT1910ES8	
		N/A		REV 1	
SCALE = NONE		DEMO CIRCUIT 2307A		SHT 1 OF 2	
		FILENAME: DC2307A-1.PCB			