

SIZE	QTY	SYM	PLATED	TOL
0.012	24	+	YES	+/-0.003
0.095	4	X	YES	+/-0.003


ADDITIONAL REQUIREMENT FOR PROTOTYPE FAB ONLY:

1. OUTGOING INSPECTION REPORT (BASED ON ACTUAL MEASUREMENTS AND CROSS SECTION).

ADDITIONAL REQUIREMENTS FOR PRODUCTION FAB ONLY:


1. PROVIDE COMPLIANCE CERTIFICATES FOR RoHS, REACH AND CONFLICT-FREE MINERALS.
2. SOLDERABILITY BOARD WITH TEST RESULTS.
3. OUTGOING INSPECTION REPORT (BASED ON ACTUAL MEASUREMENTS AND CROSS SECTION).
4. VACUUM PACKED WITH DESICCANT.
5. FULL PANEL WITH NO REJECT




LAYER STRUCTURE



NOTES: UNLESS OTHERWISE SPECIFIED

1. FAB PER IPC-A-600.
2. MATERIAL: -LEAD FREE ASSEMBLY COMPLIANT, ISOLA FR-370HR OR EQUIVALENT.
-FINISHED THICKNESS TO BE 0.062 +/- .005
-TOTAL OF 4 LAYERS WITH 2 OZ. CU ON THE OUTER LAYERS AND 2 OZ. CU ON THE INNER LAYERS.
-FLAMMABILITY RATING: 94 V-0 MINIMUM.
3. SIZE: CUT TO DIMENSIONS AND TOLERANCES SHOWN.
0.00 ARE PRIMARY DATUMS.
4. DRILLING: -DRILL HOLES PER SCHEDULE. PLATE THROUGH HOLES WITH COPPER, 0.001\"/>



UNLESS OTHERWISE SPECIFIED		 ANALOG DEVICES		 POWER BY LINEAR™	
DIMENSIONS ARE IN INCHES					
TOLERANCES:					
0.XX" = ± 0.01"					
0.XXX" = ± 0.005"					
INTERPRET DIM AND TOL PER ASME Y14.5M-1994					
THIRD ANGLE PROJECTION					
					
TITLE: FABRICATION DRAWING					
NO-OPTO ISOLATED FLYBACK CONVERTER					
SIZE	IC NO.	LT3001ES5		REV	
N/A		DC3006A		1	
FILENAME: DC3006A-1.PCB				SHT 1 OF 1	