



REVISIONS		
REV	DESCRIPTION	DATE




SIZE	QTY	SYM	PLTD
65	7	+	PLTD
55	5	⊗	PLTD
70	2	⊠	NPLTD
10	15	◇	PLTD
125	4	⊗	PLTD
20	9	⊗	PLTD

NOTES : Unless Otherwise Specified

1. FAB PER IPC-A-600.
2. MATERIAL: EPOXY FIBERGLASS, NEMA GRADE FR-4.
2 OZ. COPPER FINISHED ON OUTER LAYERS.
1 OZ. COPPER FINISHED ON INNER LAYERS.
THICKNESS .062 +/- .006 TOTAL OF 4 LAYERS.
FLAMABILITY RATING: 94 V-0 MINIMUM .
3. DRILLING: DRILL HOLES PER SCHEDULE. PLATE THROUGH HOLES WITH COPPER, .001 INCH THICK MIN. ALL HOLE SIZES ARE SPECIFIED AFTER PLATING.
HOLE LOCATION TOLERANCES ARE +/- .003 INCH IN RELATION TO CENTER
4. SOLDER MASK : SMOBC USING LPI BOTH SIDES COLOR GREEN.
5. SILKSCREEN : USING WHITE NON-CONDUCTIVE EPOXY INK.
6. DO NOT ALTER ARTWORK e.g. TO ADD LOGO OR DATE CODE.



FAB DRAWING

APPROVALS					1630 McCarthy Blvd. Milpitas, CA 95035 PH: (408)432-1900	
		INIT	DATE			
	DRAWN					
	CHECK					
	DESIGN	JUNE WU	3/6/02	TITLE: LT3439EFE, Low Noise Isolated Power Supply		
	ENGR	David C.	3/6/02			
				SIZE	A	REV. A
					DC511A	
SCALE = NONE			DES-230530		SHT 1 of 1	