



TOP SILKSCREEN
 LINEAR TECHNOLOGY
 DC843A-2 * LT3479EDE
 HIGH CURRENT BOOST LED DRIVER
 DATE: 02-09-05

REVISIONS

REV	DESCRIPTION	APPR	DATE
A	PROTOTYPE RELEASE		

NOTES: UNLESS OTHERWISE SPECIFIED

1. WORKMANSHIP SHALL BE IN ACCORDANCE WITH IPC-A-610.
2. NO SHUNT.
3. PARTS TO OMIT WILL BE SPECIFIED ON THE BILLS OF MATERIAL. LOCATIONS OF OMITTED PARTS SHALL BE FREE OF SOLDER. MASK THE SOLDER STENCIL WHERE SMT PARTS ARE OMITTED.
4. DEPANELIZE BOARDS AFTER ASSEMBLY AND ROUTE-OUT THE BREAKOUT TABS ON FOUR SIDES OF THE BOARD EDGE.
5. ASSY PROCESSES SHALL INCLUDE: REFLOW SOLDER TOP SIDE SMD.

APPROVALS

	INIT	DATE
DRAWN		
CHECK		
DESIGN	KIM T.	02-09-05
ENGR	KEITH S.	02-09-05

SCALE = NONE



1630 MCCATHY BLVD
 MILPITAS, CA 95035
 PH: (408)432-1900
 LTC CONFIDENTIAL-
 FOR CUSTOMER USE ONLY

TITLE: TOP ASSEMBLY DRAWING

HIGH CURRENT BOOST LED DRIVER

SIZE	DEMO	REV.
A	DC843A-2 * LT3479EDE	A

DES- 0000

SHT 1 of 1