




1. FAB PER IPC-A-600.
2. MATERIAL: EPOXY FIBERGLASS, NEMA GRADE FR-4.
 - 2 OZ. COPPER FINISH ON OUTER LAYERS.
 - 1 OZ. COPPER FINISH ON INNER LAYERS.
- THICKNESS .062 \pm \pm -.006 TOTAL OF 4 LAYERS.
- FLAMMABILITY RATING: 94 V-0 MINIMUM .
3. SIZE: DIMENSIONS SHOWN AND TOLERANCES TOL: \pm /.010
0.000 ARE PRIMARY DATUMS.
4. DRILLING: DRILL HOLES PER SCHEDULE. PLATE THROUGH
HOLES WITH COPPER, .001 INCH THICK MIN. ALL
HOLE SIZES ARE SPECIFIED AFTER PLATING.
- HOLE LOCATION TOLERANCES ARE \pm /.003
INCH IN RELATION TO CENTER
5. FINISH: SMOBC USING LPI BOTH SIDES COLOR GREEN.
IMMERSION GOLD PLATING
6. SILKSCREEN : BOTH SIDES USING WHITE NON-CONDUCTIVE EPOXY INK.
7. DO NOT ALTER ARTWORK TO ADD LOGO OR DATE CODE
BUT YOU MAY MODIFY PAD SIZE TO MEET END FINISH.
8. PCBs ARE TO BE RoHS COMPLIANT.
9. SCORING:



Fabrication Drawing

SIZE	QTY	SYM	PLATED	TOL
0.07	2	✕	NO	+/-0.003
0.095	10	□	YES	+/-0.003
0.01	35	◇	YES	+/-0.003
0.035	6	⊠	YES	+/-0.003

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ON ANGLE ± 1
2 PLACE $\pm .01$ 3 PLACE $\pm .005$
INTERPRET DIM AND TOL
PER ASME Y14.5M - 1994

APPROVALS		 1630 McCarthy Blvd. Milpitas, CA 95035 PH: (408)432-1900	
DRAWN	INIT	DATE	
CHECK			
DESIGN	Helen	6/03/09	
ENGR	Walker B.	6/03/09	
TITLE: LT13689EUD Monolithic 700mA Step-Down Regulator with Power-On Reset and Watchdog Timer			
SIZE	A	REV.	A
DEMO	DC1312A		
SCALE = NONE		DES	SHEET 1 of 1