



REVISION HISTORY				
ECO	REV	DESCRIPTION	APPROVAL	DATE
	4	PRODUCTION	GEORGE Q.	11/07/11

NOTES: UNLESS OTHERWISE SPECIFIED,

1. WORKMANSHIP SHALL BE IN ACCORDANCE WITH IPC-A-610.
2. ASSEMBLY PROCESS SHALL INCLUDE: REFLOW SOLDER FOR SMD'S. MAXIMUM SOLDER TEMPERATURE, 250 DEGREES CELSIUS.
3. PARTS TO OMIT WILL BE SPECIFIED ON THE BILL OF MATERIAL. LOCATIONS OF OMITTED PARTS SHALL BE FREE OF SOLDER. MASK THE SOLDER STENCIL WHERE SMT PARTS ARE OMITTED.
4. INSTALL SHUNTS AS SHOWN ON ASSY DRAWING.
5. DEPANELIZE BOARDS AFTER ASSEMBLY AND ROUTE-OUT THE BREAKOUT TABS ON FOUR SIDES OF THE BOARD EDGE.
6. DO NOT APPLY ANY KIND OF ASSEMBLY STAMP OR QA STAMP TO ANY BOARD.
7. INSTALL TURRETS AS SHOWN.



		1680 MCCARTHY BLVD MILPITAS, CA 95035 PH: (408)432-1900 www.linear.com LTC CONFIDENTIAL - FOR CUSTOMER USE ONLY	
		TITLE: TOP ASSEMBLY DRAWING, ISOLATED TRIAC DIMMABLE LED DRIVER	
PCB DES.	MI	SIZE	IC NO. LT3799EMSE
APP. ENG.	GEORGE Q.	N/A	REV 4
SCALE: NONE		FILENAME: 1775A-Rev4.PCB	
		SHT 1 of 2	