


The **LTC[®]1060** has been modified. The changes are marked below in **bold**.

ELECTRICAL CHARACTERISTICS (Complete Filter) $V_S = \pm 5V$, $T_A = 25^\circ C$ unless otherwise specified.

PARAMETER	CONDITIONS		MIN	TYP	MAX	UNITS
DC Offset V_{OS1}		●		2	15	mV
V_{OS2}	$f_{CLK} = 250kHz, 50:1, S_{A/B}$ High	●		3	40	mV
V_{OS2}	$f_{CLK} = 500kHz, 100:1, S_{A/B}$ High	●		6	80	mV
V_{OS2}	$f_{CLK} = 250kHz, 50:1, S_{A/B}$ Low	●		2	30	mV
V_{OS2}	$f_{CLK} = 500kHz, 100:1, S_{A/B}$ Low	●		4	60	mV
V_{OS3}	$f_{CLK} = 250kHz, 50:1, S_{A/B}$ Low	●		2	30	mV
V_{OS3}	$f_{CLK} = 500kHz, 100:1, S_{A/B}$ High	●		4	60	mV

 LTC and LT are registered trademarks of Linear Technology Corporation.

For further information regarding this specification notice contact:

Linear Technology Corporation
 1630 McCarthy Blvd.
 Milpitas, California 95035-7487
 Attn: Product Marketing Manager
 Phone: (408) 432-1900, x2456