



REVISION HISTORY				
ECO	REV	DESCRIPTION	APPROVED	DATE
	1	PRODUCTION	GUY H.	1-13-11




LAYER STRUCTURE




NOTES: UNLESS OTHERWISE SPECIFIED

- FAB PER IPC-A-600.
- MATERIAL: EPOXY FIBERGLASS, NEMA GRADE FR-4
FINISHED THICKNESS TO BE 0.062" +/-0.005"
4-LAYER BOARD, 2 OZ. CU ON OUTER LAYERS,
1 OZ. CU ON INNER LAYERS,
FLAMMABILITY RATING: 94 V-2 MINIMUM.
- SIZE: CUT TO DIMENSIONS AND TOLERANCES SHOWN.
0.00" ARE PRIMARY DATUMS.
- FINISH: SMOBC USING LPI BOTH SIDES, COLOR GREEN.
GOLD IMMERSION. LEAD FREE SOLDER CAN BE USED
FOR PROTOTYPE BOARDS.
SILKSCREEN: WHITE NON-CONDUCTIVE EPOXY INK.
- DRILL: PLATE THRU ALL HOLES WITH COPPER, 0.001" THICK MIN.
ALL HOLES SHALL BE DRILLED +/-0.003" WITH
RESPECT TO CTR. OF DRILLED PAD.
ALL HOLES FINISHED SIZE AFTER PLATING.
- DROP ALL UNUSED PADS ON INNER LAYERS.
- DO NOT ALTER ARTWORK e.g. TO ADD LOGO OR DATE CODE.
PAD SIZE CAN BE MODIFIED TO MEET END FINISH.
- PCBS ARE TO BE RoHS COMPLIANT.
- SCORING FOR PANELIZED PCB:



DRILL TABLE				
SYM	SIZE	TOL.	QTY	PLATED
⚡	0.108 in	+/-0.003 in	4	YES
⚡	0.094 in	+/-0.003 in	5	YES
⊗	0.070 in	+/-0.003 in	2	NO
⊗	0.064 in	+/-0.003 in	5	YES
◇	0.055 in	+/-0.003 in	15	YES
□	0.040 in	+/-0.003 in	10	YES
○	0.039 in	+/-0.003 in	21	YES
×	0.035 in	+/-0.003 in	21	YES
+	0.012 in	+/-0.003 in	312	YES

APPROVALS		 1630 MCCARTHY BLVD MILPITAS, CA 95035 TEL: (408) 432-1900 FAX: (408) 434-0507 www.linear.com LTC CONFIDENTIAL-FOR CUSTOMER USE ONLY	
PCB DES.	Guy H		
APP ENG.	GUY H.	TITLE: FAB DWG	
		LOW POWER, LOW NOISE ADC	
		SIZE N/A	REV. 1
1/13/2011 07:49:50a		SCALE: NONE	SHEET 1 OF 1