



NOTES : Unless Otherwise Specified

1. MATERIAL : FR4 OR EQUIVALENT EPOXY, 4 OZ. COPPER CLAD
THICKNESS .062 +/- .006 TOTAL OF 6 LAYERS
2. FINISH : ALL PLATED HOLES .001 MIN. / .0015 MAX. COPPER PLATE
ELECTRODEPOSITED TIN-LEAD COMPOSITION
BEFORE REFLOW , SOLDER MASK OVER BARE COPPER (SNOBC)
3. SOLDER MASK : BOTH SIDES USING LPI OR EQUIVALENT
4. SILKSCREEN : USING WHITE NON-CONDUCTIVE EPOXY INK
5. ALL DIMENSIONS ARE IN INCHES

- ART01 = LAYER 1 (COMPONENT SIDE)
- ART02 = LAYER 2 (PGND,SGND)
- ART03 = LAYER 3 (SIGNAL,VIN,VOUT)
- ART04 = LAYER 4 (SIGNAL)
- ART05 = LAYER 5 (PGND,SGND)
- ART06 = LAYER 6 (SOLDER SIDE)

SIZE	QTY	SYM	PLTD
40	24	⊗	PLTD
125	4	U	PLTD
15	173	V	PLTD
55	5	W	PLTD
94	4	X	PLTD
70	2	Y	NPLTD
205	4	Z	PLTD

Fabrication Drawing