
Digital Power Done Right



High Performance Plus Programmability

The LTC $^{\circ}$ 3880 is a digital power system manager featuring a dual output synchronous step-down controller that is fully programmable via an I 2 C-based PMBus compliant serial interface using the LTpowerPlay $^{\text{TM}}$ software. This device combines best in class analog switching regulator performance with precision mixed signal data conversion and onboard EEPROM. Real time telemetry read-back includes V_{IN} , I_{IN} , V_{OUT} , I_{OUT} and temperature allowing for smart energy management decisions. Digital control of analog power supplies with a simple PC connection enables designers of multiple rail boards a fast and easy way to do system debug and to make real-time adjustments to supply voltages, sequencing and operating limits.

Features

- I²C/PMBus Compliant Serial Interface
- High Accuracy Programming and Read-Back
- Integrated Nonvolatile Storage (EEPROM)
- Input Voltage: 4.5V to 24V
- Dual Output Voltages: 0.5V to 5.5V
- Current Mode Control for Easy Compensation and Accurate Current Sharing
- Built-in MOSFET Drivers
- Up to 30A Output per Channel

LTpowerPlay GUI Sequencing



Free Software Download www.linear.com/LTpowerPlay

▼ Info & Free Samples

www.linear.com/product/LTC3880

1-800-4-LINEAR



Watch Video video.linear.com/77

CT. LT, LTC, LTM, Linear Technology and the Linear logo are registered trademarks and LTpowerPlay is a trademark of Linear Technology Corporation. All other trademarks are the property of their respective owners.

