


REVISION HISTORY				
ECO	REV	DESCRIPTION	APPR	DATE
-	2	PRODUCTION	GB	12-9-15


LAYER STRUCTURE





NOTES: UNLESS OTHERWISE SPECIFIED

- FAB PER IPC-A-600.
- MATERIAL: -LEAD FREE ASSEMBLY COMPLIANT, ISOLA FR-370HR OR EQUIVALENT.
-FINISHED THICKNESS TO BE 0.062" +/- .005"
-TOTAL OF 4 LAYERS WITH 2 OZ. CU ON ALL LAYERS
-FLAMMABILITY RATING: 94 V-0 MINIMUM.
- SIZE: CUT TO DIMENSIONS AND TOLERANCES SHOWN.
0.00 ARE PRIMARY DATUMS.
- DRILLING: -DRILL HOLES PER SCHEDULE. PLATE THROUGH HOLES WITH COPPER, 0.001" THICK MIN.
-ALL HOLE SIZES ARE SPECIFIED AFTER PLATING.
-HOLE LOCATION TOLERANCES ARE +/-0.003" IN RELATION TO CENTER
- FINISH: -SMOBC USING LPI BOTH SIDES, COLOR GREEN, NO TENT.
-GOLD IMMERSION BOTH SIDES.
-FOR SILKSCREEN: BOTH SIDES USE WHITE NON-CONDUCTIVE INK.
- DO NOT ALTER ARTWORK e.g. TO ADD LOGO OR DATE CODE.
PAD SIZE CAN BE MODIFIED TO MEET END FINISH.
- PCBS ARE TO BE RoHS COMPLIANT.
-PLACE A Pbf STAMP ON BOTTOM OF BOARD (UNSHOWY AREA)

[8] LOCATIONS FOR BOARD CUTOUTS. (4X)



SIZE	QTY	SYM	PLATED	TOL
0.01	139	X	YES	+/-0.003
0.031	9	□	YES	+/-0.003
0.07	2	⊗	NO	+/-0.003
0.094	3	◇	YES	+/-0.003
0.187	6	+	YES	+/-0.003
0.205	2	⊗	YES	+/-0.003
0.02756	2	+ ^B	NO	+/-0.003
0.03	3	+ ^C	YES	+/-0.003

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON ANGLE ±1 0.XX" = ±0.01" 0.XXX" = ±0.005" INTERPRET DIM AND TOL PER ASME Y14.5M-1994 THIRD ANGLE PROJECTION 	APPROVALS		 LINEAR TECHNOLOGY 1630 MCCARTHY BLVD MILPITAS, CA 95035 PH: (408)452-1000 www.Linear.com LTC CONFIDENTIAL- FOR CUSTOMER USE ONLY		
	PCB DES.	NC			
	APP ENG.	GB			
TITLE: FABRICATION DRAWING:		SIZE			
AUTORESONANT WIRELESS POWER TRANSMITTER				IC NO. LTC4125 DEMO CIRCUIT 2330A	
					REV. 2
DO NOT SCALE DRAWING	SCALE: NONE	FILENAME: DC2330A-2.PCB			
		SHT 1 of 1			