




1. FABRICATION: FABRICATION AND ACCEPTANCE TO MEET THE REQUIREMENTS OF IPC-A-600 AND IPC/ANSI-MLL950-C CLASS 2, AOL .25 GENERAL INSPECTION LEVEL II.
  2. MATERIAL: -LEAD FREE ASSEMBLY COMPLIANT, ISOLA FR-370HR OR EQUIVALENT.  
-FINISHED THICKNESS TO BE 0.062" +/- .005"  
-TOTAL OF 4 LAYERS WITH 2 OZ. CU ON ALL LAYERS  
-FLAMMABILITY RATING: 94 V-0 MINIMUM.
  3. SIZE: CUT TO DIMENSIONS AND TOLERANCES SHOWN.  
0.00 ARE PRIMARY DATUMS.
  4. DRILLING: -DRILL HOLES PER SCHEDULE. PLATE THROUGH HOLES WITH COPPER, 0.001" THICK MIN.  
-ALL HOLE SIZES ARE SPECIFIED AFTER PLATING.  
-HOLE LOCATION TOLERANCES ARE +/-0.003" IN RELATION TO CENTER
  5. FINISH: -SMOBC USING LPI BOTH SIDES, COLOR GREEN, NO TENT.  
-GOLD IMMERSION BOTH SIDES.  
-FOR SILKSCREEN: BOTH SIDES USE WHITE NON-CONDUCTIVE INK.
  6. DO NOT ALTER ARTWORK e.g. TO ADD LOGO OR DATE CODE.  
PAD SIZE CAN BE MODIFIED TO MEET END FINISH.
  7. PCBs ARE TO BE RoHS COMPLIANT.  
-PLACE A Pbf STAMP ON BOTTOM OF BOARD (UNSHOWY AREA)
- [8] LOCATIONS FOR BOARD CUTOUTS. (5X)

REVISION HISTORY				
ECO	REV	DESCRIPTION	APPR	DATE
-	3	PRODUCTION	WL	06-03-19

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON ANGLE ±1 0.XXX" = "0.01" 0.XXX" = "0.005" INTERPRET DIM AND TOL PER ASME Y14.5M-1994	<h1>APPROVALS</h1>		  <div style="display: inline-block; vertical-align: middle; margin-left: 10px;">         POWER BY  <b>LINEAR™</b>          1680 MCCARTHY BLVD          MILPITAS, CA 95035          PH: (408) 432-1900          WWW.ANALOG.COM       </div>
	PCB DES.	NC	
	APP ENG.	WL	
THIRD ANGLE PROJECTION  			TITLE: FABRICATION DRAWING:  <b>SINGLE 3.6V/4.2V 650mA AUTORESONANT          WIRELESS TRANSMITTER</b>
DO NOT SCALE DRAWING	SCALE: NONE	SIZE N/A IC NO. LTC4125 DEMO CIRCUIT 2556A	REV. 03