


REVISIONS			
REV	DESCRIPTION	APPR	DATE
0	1st Prototype		


NOTES : Unless Otherwise Specified

1. FAB PER IPC-A-600.
2. MATERIAL: EPOXY FIBERGLASS, NEMA GRADE FR-4.
2 OZ. COPPER FINISH ON EXTERNAL LAYERS.
THICKNESS .062 +/-0.006 TOTAL OF 2 LAYERS.
FLAMMABILITY RATING: 94 V-0 MINIMUM .
3. SIZE: DIMENSIONS SHOWN AND TOLERANCES +/-0.010
0.00 ARE PRIMARY DATUMS.
4. DRILLING: DRILL HOLES PER SCHEDULE. PLATE THROUGH
HOLES WITH COPPER, .001 INCH THICK MIN. ALL
HOLE SIZES ARE SPECIFIED AFTER PLATING.
HOLE LOCATION TOLERANCES ARE +/-3MIL
INCH IN RELATION TO CENTER
5. FINISH: SMOBC USING LPI BOTH SIDES COLOR GREEN.
GOLD IMMERSION BOTH SIDES.
6. SILKSCREEN : USING WHITE NON-CONDUCTIVE EPOXY INK.
7. DO NOT ALTER ARTWORK TO ADD LOGO OR DATE CODE BUT YOU MAY
MODIFY PAD SIZE TO MEET END FINISH.
8. PCB's SHOULD BE RoHS COMPLIANT.

9. SCORING:



DEMO CIRCUIT 1364A
Linear Tech. Corp.



SIZE	QTY	SYM	PLATED	TOL
70	2	+	NO	+/-3Mils
63	12	X	YES	+/-3Mils
31	9	□	YES	+/-3Mils
10	12	◇	YES	+/-3Mils

FABRICATION DRAWING

APPROVALS		LINEAR TECHNOLOGY		1630 McCardy Blvd. Milpitas, CA 95035 PH: (408)432-1900	
DRAWN	INIT	DATE			
CHECK					
DESIGN	Ruth/B				
ENGR	Visd O.				
SCALE = NONE			FD	DEMO CIRCUIT 1364A	REV. 2
			TITLE: LTC4224CDD8-1/-2 Dual Low Voltage Hot Swap Controller		
			Sheet 1 of 1		