


SIZE	QTY	SYM	PLTD	TOL
72	2	+	NO	+/-0.0
95	7	X	YES	+/-0.0
15	70	□	YES	+/-0.0
20	44	◇	YES	+/-0.0
60	3	⊗	YES	+/-0.0
65	31	⊗	YES	+/-0.0
40	52	+	YES	+/-0.0
35	14	+	YES	+/-0.0

REVISIONS		
REV	DESCRIPTION	DATE

ART01 = LAYER 1 (COMPONENT SIDE)
ART02 = LAYER 2 (SOLDER SIDE)

NOTES : Unless Otherwise Specified

- 1. MATERIAL : FR4 OR EQUIVALENT EPOXY, 2 OZ. COPPER CLAD
THICKNESS .062 +/--.006 TOTAL OF 2 LAYERS
- 2. FINISH : ALL PLATED HOLES .001 MIN. / .0015 MAX. COPPER PLATE
WHITE TIN IMMERSION (OMIKRON) BOTH SIDES.
- 3. SOLDER MASK : BOTH SIDES USING GREEN LPI
BEFORE REFLOW , SOLDER MASK OVER BARE COPPER (SNOBC)
- 4. SILKSCREEN : USING WHITE NON-CONDUCTIVE EPOXY INK
- 5. ALL DIMENSIONS ARE IN INCHES
- 6. SCORING: NOT REQUIRED FOR PROTOTYPE



Fabrication Drawing

APPROVALS

INIT	DATE

LINEAR TECHNOLOGY

1630 McCarthy Blvd.
Milpitas, CA 95035
PH: (408)432-1900

TITLE: 200W Negative 48V Hot Swap Controller With
Current and Voltage Monitoring

SIZE	A	REV.	A

SCALE = NONE	DES-
	SHT 1 of 1