


SIZE	QTY	SYM	PLTD
95	8	+	PLTD
10	6	X	PLTD
15	112	□	PLTD
70	2	◇	NPLTD
215	8	⊗	PLTD
187	6	A	NPLTD

NOTES : Unless Otherwise Specified

1. FAB PER IPC-A-600. LEAD FREE ASSEMBLY TEMPERATURE REQUIRED.
2. MATERIAL: EPOXY FIBERGLASS, NEMA GRADE FR-4.
2 OZ. COPPER FINISH ON OUTER LAYERS.
THICKNESS .062 +/- .006 TOTAL OF 2 LAYERS.
FLAMABILITY RATING: 94 V-0 MINIMUM .
3. SIZE: DIMENSIONS AND TOLERANCES SHOWN.
0.00 ARE PRIMARY DATUMS.
4. DRILLING: DRILL HOLES PER SCHEDULE. PLATE THROUGH HOLES WITH COPPER. .001 INCH THICK MIN. ALL HOLE SIZES ARE SPECIFIED AFTER PLATING.
HOLE LOCATION TOLERANCES ARE +/- .003 INCH IN RELATION TO CENTER
5. FINISH: SMOBC USING LPI BOTH SIDES COLOR GREEN.
GOLD IMMERSION.
6. SILKSCREEN : USING WHITE NON-CONDUCTIVE EPOXY INK.
7. DO NOT ALTER ARTWORK e.g. TO ADD LOGO OR DATE CODE.
8. SCORING:



FAB DRAWING

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ON ANGLE ±1
2 PLACE ±.01 3 PLACE ±.005
INTERPRET DIM AND TOL
PER ASME Y14.5M - 1994

APPROVALS

INIT	DATE
PCB DESIGNER J. WU	4/9/07
ENGINEER M. Lee	4/9/07
CHECK	

SCALE = NONE

LINEAR TECHNOLOGY
1630 McCarthy Blvd.
Milpitas, CA 95035
PH: (408)432-1900

TITLE: LTC4357DCDB,
Single Positive High Voltage Ideal Diode-OR

SIZE A	DC1203A	REV. 1
--------	---------	--------

SHT 1 of 1

REVISIONS		
REV	DESCRIPTION	DATE