



REVISION HISTORY			
ECO	REV	DESCRIPTION	APP. ENG.
-	3	PRODUCTION	GLEN B.
			04-11-16




LAYERING STRUCTURE



NOTES :

1. FAB PER IPC-A-600.
2. MATERIAL: EPOXY FIBERGLASS, NELCO 4000-13EP SI
-FINISHED THICKNESS TO BE 0.062" +/- .003"
-TOTAL OF 4 LAYERS WITH 2 OZ. CU ON THE OUTER LAYERS AND 1 OZ. CU ON THE INNER LAYERS.
-FLAMMABILITY RATING: 94 V-0 MINIMUM.
3. SIZE: CUT TO DIMENSIONS AND TOLERANCES SHOWN.
0.00" ARE PRIMARY DATUMS.
4. DRILLING: -DRILL HOLES PER SCHEDULE. PLATE THROUGH HOLES WITH COPPER, 0.001" THICK MIN.
-ALL HOLE SIZES ARE SPECIFIED AFTER PLATING.
-HOLE LOCATION TOLERANCES ARE +/-0.003" IN RELATION TO CENTER
5. FINISH: -SMOBC USING LPI BOTH SIDES, COLOR GREEN.
-GOLD IMMERSION BOTH SIDES.
-FOR SILKSCREENS: USE WHITE NON-CONDUCTIVE INK.
7. DO NOT ALTER ARTWORK e.g. TO ADD LOGO OR DATE CODE.
PAD SIZE CAN BE MODIFIED TO MEET END FINISH.
8. PCBs ARE TO BE RoHS COMPLIANT.
9. SCORING FOR PANELIZED PCB (PRODUCTION FAB ONLY):

SIZE	QTY	SYM	PLATED	TOL
0.095	4	+	YES	+/-0.003
0.008	265	X	YES	+/-0.003
0.04	10	□	YES	+/-0.003
0.187	4	◇	N0	+/-0.003
0.012	37	⊗	N0	+/-0.003
0.02	1	⊗	N0	+/-0.003
0.005	6	⊕	YES	+/-0.003



UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES:
0.XX" = ±0.01"
0.XXX" = ±0.005"
INTERPRET DIM AND TOL
PER ASME Y14.5M-1994
THIRD ANGLE PROJECTION

APPROVALS

PCB DES.	AK
APP ENG.	GLEN B.
SCALE = NONE	

1630 MCCARTHY BLVD
MILPITAS, CA 95035
PH: (408)432-1800
www.linear.com
LTC CONFIDENTIAL -
FOR CUSTOMER USE ONLY

TITLE: FABRICATION DRAWING
TRANSIMPEDANCE AMPLIFIER

SIZE	IC NO.	LTC626X	REV
N/A		DEMO CIRCUITS 2414A	3
FILENAME:	DC2414A-2.PCB		

SHT 1 OF 1