


REVISION HISTORY				
ECO	REV	DESCRIPTION	APP. ENG.	DATE
-	1	PRODUCTION	CUYLER L.	10-08-14


NOTES: UNLESS OTHERWISE SPECIFIED

1. WORKMANSHIP SHALL BE IN ACCORDANCE WITH IPC-A-610.
2. ASSEMBLY PROCESS SHALL INCLUDE: REFLOW SOLDER BOTH SIDE SMD. MAXIMUM SOLDER TEMPERATURE IS 240 DEGREES CELSIUS.
3. PARTS TO OMIT WILL BE SPECIFIED ON THE BILL OF MATERIALS. LOCATIONS OF OMITTED PARTS SHALL BE FREE OF SOLDER. MASK THE SOLDER STENCIL WHERE SMT PARTS ARE OMITTED.
4. NO SHUNTS
5. DEPANELIZE BOARDS AFTER ASSEMBLY AND ROUTE-OUT THE BREAKOUT TABS ON FOUR SIDES OF THE BOARD EDGE.
6. DO NOT APPLY ANY KIND OF ASSEMBLY STAMP OR QA STAMP TO ANY BOARD.
7. MARK EACH LTC PART NUMBER AND ASSEMBLY TYPE WITH BLACK PERMANENT MARKER AS SHOWN IN TABLE BELOW:

ASSY	U1	VOUT
-A	LTC6655BHLS8-2.5#PBF	2.5V
-B	LTC6655BHLS8-4.096#PBF	4V
-C	LTC6655BHLS8-5#PBF	5V



TOP SILKSCREEN
 LINEAR TECHNOLOGY DATE: 10-08-14
 DC2095A LTC6655BHLS8
 0.25ppm NOISE,
 LOW DRIFT PRECISION REFERENCE

APPROVALS		 1630 MCCARTHY BLVD MILPITAS, CA 95035 PH: (408)432-1900 www.linear.com LTC CONFIDENTIAL- FOR CUSTOMER USE ONLY		
PCB DES.	AK			
APP ENG.	CUYLER L.	TITLE: TOP ASSEMBLY DRAWING 0.25 PPM NOISE LOW DRIFT PRECISION REFERENCE		
		SIZE	IC NO. LTC6655BHLS8	REV.
		N/A	DEMO CIRCUIT 2095A	2
SCALE = NONE		FILENAME: DC2095A-2.PCB		SHT 1 OF 2