
TEMPERATURE & HUMIDITY TEST REPORT

Eterna™ 1 & 2

Prepared for:

Christophe Niglio
Linear Technology, Corp.
30695 Huntwood Avenue
Hayward, CA 94544
Phone (510) 400-2900
cniqlio@dustnetworks.com

Reliant Labs, Inc.
925 Thompson Place • Sunnyvale, California • 94085
Phone 408.737.7500 • Fax 408.850.1852 • reliantlabs.com

Temperature & Humidity Test Report

Document Number 2253

Test Dates: 01/ 07 - 01/12/2013

Eterna 1 & 2

Testing Performed for:

Christophe Niglio
Linear Technology, Corp.
30695 Huntwood Avenue
Hayward, CA 94544

Phone: (510) 400 - 2900
Email: cniglio@dustnetworks.com

Testing Performed by:

Reliant Labs, Inc.
Carlos Carcamo
925 Thompson Place
Sunnyvale, CA 94085

Phone: (408) 737 - 7500
Fax: (408) 850 - 1852
Email: carlos@reliantlabs.com

Reference Documents			
Document	Revision	Number	Date Issued
Service Proposal	-	SV3632	01/02/2013

Table of Contents:

- 1. Products Tested..... 4
- 2. Test Equipment and Calibration Records..... 5
- 3. Functional Test Description & Test Results..... 5
- 4. Temperature and Relative Humidity Profile..... 5
- 5. Temperature and Humidity Profile and Chamber Data..... 6
- 6. Test Setup Pictures 8

1. Products Tested

The units subjected to the temperature and humidity process are documented below.

Table 1: Product Identification

Description	Model	Mac Address	Fixture #
DC9001A	Not a UUT	00-17-0D-00-00-3F-F5-16	-
LTP5900	Eterna 1	00-17-0D-00-00-3F-F8-8C	36
LTP5901	Eterna 2	00-17-0D-00-00-3F-F7-80	24
LTP5900	Eterna 1	00-17-0D-00-00-3F-F8-96	26
LTP5900	Eterna 1	00-17-0D-00-00-3F-F8-85	35
LTP5902	Eterna 2	00-17-0D-00-00-3F-F6-C3	4
LTP5902	Eterna 2	00-17-0D-00-00-3F-F6-B7	5
LTP5900	Eterna 1	00-17-0D-00-00-3F-F8-77	34
LTP5901	Eterna 2	00-17-0D-00-00-3F-F7-81	21
LTP5902	Eterna 2	00-17-0D-00-00-3F-F6-C2	3
LTP5902	Eterna 2	00-17-0D-00-00-3F-F6-C4	2
LTP5901	Eterna 2	00-17-0D-00-00-3F-F7-82	20
LTP5900	Eterna 1	00-17-0D-00-00-3F-F8-9B	33
LTP5901	Eterna 2	00-17-0D-00-00-3F-F7-7E	22
LTP5902	Eterna 2	00-17-0D-00-00-3F-F6-99	1
LTP5902	Eterna 2	00-17-0D-00-00-3F-F6-C5	6
LTP5901	Eterna 2	00-17-0D-00-00-3F-F7-B6	19
LTP5901	Eterna 2	00-17-0D-00-00-3F-F7-77	23
LTP5900	Eterna 1	00-17-0D-00-00-3F-F8-95	25
DC9001A	Not a UUT	00-17-0D-00-00-3F-FF-BD	-
LTP5901	Eterna 2	00-17-0D-00-00-3F-F7-B3	15
LTP5900	Eterna 1	00-17-0D-00-00-3F-F8-84	30
LTP5902	Eterna 2	00-17-0D-00-00-3F-F6-8F	8
LTP5901	Eterna 2	00-17-0D-00-00-3F-F7-AE	18
LTP5902	Eterna 2	00-17-0D-00-00-3F-F6-D1	9
LTP5900	Eterna 1	00-17-0D-00-00-3F-F8-8E	28
LTP5900	Eterna 1	00-17-0D-00-00-3F-F8-87	32
LTP5901	Eterna 2	00-17-0D-00-00-3F-F7-B5	16
LTP5902	Eterna 2	00-17-0D-00-00-3F-F6-B1	10
LTP5901	Eterna 2	00-17-0D-00-00-3F-F7-B4	13
LTP5900	Eterna 1	00-17-0D-00-00-3F-F8-7F	29
LTP5901	Eterna 2	00-17-0D-00-00-3F-F7-AF	14
LTP5902	Eterna 2	00-17-0D-00-00-3F-F6-C6	11
LTP5900	Eterna 1	00-17-0D-00-00-3F-F8-AB	31
LTP5900	Eterna 1	00-17-0D-00-00-3F-F8-AE	27
LTP5901	Eterna 2	00-17-0D-00-00-3F-F7-7D	17
LTP5902	Eterna 2	00-17-0D-00-00-3F-F6-95	7
LTP5902	Eterna 2	00-17-0D-00-00-3F-F6-C7	12

2. Test Equipment and Calibration Records

Equipment used to conduct the testing is detailed below. All test equipment that requires periodic calibration was in current calibration at time of test. The calibration certifications are traceable to the National Institute of Standards and Technology (NIST).

Table 2: Reliant Labs Calibration Records - Lab 6

Description	Manufacturer	Model Number	Serial Number	Calibration Due
Temp/Humidity Chamber	Espec	ESX-3CA	0110463	09/18/2013

3. Functional Test Description & Test Results

The units were operational and monitored for functionality throughout the temperature and humidity testing via Tera Term. The 'sm' command was executed to verify the 'Joins' counter was 1 on all the UUTs.

Test Results: The UUTs remained operational and the 'Joins' counter remained at 1 on all the UUTs throughout the test.

4. Temperature and Relative Humidity Profile

- Test based on IEC 61298-3
- Stabilize chamber at 25°C / 50%RH (2hrs)
- Ramp from 25°C to 40°C at constant 50%RH (.5hrs)
- Dwell at 40°C / 50%RH with UUT powered on (24hrs)
- Ramp from 50%RH to 93%RH at 40°C with UUT powered off (3hrs)
- Dwell at 40°C / 93%RH with UUT powered off (48hrs)
- Dwell at 40°C / 93%RH with UUT powered on (8hrs)
- Ramp from 93%RH to 50%RH at 40°C with UUT powered on (3hrs)
- Dwell at 40°C / 50%RH with UUT powered on (24hrs)

5. Temperature and Humidity Profile and Chamber Data




Figure 1 Temperature and Humidity Profile Chart




Figure 2 Temperature and Humidity Chamber Data Chart

6. Test Setup Pictures



Figure 3 Test Samples in Chamber



Figure 4 Test Samples in Chamber - Close-up



Figure 5 Test Equipment and Chamber Setup