

Xgpro v8.01

File(F) Select IC(S) Project(P) Device(D) Tools(V) Help(H) Language(L)



Select IC

24C01

IC Information(No Project opened)

ChipType: EEPROM ChkSum: 0x0000 2BD4
IC Size: 0x80 Bytes (128 Bytes)

Set Interface

ZIF socket ICSP port ICSP_VCC Enable

8 Bits 16 Bits

Addr...	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F	ASCII
000-000	31	2F	30	31	2F	39	33	00	00	00	3F	F0	03	A2	DF	36	1/01/93...?...6
000-001	88	DD	3F	F0	2F	EB	5C	9B	FB	F8	3F	F0	0B	CE	5D	C7	..?./\...?...]
000-002	D5	A4	EE	C0	00	00	00	00	00	00	00	00	00	00	00	00
000-003	02	32	30	30	58	2D	31	38	30	31	00	4E	43	43	31	37	.200X-1801.NCC17
000-004	30	31	20	00	00	00	00	00	00	00	00	00	FC	5F	01	01	01
000-005	FF	FD	01	02	FF	FC	01	02	FF	FC	01	02	FF	FC	01	02
000-006	FF	FC	01	02	FF	FC	01	02	FF	FC	01	02	FF	FC	01	02
000-007	FF	FC	01	02	FF	FC	30	37	2F	30	31	2F	31	36	00	3007/01/16.0

USB
1
24C0
Me
Prog
TL86
1

Flash Device Info

Options

Pin Detect Check ID
 Erase before
 Verify after Auto SN_NUM
 Skip Addr. Range: ALL Sect
 Blank 0x000000 ->000000

IC Config Informaton

Ready

Hardware Interface Ver: TL866II-Plus

0000 00