

# 7075 Eight 1×12 Two-Pole Multiplexer Card

**MULTIPLEX CONFIGURATION:** Eight 1×12 banks. Adjacent banks can be connected together. Jumpers can be removed to isolate any bank from the backplane.

**CONTACT CONFIGURATION:** 2-pole Form A (HI, GUARD).

**CONNECTOR TYPE:** 25-pin subminiature D connector, eight for bank connection, one for row connection.

**MAXIMUM SIGNAL LEVEL:**

**DC Signals:** 110V DC pin to pin, 1A switched, 30VA (resistive load).

**AC Signals:** 175V AC peak pin to pin, 1A switched, 60VA (resistive load).

**COMMON MODE VOLTAGE:** 110V DC, 175V AC peak pin-to-pin or pin-to-chassis.

**CONTACT LIFE:**

**Cold Switching:** 10<sup>8</sup> closures.

**At Maximum Signal Level:** 10<sup>5</sup> closures.

**CHANNEL RESISTANCE (per conductor):** <0.60Ω initial, <1.5Ω at end of contact life.

**CONTACT POTENTIAL:** <5μV per contact pair (HI to GUARD).

**OFFSET CURRENT:** <100pA (HI to GUARD).

**CROSSTALK (1MHz, 50Ω load):**

**Bank:** <-60dB.

**Channel:** <-60dB.

**INSERTION LOSS (1MHz, 50Ω source, 50Ω load):** 0.1dB typical.

**3dB BANDWIDTH (50Ω load):**

Configured as 1×12: 30MHz typical.

Configured as 1×96: 2.5MHz typical.

**ISOLATION:**

**Bank:** >10<sup>10</sup>Ω, <3pF

**Channel:** >10<sup>10</sup>Ω, <5pF

**Differential:**

Configured as 1×12: >10<sup>9</sup>Ω, <100pF nominal.

Configured as 1×96: >10<sup>8</sup>Ω, <600pF nominal.

**Common Mode:**

Configured as 1×12: >10<sup>9</sup>Ω, <165pF nominal.

Configured as 1×96: >10<sup>8</sup>Ω, <700pF nominal.

**RELAY DRIVE CURRENT (per relay):** 28mA.

**RELAY SETTLING TIME:** <3ms.

**EMC:** Conforms to European Union Directive 89/336/EEC.

**SAFETY:** Conforms to European Union Directive 73/23/EEC (meets EN61010-1/IEC 1010).

**ENVIRONMENT:**

**Operating:** 0° to 50°C, up to 35°C at 70% R.H.

**Storage:** -25° to 65°C.

**ACCESSORY SUPPLIED:** Instruction manual, jumpers for multiplexer expansion.

**ACCESSORIES AVAILABLE:**

7076-RMTC High Isolation Row Cable Assembly,  
3m (10 ft)

7076-CMTC High Isolation Column/Bank Cable  
Assembly, 3m (10 ft)

7075-MTC\* Row/Column/Bank Standard Cable  
Assembly, 3m (10 ft)

\* Standard cable can be used for either row or column connection.

Specifications are subject to change without notice.

