

Measurements International

Metrology is Our Science, Accuracy is Our Business™

RESISTANCE TRANSFER STANDARD

MODEL 9316 & 9317

- High Stability
- 1 MΩ & 10 MΩ/Step
- Matched to < 10 ppm
- Low Temperature Coefficient
- Eliminates Oil/Air Bath Requirement



MODEL 9316/9317 RESISTANCE TRANSFER STANDARD

The model 9316/9317 Resistor Transfer Standard consists of 11 equal steps of 1 M Ω , (9316) and 10 M Ω , (9317). Specially designed toggle switches isolate each resistor and allows the standard to be configured in series, parallel, series-parallel, or separately without the use of external shorting bars.

Precise transfer measurements up to 110 M Ω relative to a single 100 k Ω resistance standard can be obtained with the MI 9316/9317 Resistance Transfer Standard. Based on a unique method for establishing known ratios, the 9316/9317 utilizes a transfer technique that consists of switching resistance elements in series, parallel or series-parallel selections.

Insulation leakage paths (other than those within each resistance section) are from the external terminals to ground. By utilizing three-terminal measurement techniques insulation leakage errors in the transfer of calibration from one resistance level to another are minimized.





Measurements International

Metrology is Our Science, Accuracy is Our Business™

MODEL 9316/9317 RESISTANCE TRANSFER STANDARD

Specifications: Rev 4

Model	9316	9317
Initial Accuracy	± 25 ppm	± 30 ppm
Short Term Stability*	± 2 ppm	± 2 ppm
1 Year Stability	± 30 ppm	± 35 ppm
2 Year Stability	± 50 ppm	± 50 ppm
Temperature Coefficient	≤±5 ppm/°C	≤ ± 5 ppm/°C
Leakage Resistance: Terminal to Case	> 10 ¹³ Ω	> 10 ¹³ Ω
Power Rating	1 W/Step (2.5 kV Max)	1 W/Step (2.5 kV Max)
Breakdown Voltage	5 kV	5 kV

^{*}Limited to 48 hours values repeatability at 23 °C ± 0.05 °C

Dimensions (L \times W \times H): Weight:

457 × 152 × 173 (mm) 4.5 kg 9 kg

Main Power:

N/A

Corporate Headquarters Measurements International

PO Box 2359, 118 Commerce Drive Prescott, Ontario, Canada K0E 1T0

Phone: 613-925-5934 Fax: 613-925-1195 Email: sales@mintl.com Toll Free: 1-800-324-4988 **Worldwide Offices** MI-USA

Phone: 407-706-0328 Email: sales@mintl.com

MI-China

Email: sales@mintl.com

MI-Europe

Phone: +(420) 731-440-663 Email: sales@mintl.com

MI-Japan

Phone: +(86) 10-64459890 Phone: +(81) 72 39 64 660 Email: kaz@mijpn.com

MI-India

Phone: +(91) 98 10 134 932 Email: sales@MILLP.co.in

Shipping Weight:



www.mintl.com