## Gated Integrators and Boxcar Averagers

SR235 — Analog processor (2-channel)



- · 36 functions
- · Dual inputs
- · Post filtering and gain adjustment
- · 2 % basic accuracy

· SR235 ... \$1500 (U.S. list)

## **SR235 Analog Processor**

The SR235 Analog Processor provides a variety of convenient signal processing functions on one or two inputs. Background subtraction, ratioing and logarithmic compression are just a few of the functions which can be implemented with the SR235. With its many output functions, high accuracy, and variable filtering and gain, the SR235 is the perfect addition for any boxcar system—especially those in which a computer is unavailable to perform signal processing.

The SR235 outputs a voltage proportional to a function of an argument formed from its two inputs (A and B). Allowable arguments are: A, B,  $\sqrt{(A^2 + B^2)}$ , A – B, A × B / 10, and 10A / |B|. The functions that can be selected are: x,  $x^2$ ,  $\sqrt{x}$ ,  $\ln|x|$ , -dx/dt, and -(dx/dt) / 100. Filtering can be performed on the argument with time constants from 0.3 ms to 30 s.

## **Ordering Information**

SR235 Analog processor \$1500

## **SR235 Specifications**

A and B inputs

protected to 100 V, <2 mV input offset Argument (x)A, B,  $\sqrt{(A^2+B^2)}$ , A-B, A×B/10, 10A/|B| Time constant: 0.3 ms to 30 s (1-3-10 Argument filter seq.) When OFF, argument is unfiltered. Gain 0.1 to 20 in a 1-2-5 sequence  $x, x^2, \sqrt{x}, \ln|x|, -\frac{dx}{dt}, -\frac{(dx}{dt})/100$ F(x) output -dx/dt to 10 Hz, -(dx/dt)/100 to 1 kHz, Frequency range  $\sqrt{(A^2+B^2)}$  to 20 Hz, all others to 50 kHz Gain, 2%; rms sum, 3%; difference, Accuracy 1%; multiplication, 2% of full scale; division (denominator >0.1), 3 % of full scale;  $\ln |x|$ ,  $x^2$ ,  $\sqrt{x}$  acc. to  $\pm 20 \,\mathrm{mV}$ (ref. to input or output, whichever is less); -dx/dt and -(dx/dt)/100, 5% +24 V/120 mA, -24 V/80 mA, 5 WPower Warranty One year parts and labor on defects



phone: (408)744-9040 www.thinkSRS.com

in materials and workmanship

1 MΩ input impedance,  $\pm 10$  V range,