

Lassen SQ GPS Module

Low-power, micro-sized GPS solution for mobile products

Key Features and Benefits

- 100 mW @ 3.3V
- 26 mm x 26 mm x 6 mm
- TSIP, TAIP and NMEA 0183 protocols
- Flash memory
- Small companion antenna: 20.1 mm x 20 mm x 8 mm
- Antenna short-circuit detection and protection

Trimble's new Lassen™ SQ module adds complete GPS functionality to your mobile product in a postage-stamp-sized footprint with ultra-low power consumption. The module is designed for portable handheld, battery-powered applications such as cell phones, pagers, PDAs, digital cameras, and many others.

Using Trimble's breakthrough FirstGPS™ architecture, the module delivers complete position, velocity and time (PVT) solutions for use in the host application. The Lassen SQ module uses minimal power and space and delivers a robust, reliable PVT solution.

The Lassen SQ module is the only stamp-sized GPS product with the two most popular standard protocols: TSIP (Trimble Standard Interface Protocol) and NMEA 0183. The module is enclosed within a metal shield for ease of handling. The shield acts as a protective case.

FirstGPS Architecture

The FirstGPS architecture consists primarily of two integrated circuits and FirstGPS firmware. This technology enables the Lassen SQ to achieve the unique combination of both ultra-low power usage and micro-size in the same unit.

Hardware

The Lassen SQ module packages this architecture in a tiny form



Lassen SQ GPS receiver with metal shield

factor, (approximately 26 mm x 26 mm, including the metal shield). It typically requires only 100 mW of power (at 3.3 VDC). Total typical power usage, including the Trimble 3.3 VDC miniature antenna, is ≤ 133 mW.

The highly integrated module is a miniature board containing a GPS hardware core based on Trimble's Colossus™ RF ASIC and IO-S digital signal processor (DSP) design and a 32-bit RISC CPU. The module offers onboard data storage in flash memory for complete processing capability.

Antennas

The Lassen SQ module is compatible with active, 3.3 VDC antennas. Three such antennas are available

from Trimble and are recommended for use according to your application:

- An ultra-compact embedded antenna, approximately the same size as the module itself. This antenna is unpackaged, for easy integration into mobile applications.
- A compact, unpackaged antenna slightly larger than the ultra-compact model above.
- A compact, packaged antenna with magnetic mount for flexible, movable installation.

Starter Kit

The Lassen SQ Starter Kit provides everything you need to get started integrating state-of-the-art GPS capability into your application.

Lassen-SQ GPS Module

Low-power, micro-size GPS solution for mobile products

KEY FEATURES

- Ultra-low power consumption: 100 mW @ 3.3 V
- Small, thin-model design: 26 mm W x 26 mm L x 6 mm H (1.02" x 1.02" x 0.24")
- TSIP & NMEA protocols
- Flash memory
- Small companion antennas
- Antenna short-circuit detection and protection

PERFORMANCE SPECIFICATIONS

General:	L1 (1575.42 MHz) frequency, C/A code, 8-channel, continuous tracking receiver, 32 correlators
Update Rate:	TSIP @ 1 Hz; NMEA @ 1 Hz; TAIP @ 1 Hz
Accuracy:	Horizontal: <6 meters (50%), <9 meters (90%) Altitude: <11 meters (50%), <18 meters (90%) Velocity: 0.06 m/sec PPS: ±95 nanoseconds
Acquisition:	Reacquisition:<2 sec. (90%) Hot Start: <14 sec (50%), <18 sec (90%) Warm Start: <38 sec (50%), <45 sec (90%) Cold Start: <90 sec (50%), <170 sec (90%) Cold start requires no initialization. Warm start implies last position, time and almanac are saved by backup power. Hot start implies ephemeris also saved.
Dynamics:	Acceleration: 4g (39.2 m/sec ²) Motional jerk: 20 m/sec ³
Operational Limits:	Altitude <18000m or velocity <515m/s (COCOM limit) Either limit may be exceeded but not both

INTERFACE CHARACTERISTICS

Connectors:	I/O: 8-pin (2x4) male header, micro terminal strip ASP 69533-01 or similar RF: Low-profile coaxial connector H.FL-R-SMT (10), 50 Ohm
Serial Port:	1 serial port (transmit/receive)
PPS:	3.3 V CMOS-compatible, TTL-level pulse Once per second with the rising edge of the pulse synchronized with UTC
Protocols:	TSIP @ 9600 baud, 8 Bits NMEA 0183 v3.0, selectable baud rate, 8 Bits TAIP @ selectable baud rate, 8 Bits
NMEA Messages:	GGA, VTG, GLL, ZDA, GSA, GSV and RMC Messages selectable by TSIP command; selection stored in flash memory

ELECTRICAL CHARACTERISTICS

Prime Power:	+3.0 VDC to +3.6 VDC (3.3 V typ.)
Power Consumption:	GPS board only: 100 mW @ 3.3 V w/embedded ant.: 133.3 mW @ 3.3 V
Backup Power:	+2.5.VDC to +3.6VDC
Ripple Noise:	Max 60 mV, peak-to-peak from 1 Hz to 1 MHz
Antenna Fault Protection:	Short-circuit detection and protection

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature:	-40°C to +85°C
Storage Temperature:	-55°C to +105°C
Vibration	0.008 g ² /Hz 5 Hz to 20 Hz 0.05 g ² /Hz 20 Hz to 100 Hz -3 dB/octave 100 Hz to 900 Hz
Operating Humidity	5% to 95% R.H. non-condensing @ +60°C

PHYSICAL CHARACTERISTICS

Enclosure:	Metal enclosure with solder mounting tabs
Outside Dimensions:	26 mm W x 26 mm L x 6 mm H (1.02" x 1.02" x 0.24")
Weight:	Approximately 5.7 grams (0.2 ounce) including the shield

ORDERING INFORMATION & ACCESSORIES

Module
Lassen SQ module, in metal enclosure with solder mounting tabs

Lassen SQ Starter Kit
Includes Lassen SQ module mounted on interface board in metal enclosure, Compact magnetic-mount antenna, AC/DC power adapter, Serial interface cable, Reference manual and GPS toolkit software supplied on a CD-ROM

Transition cable:
RF cable for connecting antennas with MCX connector to on-module RF connector. Cable length: 10 cm



Ultra-Compact Embedded Antenna:
3.3V active miniature unpackaged antenna
Cable length: 8 cm
Dim: 22 mm W x 21 mm L x 8 mm H (0.866" x 0.827" x 0.315")
Connector: HFL; mates directly to on-module RF connector



Compact Unpackaged Antenna:
3V active micropatch unpackaged antenna
Cable length: 11 cm
Dim: 34.6 mm W x 29 mm L x 9 mm H (1.362" x 1.141" x 0.354")
Connector: MCX; mates with optional RF transition cable to on-module RF connector



Compact Magnetic-Mount Antenna:
3V active micropatch antenna with magnetic mount
Cable length: 5 m
Dim: 42 mm W x 50.5 mm L x 13.8 mm H (1.65" x 1.99" x 0.55")
Connector: MCX, mates through the optional RF transition cable to the module RF connector

Specifications subject to change without notice



Trimble Navigation Limited
Corporate Headquarters
645 North Mary Avenue
Sunnyvale, CA 94085
1-800-827-6668
+1-408-481-7920
www.trimble.com

Trimble Navigation Europe
Limited
Trimble House
Meridian Office Park
Osborne Way
Hook, Hampshire RG27 9HX
U.K.
+44 1256-760-150

Trimble Navigation
Australia PTY Limited
P.O. Box 769
Spring Hill QLD 4004
Australia
+61-7-3216-0044

Trimble Export Limited
27th Fl., Korea World Trade Center,
159-1,Samsung-dong,Kangnam-gu
Seoul, 135-729
South Korea
Phone: 82-2-551-2730
Fax: 82-2-551-2720
korea_sales@trimble.com

Trimble Navigation Ltd
Suite 7B, Jinlin Plaza, 666 Fuzhou Road
Shanghai, 200001 China
Phone: 86-21-6391-7814
Fax: 86-21-6391-7834

