Version: 2.0

Date of Issue: 05 May 2017

Date of First Issue: 03 September 2012

**SECTION 1: IDENTIFICATION** 



www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Product identifier used on the label

Gagekote 5 Part B

Other means of identification

Not applicable

Recommended use of the chemical and restrictions

on use

Recommended use Epoxy / Urethane Resin
Restrictions on use Epoxy and Anything other than the above.

Details of the supplier of the safety data sheet

Supplier VISHAY MEASUREMENTS GROUP, INC.

Address of Supplier Post Office Box 27777
Raleigh, NC 27611

USA

 Telephone
 +1 919-365-3800

 Fax
 +1 919-365-3945

 E-Mail (competent person)
 mm.us@vishaypg.com

Emergency telephone number 1-800-424-9300 CHEMTREC (24 hours)

## SECTION 2: HAZARD(S) IDENTIFICATION

Classification of the substance or mixture in accordance with paragraph (d) of 29 CFR 1910.1200

Physical hazards Not classified

Health hazards Skin Corrosion/Irritation, Category 2
Skin Sensitisation, Category 1

Eye Irritation, Category 2

Environmental hazards Hazardous to the aquatic environment, Chronic, Category 2

Hazard Symbol





Signal Word(s) DANGER

Hazard Statement(s) Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

Toxic to aquatic life with long lasting effects.

Precautionary Statement(s) Wash hands and exposed skin thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN: Wash with plenty of water.

If skin irritation occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Other hazards None known.

Percent of the mixture consists of ingredient(s) of

unknown acute toxicity:

0%

14018 Page: 1 of 7

Version: 2.0

Date of Issue: 05 May 2017

Date of First Issue: 03 September 2012



www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substances Not applicable

Mixtures Substances in preparations / mixtures

Chemical identity of the substance	%W/W	CAS No.	EC No.	Hazard classification
Phenol, polymer with formaldehyde, glycidyl ether	<60	28064-14-4	608-164-0	Skin Corrosion/Irritation, Category 2 Skin Sensitisation, Category 1 Eye Irritation, Category 2 Hazardous to the aquatic environment, Chronic, Category 2
$\begin{tabular}{ll} Poly[oxy(methyl-1,2-ethanediyl)],\\ \alpha-(2-oxiranylmethyl)-\omega-(2-oxiranylmethoxy)- \end{tabular}$	30 - 35	26142-30-3	607-873-2	Skin Corrosion/Irritation, Category 2 Skin Sensitisation, Category 1 Eye Irritation, Category 2
Talc	20 - 25	14807-96-6	238-887-9	Not classified

## **SECTION 4: FIRST AID MEASURES**



#### Description of first aid measures

Self-protection of the first aider

Inhalation

Skin Contact

**Eve Contact** 

Ingestion

Most important symptoms and effects, both acute and delayed

Indication of any immediate medical attention and special treatment needed

Use personal protective equipment as required. Wear appropriate personal protective equipment, avoid direct contact. Ensure adequate ventilation. Avoid

breathing vapours. Avoid contact with skin, eyes or clothing.

If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Apply artificial respiration if breathing has ceased or

shows signs of failing. Get medical advice/attention if you feel unwell. IF ON SKIN (or hair): After contact with skin, take off immediately all

contaminated clothing, and wash immediately with plenty of soap and water. If

irritation (redness, rash, blistering) develops, get medical attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate with eyewash solution or clean water, holding the eyelids apart, for at least 15 minutes.

Immediately call a POISON CENTER/doctor.

Rinse mouth with water (do not swallow). Do NOT induce vomiting. If vomiting occurs turn patient on side. Never give anything by mouth to an unconscious person. IF exposed or concerned: Call a POISON CENTER/doctor.

Causes skin irritation. Causes eye irritation. May cause an allergic skin reaction.

Treat symptomatically.

#### **SECTION 5: FIRE-FIGHTING MEASURES**

#### **Extinguishing media**

Suitable Extinguishing Media

Unsuitable extinguishing Media

Special hazards arising from the substance or mixture

Special protective equipment and precautions for fire fighters

As appropriate for surrounding fire. Extinguish preferably with foam, carbon dioxide or dry chemical.

Do not use water jet. Direct water jet may spread the fire.

Not flammable. May decompose in a fire giving off toxic fumes. Combustion products: Carbon monoxide, Carbon dioxide

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Do not breathe fumes. Keep containers cool by spraying with water if exposed to fire. Avoid run off to waterways and sewers.

14018 Page: 2 of 7

Version: 2.0

Date of Issue: 05 May 2017

Date of First Issue: 03 September 2012

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

www.vishaypg.com



## SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Wear appropriate personal protective equipment, avoid direct contact. Ensure operatives are trained to minimise exposures. Contaminated clothing should be laundered before reuse. Ensure adequate ventilation. Avoid breathing vapours. Avoid contact with skin,

eyes or clothing.

Large spillages: Evacuate the area and keep personnel upwind. Only trained and properly

protected personnel must be involved in clean-up operations.

Avoid release to the environment. Do not allow to enter drains, sewers or

watercourses.

Methods and material for containment and cleaning

Contain spillages with sand, earth or any suitable adsorbent material. Sweep or shovel-up spillage and remove to a safe place. Transfer to a container for

disposal or recovery.

Small spillages: Allow small spillages to evaporate provided there is adequate ventilation. Large spillages: Only trained and properly protected personnel must be involved in clean-up

operations.

#### **SECTION 7: HANDLING AND STORAGE**

Precautions for safe handling Ensure operatives are trained to minimise exposures. Ensure adequate

ventilation. Wear appropriate personal protective equipment, avoid direct contact. Avoid breathing vapours. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Keep good industrial hygiene. Wash hands thoroughly after handling. Contaminated clothing should be thoroughly cleaned. Do not eat, drink or smoke at the work

place. Keep from direct sunlight.

Conditions for safe storage, including any

incompatibilities Storage temperature Incompatible materials Keep only in original container. Store in a cool/low-temperature, well-ventilated (dry) place away from heat and ignition sources.

Store at ambient temperature.

Strong oxidising agents, Acids and Bases.

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Occupational Exposure Limits**

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m³)	STEL (ppm)	STEL (mg/m³)	Note
Talc						NIOSH
(containing no asbestos and less than	-	2	-	-	Respirable Dust	
	14007-90-0	20 mppcf*	-	-	-	OSHA
1% quartz)		-	2	-	-	ACGIH, A4

Note: OSHA PELs 1910.1000 TABLE Z-3/ NIOSH RELs / ACGIH TLVs

A4: Not Classifiable as a Human Carcinogen: Agents which cause concern that they could be carcinogenic for humans but which cannot be assessed conclusively because of the lack of data. In vitro or animal studies do not provide indications of carcinogenicity which are sufficient to classify the agent into one of the other categories.

\*Mppcf: Millions of particles per cubic foot of air

The other components listed in Section 3 do not have occupational exposure limits.

Not established **Biological Exposure Indices** 

Appropriate engineering controls Ensure adequate ventilation. Store in a cool/low-temperature, well-ventilated

(dry) place away from heat and ignition sources. Atmospheric levels should be

controlled in compliance with the occupational exposure limit.

Individual protection measures, such as personal Keep good industrial hygiene. Wear appropriate personal protective equipment,

14018 Page: 3 of 7

Version: 2.0

Date of Issue: 05 May 2017

Date of First Issue: 03 September 2012



www.vishaypg.com

#### ACCORDING TO OSHA HCS (29 CFR 1910.1200)

#### protective equipment (PPE)

avoid direct contact. Avoid breathing vapours. Avoid contact with skin, eyes or clothing. IF exposed: Wash immediately with water. Wash contaminated clothing before reuse. Do not eat, drink or smoke at the work place.

Eye/face protection



Wear protective eye glasses for protection against liquid splashes. Wear eye protection with side protection (EN166).

Skin protection



#### Hand protection:

Wear impervious gloves (EN374). Protective index 6, corresponding > 480 minutes of permeation time according to EN 374 Gloves should be changed regularly to avoid permeation problems. Breakthrough time of the glove material: refer to the information provided by the gloves' producer. Suitable materials: Butyl rubber, Nitrile rubber, Neoprene.

#### **Body protection:**

Wear impervious protective clothing, including boots, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection



In case of inadequate ventilation wear respiratory protection. A suitable mask with filter type A (EN141 or EN405) may be appropriate. A suitable mask with filter type A (EN141 or EN405) may be appropriate.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

#### Information on basic physical and chemical properties

Appearance Green, thixotropic paste

Odor Slight

Odor Threshold Not established pH Not established

Melting Point/Freezing Point

Not established
Initial boiling point and boiling range

Not established

Flash Point Soling Fland boiling range Not established >150 °C [Closed cup]

Evaporation rate (Butyl acetate = 1)

Not established

Flammability (solid, gas)

Upper/lower flammability or explosive limits

Vapour pressure

LT 1mm Hg

Vapour density

Relative density

Solubility(ies)

Not applicable

Not established

Partly soluble in water.

Partition coefficient: n-octanol/water Not established Auto-ignition temperature Not established Decomposition Temperature Not established

Viscosity Green, thixotropic paste

## **SECTION 10: STABILITY AND REACTIVITY**

 Reactivity
 Stable under normal conditions.

 Chemical stability
 Stable under normal conditions.

Possibility of hazardous reactions Stable under normal conditions. Hazardous polymerisation will not occur.

Conditions to avoid

**Incompatible materials** Strong oxidising agents, Acids and Bases.

Hazardous decomposition product(s) Combustion products: Carbon monoxide, Carbon dioxide

Heat

14018 Page: 4 of 7

Version: 2.0

Date of Issue: 05 May 2017

Date of First Issue: 03 September 2012



www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

#### **SECTION 11: TOXICOLOGICAL INFORMATION**

Information on toxicological effects (Substances in preparations / mixtures)

Acute toxicity - Ingestion Based upon the available data, the classification criteria are not met.

Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg

bw/dav.

Acute toxicity - Inhalation Based upon the available data, the classification criteria are not met.

Acute Toxicity Estimate Mixture Calculation: Estimated LC50 >20.0 mg/l.

Acute toxicity - Skin Contact

Based upon the available data, the classification criteria are not met.

Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg

Based upon the available data, the classification criteria are not met.

bw/day.

Skin corrosion/irritation Skin Corrosion/irritation, Category 2; Causes skin irritation.

**Serious eye damage/irritation** Eye Irritation, Category 2; Causes serious eye irritation.

Respiratory or skin sensitizationSkin Sensitisation, Category 1; May cause an allergic skin reaction.Germ cell mutagenicityBased upon the available data, the classification criteria are not met.CarcinogenicityBased upon the available data, the classification criteria are not met.Reproductive toxicityBased upon the available data, the classification criteria are not met.STOT - single exposureBased upon the available data, the classification criteria are not met.STOT - repeated exposureBased upon the available data, the classification criteria are not met.

Aspiration hazard

Information on likely routes of exposure

InhalationUnlikely – accidental exposureIngestionUnlikely – accidental exposureSkin ContactPossible – accidental exposureEye ContactUnlikely – accidental exposure

Early onset symptoms related to exposure

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye

irritation.

None known

Delayed health effects from exposure

Other information

NTP Report on Carcinogens All chemicals are not listed

IARC Monographs Talc - Group 3: Not classifiable as to its carcinogenicity to humans.

OSHA Designated Carcinogen All chemicals are not listed

#### **SECTION 12: ECOLOGICAL INFORMATION**

**Ecotoxicity** Aquatic Chronic 2; Toxic to aquatic life with long lasting effects.

Estimated Mixture LC50 > 1 to  $\leq$  10 mg/l. (Fish)

**Persistence and degradability**No data for the mixture as a whole. **Bioaccumulative potential**No data for the mixture as a whole.

**Mobility in soil** The product is predicted to have low mobility in soil. Partly soluble in water.

Other adverse effects None known.

#### **SECTION 13: DISPOSAL CONSIDERATIONS**

Waste treatment methods Dispose of this material and its container as hazardous wasteSend after pre-

treatment to a appropriate hazardous waste incinerator facility according to

legislation.

Additional Information Dispose of contents in accordance with local, state or national legislation.

14018 Page: 5 of 7

Version: 2.0

Date of Issue: 05 May 2017

Date of First Issue: 03 September 2012



ACCORDING TO OSHA HCS (29 CFR 1910.1200)

#### **SECTION 14: TRANSPORT INFORMATION**

ADR/RID **IMDG** IATA **UN** number UN 3082 UN 3082 UN 3082

**UN proper shipping name ENVIRONMENTALLY ENVIRONMENTALLY ENVIRONMENTALLY** HAZARDOUS SUBSTANCE, HAZARDOUS SUBSTANCE, HAZARDOUS SUBSTANCE, LIQUID (CONTAINS, Phenol, LIQUID (CONTAINS, Phenol, LIQUID (CONTAINS, Phenol,

polymer with formaldehyde, polymer with formaldehyde, glycidyl ether) glycidyl ether) Transport hazard class(es)

Ш Ш Ш Packing group

**Environmental hazards** Environmentally hazardous Classified as a Marine Environmentally hazardous substance. Pollutant. substance.

Transport in bulk according to Annex Not applicable

II of MARPOL 73/78 and the IBC Code Special precautions for user See Section: 2

#### SECTION 15: REGULATORY INFORMATION

# Safety, health and environmental regulations/legislation specific for the substance or mixture

**US Federal Regulations** 

Phenol, polymer with formaldehyde, glycidyl ether: Exempt from reporting under TSCA (Toxic Substance Control Act)

Poly[oxy(methyl-1,2-ethanediyl)],  $\alpha$ -(2-oxiranylmethyl)- $\omega$ -(2-oxiranylmethoxy)-:

Exempt from reporting under CDR

Talc: Subject to 25,000 lb reporting threshold

All chemicals are not listed EPCRA/SARA Section 302 Extremely Hazardous

Substances

EPCRA Section 313 Toxics Release Inventory (TRI) All chemicals are not listed

NIOSH Occupational Carcinogen List All chemicals are not listed All chemicals are not listed OSHA List of highly hazardous chemicals, toxics and

NTP Report on Carcinogens (RoC) List All chemicals are not listed All chemicals are not listed Poison Prevention Packaging Act

**US State Regulations** 

California State, Proposition 65 List All chemicals are not listed California State, Safer Consumer Products Regulations Talc - Candidate Chemicals List Maine State, Toxic Chemicals in Children's Products Act All chemicals are not listed New Jersey State Worker and Community RTK Act Talc - RTKHSL. SHHSL Pennsylvania State, Worker and Community RTK Act Talc - Hazardous Substance List Rhode Island State, Hazardous Substances RTK Act Talc - Hazardous Substance List

Non-Regional

IARC Monographs, List of Classifications Talc - Group 3: Not classifiable as to its carcinogenicity to humans.

#### **SECTION 16: OTHER INFORMATION**

The following sections contain revisions or new statements: New SDS Regulation compliant with HazCom 2012 format, all sections have been updated to include new information. Please review SDS with care.

Version 2.0

**Revision Date** 05 May 2017 **Date of First Issue** 03 September 2012

#### References:

Existing Safety Data Sheet (SDS) EU Data: the Classification and Labelling Inventory for Phenol, polymer with formaldehyde, glycidyl ether (CAS No. 28064-14-3), Poly[oxy(methyl-1,2-ethanediyl)], α-(2-oxiranylmethyl)-ω-(2-oxiranylmethoxy)- (CAS No. 26142-30-4) and Talc (CAS No. 14807-96-6).

14018 Page: 6 of 7



www.vishaypg.com

polymer with formaldehyde,

glycidyl ether)

Version: 2.0

Date of Issue: 05 May 2017

Date of First Issue: 03 September 2012



www.vishaypg.com

#### ACCORDING TO OSHA HCS (29 CFR 1910.1200)

GHS Classification of the substance or mixture	Classification Procedure		
Skin Corrosion/Irritation, Category 2	Threshold Calculation		
Skin Sensitisation, Category 1	Threshold Calculation		
Eye Irritation, Category 2	Threshold Calculation		
Hazardous to the aquatic environment, Chronic, Category 2	Summation Calculation		

#### **LEGEND**

ACGIH: American Conference of Governmental Industrial Hygienists

BEI: Biological Exposure Indices (ACGIH)

IARC: International Agency for Research on Cancer

Irr: Irritation

NIOSH: National Institute of Occupational Safety and Health

NTP: National Toxicology Program

OSHA: The Occupational Safety & Health Administration

PBT: Persistent, Bioaccumulative and Toxic

PEL: Permissible exposure limit

REL: Recommended exposure limit SCL: Specific Concentration Limit

OL: " D: L (

Skin": Risk of overexposure via dermal contact

STEL: Short Term Exposure Limit

TLV: Threshold Limit value

TSCA: Toxic Substance Control Act TWA: Time Weighted Average URT: Upper respiratory tract

vPvB: very Persistent and very Bioaccumulative

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

#### **Disclaimers**

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Vishay Precision Group gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Vishay Precision Group accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

14018 Page: 7 of 7