Version: 4.0

Date of Issue: 08 May 2017 Date of First Issue: 20 March 2012



www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

SECTION 1: IDENTIFICATION

Product identifier used on the label M-Bond AE Resin

Other means of identification Not applicable

Recommended use of the chemical and restrictions

on use

Recommended use Adhesives.
Restrictions on use None known.

Details of the supplier of the safety data sheet

Supplier VISHAY MEASUREMENTS GROUP, INC.

Address of Supplier Post Office Box 27777
Raleigh, NC 27611

USA

 Telephone
 +1 919-365-3800

 Fax
 +1 919-365-3945

 E-Mail (competent person)
 mm.us@vishaypg.com

Emergency telephone number 1-800-424-9300 CHEMTREC (24 hours)

SECTION 2: HAZARD(S) IDENTIFICATION

Classification of the substance or mixture in accordance with paragraph (d) of 29 CFR 1910.1200

Physical hazards Not classified

Health hazards Skin Corrosion/Irritation, Category 2

Skin Sensitisation, Category 1 Eye Damage, Category 1

Germ cell mutagenicity, Category 2

Specific target organ toxicity — single exposure, Category 1 Specific target organ toxicity — single exposure, Category 2 Hazardous to the aquatic environment, Chronic, Category 3

Hazard Symbol

Environmental hazards







Signal Word(s) DANGER

Hazard Statement(s) Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye damage. Suspected of causing genetic defects.

Causes damage to organs (CNS and blood effects - Oral). May cause damage to organs (Respiratory tract - Oral). Harmful to aquatic life with long lasting effects.

Precautionary Statement(s)

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe vapour.

Wash hands and exposed skin thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

14039 Page: 1 of 8

Version: 4.0

Date of Issue: 08 May 2017 Date of First Issue: 20 March 2012



www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.

IF exposed: Call a POISON CENTER or doctor/physician.

Other hazards None known

Percent of the mixture consists of ingredient(s) of unknown acute toxicity:

0%

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substances Not applicable

Mixtures Substances in preparations / mixtures

Chemical identity of the substance	%W/W	CAS No.	EC No.	Hazard classification
Bis-[4-(2,3-epoxipropoxi)phenyl] propane	< 75	1675-54-3	216-823-5	Skin Corrosion/Irritation, Category 2 Skin Sensitisation, Category 1
				Eye Irritation, Category 2
Bisphenol A Diglycidyl Ether	15 – 25	25085-99-8	-	Skin Corrosion/Irritation, Category 2
				Skin Sensitisation, Category 1 Hazardous to the aquatic environment, Chronic, Category 2
2,3-Epoxypropyl o-tolyl ether	< 5	2210-79-9	218-645-3	Skin Corrosion/Irritation, Category 2
				Skin Sensitisation, Category 1
				Germ cell mutagenicity, Category 2 Hazardous to the aquatic environment, Chronic, Category 2
Resorcinol	< 5	108-46-3	203-585-2	Acute toxicity, Category 4 – Oral
				Skin Corrosion/Irritation, Category 2
				Eye Damage, Category 1
				Skin Sensitisation, Category 1B
				Specific target organ toxicity — single exposure, Category 1
				Specific target organ toxicity — single exposure, Category 2
				Hazardous to the aquatic environment, Acute, Category 1
				Hazardous to the aquatic environment, Chronic, Category 1

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Self-protection of the first aider

Inhalation

Skin Contact

Eye Contact

Ingestion

Use personal protective equipment as required. Wear appropriate personal protective equipment, avoid direct contact. Ensure adequate ventilation. Avoid

all contact. Do not breathe vapour.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention.

IF ON SKIN: Remove contaminated clothing and wash all affected areas with plenty of water. If irritation (redness, rash, blistering) develops, get medical attention. IF exposed or concerned: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

IF SWALLOWED: Rinse mouth. Make victim drink plenty of water. Do not induce vomiting unless instructed to do so by medical personnel. Call a POISON

14039 Page: 2 of 8

Version: 4.0

Date of Issue: 08 May 2017 Date of First Issue: 20 March 2012 MICROE MEASUREMENTS

www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Most important symptoms and effects, both acute and delayed

Indication of any immediate medical attention and special treatment needed

Notes to a physician:

CENTER/doctor if you feel unwell. IF exposed or concerned: Get medical advice/attention.

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Suspected of causing genetic defects. Causes damage to organs (CNS and blood effects - Oral). May cause damage to organs (Respiratory tract - Oral).

Treat symptomatically.

IF IN EYES: Obtain prompt consultation, preferably from an ophthalmologist. Following severe exposure the patient should be kept under medical review for at least 48 hours.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media

Unsuitable extinguishing Media

Special hazards arising from the substance or mixture

Special protective equipment and precautions for fire fighters

As appropriate for surrounding fire. Extinguish with carbon dioxide, dry chemical, foam or waterspray.

Do not use water jet. Direct water jet may spread the fire.

May decompose in a fire giving off toxic fumes. Decomposes in a fire giving off toxic fumes: Phenolics, Carbon monoxide and Carbon dioxide.

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Do not breathe fumes. Keep containers cool by spraying with water if exposed to fire. Avoid run off to waterways and sewers.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

emergency procedures

·

Methods and material for containment and cleaning up

Ensure adequate ventilation. Stop leak if safe to do so. Use personal protective equipment as required. Wear appropriate personal protective equipment, avoid direct contact. Do not breathe vapour. Avoid all contact. Do not ingest. If swallowed then seek immediate medical assistance. Isolate the area and allow vapours to disperse.

Avoid release to the environment. Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body. Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a container for disposal. Ventilate the area and wash spill site after material pickup is complete. Dispose of this material and its container as hazardous waste

SECTION 7: HANDLING AND STORAGE

Environmental precautions

Precautions for safe handling

Conditions for safe storage, including any incompatibilities
Storage temperature

Storage life Incompatible materials

Avoid all contact. Do not breathe vapour. Ensure adequate ventilation. Wear appropriate personal protective equipment, avoid direct contact. Use personal protective equipment as required. See Section: 8. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work.

Contaminated clothing should be laundered before reuse.

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Keep

away from heat, sources of ignition and direct sunlight. Ambient. Keep at temperature not exceeding (°C): 27

Stable under normal conditions.

Keep away from: Flammable liquids, Strong Oxidizing agents, Corrosive Substances, Strong Acids and strong mineral and organic bases, especially primary and secondary aliphatic amines.

14039 Page: 3 of 8

Version: 4.0

Date of Issue: 08 May 2017 Date of First Issue: 20 March 2012



www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

No OSHA permissible exposure limit (PEL).

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m³)	STEL (ppm)	STEL (mg/m³)	Note
1,3-Benzenediol	108-46-3	10	45	20	90	NIOSH
(Resorcinol)		10	-	20	-	ACGIH, A4

Note: OSHA PELs 1910.1000 TABLE Z-1/ NIOSH RELs / ACGIH TLVs

A4: Not Classifiable as a Human Carcinogen: Agents which cause concern that they could be carcinogenic for humans but which cannot be assessed conclusively because of the lack of data. In vitro or animal studies do not provide indications of carcinogenicity which are sufficient to classify the agent into one of the other categories.

The other components listed in Section 3 do not have occupational exposure limits.

Biological Exposure Indices

Not established

Appropriate engineering controls

Ensure adequate ventilation or use appropriate containment. Atmospheric levels should be controlled in compliance with the occupational exposure limit. A washing facility/water for eye and skin cleaning purposes should be present.

Individual protection measures, such as personal protective equipment (PPE)

General hygiene measures for the handling of chemicals are applicable. Avoid all contact. Do not breathe vapour. Wash hands before breaks and after work. Keep work clothes separately. Contaminated clothing should be laundered before reuse. Do not eat, drink or smoke at the work place.

Eye/face protection



Wear protective eye glasses for protection against liquid splashes. Wear eye protection with side protection (EN166).

Skin protection



Hand protection:

Wear impervious gloves (EN374). Gloves should be changed regularly to avoid permeation problems. Breakthrough time of the glove material: refer to the information provided by the gloves' producer.

Body protection:

Wear impervious protective clothing, including boots, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection



In case of inadequate ventilation wear respiratory protection. Open system(s): Wear suitable respiratory protective equipment.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance Odor Odor Threshold pH

ρπ ••••••

Melting Point/Freezing Point

Clear - Amber Coloured liquid.

Faint Epoxy Odour Not available. Not established. Not available.

14039 Page: 4 of 8

Version: 4.0

Date of Issue: 08 May 2017 Date of First Issue: 20 March 2012

Relative density



www.vishaypq.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Initial boiling point and boiling range

Flash Point

Not available.

Evaporation rate (Butyl acetate = 1)

Not available.

Flammability (solid, gas)

Not available.

Not available.

Not applicable - Liquid

Upper/lower flammability or explosive limits

Vapour pressure

Vapour density

Not available.

1 @ 118°C (mmHg)

>3.8 (Air = 1)

Solubility(ies)

The substance is essentially insoluble in water.

Partition coefficient: n-octanol/water Not available.
Auto-ignition temperature Not available.
Decomposition Temperature Not available.
Viscosity Not available.

SECTION 10: STABILITY AND REACTIVITY

Reactivity Stable under normal conditions.

Chemical stability Stable under normal conditions. May decompose if heated.

Possibility of hazardous reactions Hazardous polymerisation will not occur.

Conditions to avoid Keep away from heat, sources of ignition and direct sunlight. Keep at

temperature not exceeding (°C): 27

Incompatible materials Flammable liquids, Strong Oxidizing agents, Corrosive Substances, Strong

1.15 (H2O = 1)

Acids and strong mineral and organic bases, especially primary and secondary

aliphatic amines.

Hazardous decomposition product(s) Decomposes in a fire giving off toxic fumes: Phenolics, Carbon monoxide and

Carbon dioxide.

SECTION 11: TOXICOLOGICAL INFORMATION

Acute toxicity - Skin Contact

Information on toxicological effects (Substances in preparations / mixtures)

Acute toxicity - Ingestion Based upon the available data, the classification criteria are not met.

Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg

bw/day

Resorcinol: LD50 (oral,rat) mg/kg: 510 (OECD 401)

Acute toxicity - Inhalation Based upon the available data, the classification criteria are not met.

Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 20.0 mg/l. Based upon the available data, the classification criteria are not met.

Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg

hw/dav

Skin corrosion/irritation Skin Corrosion/Irritation, Category 2; Causes skin irritation.

Resorcinol: Test Result: Irritating to skin. (in vivo; FHSLA)

Serious eye damage/irritationEye Damage, Category 1; Causes serious eye damage.Resorcinol:Test Result: Causes serious eye damage. (in vivo; FHSLA)

Respiratory or skin sensitization Skin Sensitisation, Category 1: May cause an allergic skin reaction.

2,3-Epoxypropyl o-tolyl ether: Test Result: Positive (OECD 406)
Resorcinol: Test Result: Positive (OECD 429)

Germ cell mutagenicity Germ cell mutagenicity, Category 2: Suspected of causing genetic defects.

2,3-Epoxypropyl o-tolyl ether: Test Result: Positive (OECD 471)

CarcinogenicityBased upon the available data, the classification criteria are not met.Reproductive toxicityBased upon the available data, the classification criteria are not met.

STOT - single exposure Specific target organ toxicity — single exposure, Category 1; Causes damage to

organs. - oral

Specific target organ toxicity — single exposure, Category 2; May cause

damage to organs - oral.

Resorcinol: NOAEL 80 mg/kg bw/day (OECD 408)

STOT - repeated exposureBased upon the available data, the classification criteria are not met. **Aspiration hazard**Based upon the available data, the classification criteria are not met.

14039 Page: 5 of 8

Version: 4.0

Date of Issue: 08 May 2017 Date of First Issue: 20 March 2012



www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Information on likely routes of exposure

InhalationPossible – accidental exposureIngestionUnlikely – accidental exposureSkin ContactPossible – accidental exposureEye ContactUnlikely – accidental exposure

Early onset symptoms related to exposure

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Suspected of causing genetic defects. Causes damage to organs (CNS and blood effects - Oral). May cause damage to organs (Respiratory tract - Oral).

Delayed health effects from exposure

Symptoms of poisoning may be delayed for several days.

Other information

NTP Report on Carcinogens All chemicals are not listed

IARC Monographs Bis-[4-(2,3-epoxipropoxi)phenyl]propane: Group 3

OSHA Designated Carcinogen All chemicals are not listed

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity Aquatic Chronic 3: Harmful to aquatic life with long lasting effects.

Estimated Mixture LC50 1 to ≤ 10 mg/l (Fish) LC50 (fish) mg/l 2.8 – 5.1 (OECD 203)

2,3-Epoxypropyl o-tolyl ether:

Resorcinol:

Persistence and degradability

Bioaccumulative potential

LC50 (fish) mg/l 2.8 – 5.1 (OECD 203)

EC50 (Daphnia magna) mg/l 1 (OECD 202)

Part of the components are poorly biodegradable.

The product has low potential for bioaccumulation.

Mobility in soilThe product is predicted to have low mobility in soil (Insoluble in water).

Other adverse effects None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods This material and its container must be disposed of as hazardous waste. Send

after pre-treatment to a appropriate hazardous waste incinerator facility

according to legislation.

Additional Information Dispose of contents in accordance with local, state or national legislation.

SECTION 14: TRANSPORT INFORMATION

(Not classified according to the United Nations 'Recommendations on the Transport of Dangerous Goods')

ADR/RID **IMDG** IATA Not applicable **UN** number Not applicable Not applicable UN proper shipping name Not applicable Not applicable Not applicable Transport hazard class(es) Not applicable Not applicable Not applicable Packing group Not applicable Not applicable Not applicable **Environmental hazards** Not classified Not classified as a Not classified

See Section: 2

Marine Pollutant/ Environmentally hazardous substance

Transport in bulk according to Annex II of MARPOL

73/78 and the IBC Code

nd the IBC Code

Special precautions for user Not applicable

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture US Federal Regulations

TSCA (Toxic Substance Control Act)

Bis-[4-(2,3-epoxipropoxi)phenyl]propane: Subject to 25,000 lb reporting

14039 Page: 6 of 8

Version: 4.0

Date of Issue: 08 May 2017 Date of First Issue: 20 March 2012



www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

threshold

Bisphenol A Diglycidyl Ether (MW <700): Exempt from reporting under CDR 2,3-Epoxypropyl o-tolyl ether: Subject to 25,000 lb reporting threshold

EPCRA/SARA Section 302 Extremely Hazardous All chem

Substances

EPCRA Section 313 Toxics Release Inventory (TRI)

Program

NIOSH Occupational Carcinogen List

OSHA List of highly hazardous chemicals, toxics and

reactives

NTP Report on Carcinogens (RoC) List Poison Prevention Packaging Act

US State Regulations

California State, Proposition 65 List
California State, Safer Consumer Products Regulations
Maine State, Toxic Chemicals in Children's Products Act
New Jersey State Worker and Community RTK Act
Pennsylvania State, Worker and Community RTK Act
Rhode Island State, Hazardous Substances RTK Act

Non-Regional

IARC Monographs, List of Classifications

All chemicals are not listed

All chemicals are not listed All chemicals are not listed

All chemicals are not listed All chemicals are not listed All chemicals are not listed All chemicals are not listed All chemicals are not listed All chemicals are not listed

Bis-[4-(2,3-epoxipropoxi)phenyl]propane: Group 3

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: Updated substance / mixture classification. New SDS Regulation compliant with HazCom 2012 format, all sections have been updated to include new information. Please review SDS with care.

Version 4.0

Revision Date 08 May 2017

Date of First Issue 20 March 2012

References:

Existing Safety Data Sheet (SDS), EU Data: Harmonised Classification(s) for Bis-[4-(2,3-epoxipropoxi)phenyl]propane (CAS No. 1675-54-3), 2,3-Epoxypropyl o-tolyl ether (CAS No. 2210-79-9) and Resorcinol (CAS No. 108-46-3). Existing ECHA registration(s) for 2,3-Epoxypropyl o-tolyl ether (CAS No. 2210-79-9) and Resorcinol (CAS No. 108-46-3), and the Classification and Labelling Inventory for Bisphenol A Diglycidyl Ether (CAS No. 25085-99-8).

GHS Classification of the substance or mixture	Classification Procedure		
Skin Corrosion/Irritation, Category 2	Threshold Calculation		
Skin Sensitisation, Category 1	Threshold Calculation		
Eye Damage, Category 1	Threshold Calculation		
Germ cell mutagenicity, Category 2	Threshold Calculation		
Specific target organ toxicity — single exposure, Category 1	Threshold Calculation		
Specific target organ toxicity — single exposure, Category 2	Threshold Calculation		
Hazardous to the aquatic environment, Chronic, Category 3	Summation Calculation		

LEGEND

ACGIH: American Conference of Governmental Industrial Hygienists

BEI: Biological Exposure Indices (ACGIH)

IARC: International Agency for Research on Cancer

Irr: Irritation

NIOSH: National Institute of Occupational Safety and Health

NTP: National Toxicology Program

OSHA: The Occupational Safety & Health Administration

PBT: Persistent, Bioaccumulative and Toxic

PEL: Permissible exposure limit

REL: Recommended exposure limit

SCL: Specific Concentration Limit

Skin": Risk of overexposure via dermal contact

STEL: Short Term Exposure Limit

TLV: Threshold Limit value

TSCA: Toxic Substance Control Act TWA: Time Weighted Average URT: Upper respiratory tract

vPvB: very Persistent and very Bioaccumulative

14039 Page: 7 of 8

Version: 4.0

Date of Issue: 08 May 2017 Date of First Issue: 20 March 2012



www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Vishay Precision Group gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Vishay Precision Group accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

14039 Page: 8 of 8