Revision: 1.1 Date: 26.08.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypq.com

1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product Name PLM-9
Chemical Name Mixture
CAS No. Mixture
EINECS No. Mixture
REACH Registration No. None assigned.

1.2 Relevant identified uses of the substance or mixture

and uses advised against

Identified use(s) Photostress® measurements.

Uses advised against None known.

1.3 Details of the supplier of the safety data sheet

Company Identification VISHAY MEASUREMENTS GROUP, INC.

Post Office Box 27777 Raleigh, NC 27611

USA

 Telephone
 919-365-3800

 Fax
 919-365-3945

E-Mail (competent person) mm.us@vishaypg.com

1.4 Emergency telephone number 1-800-424-9300

CHEMTREC

2. SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Skin Irrit. 2; H315 Skin Sens. 1; H317 Eye Irrit. 2; H319 Muta. 2; H341 Carc. 2; H351

Aquatic Chronic 2; H411

2.2 Label elements GHS Classification

Product Name PLM-9

Hazard pictogram(s)

GHS Classification

2.1.1







Signal word(s) Warning

Contains: Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average

molecular weight ≤ 700), N-Butyl Glycidyl Ether, p-tert-butylphenyl 1-(2,3-

epoxy)propyl ether.

Hazard statement(s) H315: Causes skin irritation.

H317: May cause an allergic skin reaction.
H319: Causes serious eye irritation.
H341: Suspected of causing genetic defects.
H351: Suspected of causing cancer.

H411: Toxic to aquatic life with long lasting effects.

Precautionary statement(s) P201: Inhämta särskilda instruktioner före användning.

P280: Använd skyddshandskar/skyddskläder/ögonskydd/ansiktsskydd.

Revision: 1.1 Date: 26.08.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypg.com

P302+P352: VID HUDKONTAKT: Tvätta med mycket vatten. P333+P313: Vid hudirritation eller utslag: Sök läkarhjälp.

P305+P351+P338: VID KONTAKT MED ÖGONEN: Skölj försiktigt med vatten i flera minuter. Ta ur eventuella kontaktlinser om det går lätt. Fortsätt att skölja. P308+P313: Vid exponering eller misstanke om exponering Sök läkarhjälp.

2.3 Other hazards None

3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances Not applicable

3.2 Mixtures

GHS Classification

Chemical identity of the substance	%W/W	CAS No.	EC No.	Hazard statement(s)	
Reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	<100	25068-38-6	500-033-5	Skin Irrit. 2; H315 (SCL: ≥ 5%) Skin Sens. 1; H317 Eye Irrit. 2; H319 (SCL: ≥ 5%) Aquatic Chronic 2; H411	
p-Tert-butylphenyl 1-(2,3- epoxy)propyl ether	< 10	3101-60-8	221-453-2	Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 2; H411	
N-Butyl Glycidyl Ether	2 – 5	2426-08-6	219-376-4	Flam. Liq. 3; H226 Acute Tox. 4; H302 & H332 Skin Sens. 1; H317 STOT SE 3; H335 Muta. 2; H341 Carc. 2; H351 Aquatic Chronic 3; H412	

H226: Flammable liquid and vapour. H302+H332: Harmful if swallowed or if inhaled. H315: Causes skin irritation. H317: May cause an allergic skin reaction. H319: Causes serious eye irritation. H335: May cause respiratory irritation. H341: Suspected of causing genetic defects. H351: Suspected of causing cancer. H411: Toxic to aquatic life with long lasting effects. H412: Harmful to aquatic life with long lasting effects. SCL: Specific Concentration Limit.

4. SECTION 4: FIRST AID MEASURES



4.1 Description of first aid measures

Inhalation

Self-protection of the first aider

Do not breathe vapour. Wear suitable respiratory protective equipment if exposure to high levels of material are likely. Wear suitable protective clothing.

Do not use mouth-to-mouth resuscitation.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Apply artificial respiration if necessary (do not employ mouth-to-mouth method). IF exposed or concerned: Get medical

advice/attention.

Skin Contact

IF ON SKIN: Remove contaminated clothing and wash affected skin with water.

Contaminated clothing should be thoroughly cleaned. If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical

advice/attention.

Eye Contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get

Revision: 1.1 Date: 26.08.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypq.com

medical advice/attention.

IF SWALLOWED: Get medical advice/attention if you feel unwell. Do not induce Ingestion vomiting. Do not give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute May cause an allergic skin reaction. Causes skin irritation. Causes serious eye irritation. Suspected of causing genetic defects. Suspected of causing cancer. and delayed

Treat symptomatically.

4.3 Indication of any immediate medical attention and special treatment needed

5. SECTION 5: FIRE-FIGHTING MEASURES

5.1 Extinguishing media

4.2

Suitable Extinguishing Media Extinguish with carbon dioxide, dry chemical, foam or waterspray. Alcohol

resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

Do not use water jet. May spread fire.

5.2 Special hazards arising from the substance or

Unsuitable Extinguishing Media

mixture

May decompose in a fire giving off toxic fumes. Phenolics, Carbon monoxide, Carbon dioxide, Acids and Aldehydes. Container may rupture from gas

generation in a fire situation. Dense smoke is emitted when burned without sufficient oxygen.

5.3 Advice for fire-fighters

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Do not breathe fumes. Keep containers cool by spraying

with water if exposed to fire. Avoid run off to waterways and sewers.

6. SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and Stop leak if safe to do so. Eliminate all ignition sources if safe to do so. Ensure emergency procedures adequate ventilation. Do not breathe vapour. Avoid contact with skin, eyes or

clothing. Wear suitable respiratory protection. Use personal protective

equipment as required. See Section: 8.

6.2 **Environmental precautions** Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled

discharges into watercourses must be alerted to the Environment Agency or

other appropriate regulatory body.

6.3 Methods and material for containment and cleaning

Ensure suitable personal protection during removal of spillages. Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a container for disposal. Dispose of this material and its container as hazardous waste. To clean the floor and all objects contaminated by this material use soap

and water.

6.4 Reference to other sections See Section: 8, 13

7. SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling Obtain special instructions before use. Do not handle until all safety precautions

sunlight.

have been read and understood. Do not breathe vapour. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective

equipment as required. See Section: 8. Do not eat, drink or smoke when using

this product. Wash hands before breaks and after work. Keep in a cool, dry, well ventilated place. Keep away from heat and direct

7.2 Conditions for safe storage, including any incompatibilities

Storage Temperature

Storage Life

Incompatible materials

Ambient. Stable under normal conditions.

Keep away from: Oxidizing agents, unintended contact with amines, Strong

Acids, mercaptans and Alkalis.

7.3 Photostress® measurements. Specific end use(s)

Revision: 1.1 Date: 26.08.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypq.com

8. **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

8.1 **Control parameters**

8.1.1 Occupational exposure limits

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m³)	STEL (ppm)	STEL (mg/m³)	Note
N-Butyl Glycidyl Ether	2426-08-6	=	-	5.6*	30*	NIOSH
N-Butyl Glycidyl Ether	2426-08-6	50	270	-	-	OSHA

Note: OSHA 1910.1000 TABLE Z-1 / *NIOSH 15 minute value

8.1.2 Not established. **Biological limit value**

8.1.3 **PNECs and DNELs** Not established.

8.2 **Exposure controls**

8.2.1 Appropriate engineering controls Ensure adequate ventilation or use appropriate containment. Use with local

exhaust ventilation. Atmospheric levels should be controlled in compliance with the occupational exposure limit. Guarantee that the eye flushing systems and

safety showers are located close to the working place. General hygiene measures for the handling of chemicals are applicable. Use

> personal protective equipment as required. Keep work clothes separately. Contaminated clothing should be thoroughly cleaned. Avoid contact with skin,

eyes or clothing. Do not eat, drink or smoke during work.

Wear protective eye glasses for protection against liquid splashes. Wear eye

protection with side protection (EN166).

8.2.2 Individual protection measures, such as personal

protective equipment (PPE)

Eye/face protection



Skin protection



Hand protection: Wear impervious gloves (EN374). Breakthrough time of the glove material: refer to the information provided by the gloves' producer. The gloves type used must be chosen based on the work activity and duration as well as concentration/quantity of material being handled. Recommended: Butyl rubber, Nitrile rubber, Neoprene, PVC.

Body protection: Wear impervious protective clothing, including boots, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

In case of inadequate ventilation wear respiratory protection. Open system(s): Wear suitable respiratory protective equipment.

Respiratory protection

Thermal hazards Not applicable.

8.2.3 **Environmental Exposure Controls** Avoid release to the environment.

9. **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

9.1 Information on basic physical and chemical properties

Appearance

Odour

Odour Threshold

Melting Point/Freezing Point

Clear - Light Coloured liquid

Faint Odour

Not available. Not established.

-16 °C (CAS No. 25068-38-6)

Revision: 1.1 Date: 26.08.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypq.com

Initial boiling point and boiling range ~320°C (CAS No. 25068-38-6) Flash point > 264 < 268°C (CAS No. 25068-38-6)

Evaporation rate Not available.

Flammability (solid, gas) Not applicable - Liquid

Upper/lower flammability or explosive limits Not applicable. Vapour pressure 1 mm Hg Vapour density >1 (Air = 1) Relative density 1.14 (H2O = 1)

Solubility(ies) Partly soluble in water.

Partition coefficient: n-octanol/water \geq 2.64 \leq 3.78 log Pow (25 °C) (CAS No. 25068-38-6)

Auto-ignition temperature Not applicable.

Decomposition Temperature >350°C (CAS No. 25068-38-6)

Not available. Viscosity Explosive properties Not explosive. Oxidising properties Not oxidisina.

9.2 Other information None.

10. **SECTION 10: STABILITY AND REACTIVITY**

10.1 Reactivity Stable under normal conditions **Chemical stability** 10.2 Stable under normal conditions.

10.3 Possibility of hazardous reactions Reaction with some curing agents may produce considerable heat. Reacts with

amines. Polymerization may occur. Contact with aliphatic amines will cause

irreversible polymerization with considerable heat build-up. 10.4 Conditions to avoid

Avoid contact with heat and ignition sources and oxidizers.

The product may decompose if heated to temperatures above (°C): 300 10.5 Incompatible materials Keep away from: Oxidizing agents, unintended contact with amines, Strong

Acids mercaptans and alkalis. Polymerization may occur.

10.6 **Hazardous Decomposition Product(s)** Decomposes in a fire giving off toxic fumes: Phenolics, Carbon monoxide,

Carbon dioxide, Acids and Aldehydes.

SECTION 11: TOXICOLOGICAL INFORMATION 11.

Information on toxicological effects (Substances in preparations / mixtures)

Acute toxicity

11.1

Ingestion Based upon the available data, the classification criteria are not met.

LC50 > 2000 mg/kg bw/day

Inhalation Based upon the available data, the classification criteria are not met.

LC50 > 20 mg/kg bw/day

Dermal Based upon the available data, the classification criteria are not met.

LC50 > 2000 mg/kg bw/day

Skin corrosion/irritation Skin Irrit. 2: Causes skin irritation. Serious eye damage/irritation Eye Irrit. 2: Causes serious eye irritation.

Respiratory or skin sensitization Skin Sens. 1: May cause an allergic skin reaction.

Germ cell mutagenicity Muta. 2: May cause genetic defects. Carcinogenicity Carc. 2: Suspected of causing cancer.

Reproductive toxicity Based upon the available data, the classification criteria are not met. STOT - single exposure Based upon the available data, the classification criteria are not met. STOT - repeated exposure Based upon the available data, the classification criteria are not met. Aspiration hazard Based upon the available data, the classification criteria are not met.

11.2 Other information

> NTP Report on Carcinogens Not listed. IARC Monographs Not listed.

Revision: 1.1 Date: 26.08.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypq.com

12. **SECTION 12: ECOLOGICAL INFORMATION**

12.1 **Toxicity** Aquatic Chronic 2 Toxic to aquatic life with long lasting effects.

Estimated LC50 (Fish) > 1 ≤10 mg/l

12.2 Persistence and degradability Part of the components are poorly biodegradable. 12.3 Bioaccumulative potential The product has low potential for bioaccumulation.

12.4 Mobility in soil The product is predicted to have low mobility in soil. (Partly soluble in water).

12.5 Results of PBT and vPvB assessment Not classified as PBT or vPvB.

12.6 Other adverse effects None known.

13. **SECTION 13: DISPOSAL CONSIDERATIONS**

13.1 Waste treatment methods This material and its container must be disposed of as hazardous waste

> (2008/98/EEC). Dispose of contents in accordance with local, state or national legislation. Containers of this material may be hazardous when empty since they retain product residue. Do not allow to enter drains, sewers or watercourses.

Additional Information 13.2 Dispose of contents in accordance with local, state or national legislation.

SECTION 14: TRANSPORT INFORMATION 14.

ADR/RID / IMDG / IATA

14.1 **UN** number UN 3082

14.2 **UN Proper Shipping Name** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction

9

product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular

weight ≤ 700) and p-Tert-butylphenyl 1-(2,3-epoxy)propyl ether)

Transport hazard class(es) 14.3

Packing Group Ш 14.4

14.5 **Environmental hazards** Marine Pollutant / Environmentally hazardous substance

14.6 Special precautions for user See Section: 2 Transport in bulk according to Annex II of 14.7 Not applicable.

MARPOL73/78 and the IBC Code

14.8 Additional information None.

15. **SECTION 15: REGULATORY INFORMATION**

15.1 Safety, health and environmental

regulations/legislation specific for the substance or

mixture

15.1.1 **National regulations**

> OSHA Occupational Safety and Health Standards None.

European regulations 15.1.2

> Authorisations and/or restrictions on use None. Substance(s) of Very High Concern (SVHCs) None.

Wassergefährdungsklasse (Germany) Water hazard class: 2

15.2 **Chemical Safety Assessment** Not available.

SECTION 16: OTHER INFORMATION 16.

The following sections contain revisions or new statements: 1-16.

References: Existing Safety Data Sheet (SDS). Existing ECHA registration(s) for Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)(CAS# 25068-38-6) and P-Tert-butylphenyl 1-(2,3-epoxy)propyl ether (CAS# 3101-60-8), and Harmonised Classification(s) for N-Butyl Glycidyl Ether (CAS# 2426-08-6).

Revision: 1.1 Date: 26.08.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypg.com

GHS Classification of the substance or mixture	Classification Procedure
Skin Irrit. 2; H315	Threshold Calculation
Skin Sens. 1; H317	Threshold Calculation
Eye Irrit. 2; H319	Threshold Calculation
Muta. 2; H341	Harmonised Classification
Carc. 2; H351	Harmonised Classification
Aquatic Chronic 2; H411	Summation Calculation

LEGEND

LTEL Long Term Exposure Limit
STEL Short Term Exposure Limit
DNEL Derived No Effect Level

PNEC Predicted No Effect Concentration

PBT PBT: Persistent, Bioaccumulative and Toxic vPvB vPvT: very Persistent and very Toxic

NTP National Toxicology Program

IARC International Agency for Research on Cancer
OSHA The Occupational Safety & Health Administration
NIOSH National Institute for Occupational Safety and Health

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Vishay Precision Group gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Vishay Precision Group accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Annex to the extended Safety Data Sheet (eSDS)

No information available.