

SAFETY DATA SHEET

Revision: 1.1 Date: 23.07.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vishaypg.com

1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier**
Product Name 3140-RTV
Chemical Name Mixture
CAS No. Mixture
EINECS No. Mixture
REACH Registration No. None assigned.
- 1.2 Relevant identified uses of the substance or mixture and uses advised against**
Identified Use(s) PC1 Adhesives, sealants
Uses Advised Against None known.
- 1.3 Details of the supplier of the safety data sheet**
Company Identification VISHAY MEASUREMENTS GROUP UK LTD
Stroudley Road
Basingstoke
Hampshire
RG24 8FW
United Kingdom
Telephone +44 (0) 1256 462131
Fax +44 (0) 1256 471441
E-Mail (competent person) mm.uk@vishaypg.com
- 1.4 Emergency telephone number** (00-1) 703-527-3887
CHEMTREC

2. SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture**
- 2.1.1 Regulation (EC) No. 1272/2008 (CLP)** Skin Sens. 1; H317
- 2.2 Label elements**
According to Regulation (EC) No. 1272/2008 (CLP)
Product Name 3140-RTV
- Hazard Pictogram(s)
- 
- Signal Word(s) Warning
- Contains: Trimethoxy(methyl)silane
- Hazard Statement(s) H317: May cause an allergic skin reaction.
- Precautionary Statement(s) P261: Avoid breathing vapours.
P272: Contaminated work clothing should not be allowed out of the workplace.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352: IF ON SKIN: Wash with plenty of soap and water.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
P363: Wash contaminated clothing before reuse.
- Additional Information** EUH066: Repeated exposure may cause skin dryness or cracking.
- 2.3 Other hazards** Contact with water or humid air will form methanol.
Product may emit formaldehyde vapour at temperatures above 180°C in the

SAFETY DATA SHEET

Revision: 1.1 Date: 23.07.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vishaypg.com

presence of air. Formaldehyde vapour is a suspected carcinogen, toxic by inhalation and irritating to eyes and the respiratory system. Exposure limits should be strictly respected.

3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

EC Classification Regulation (EC) No. 1272/2008 (CLP)

Chemical identity of the substance	%W/W	CAS No.	EC No.	REACH Registration No.	Hazard Statement(s)
Trimethylated silica	< 25	68909-20-6	272-697-1	None assigned	EUH066
Trimethoxy(methyl)silane	5 - 10	1185-55-3	214-685-0	None assigned	Flam. Liq. 2; H225 Skin Sens. 1; H317
Methanol	< 0.2	67-56-1	200-659-6	None assigned	Flam. Liq. 2; H225 Acute Tox. 3; H301 Acute Tox. 3; H311 Acute Tox. 3; H331 STOT RE 1; H370

H225: Highly flammable liquid and vapour. H301: Toxic if swallowed. H311: Toxic in contact with skin. H317: May cause an allergic skin reaction. H331: Toxic if inhaled. H370: Causes damage to organs. EUH066: Repeated exposure may cause skin dryness or cracking.

4. SECTION 4: FIRST AID MEASURES



4.1 Description of first aid measures

Inhalation

If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

Skin Contact

IF ON SKIN: Remove contaminated clothing and wash all affected areas with plenty of water. Contaminated clothing should be thoroughly cleaned. If skin irritation or rash occurs: Get medical advice/attention.

Eye Contact

Rinse cautiously with water for several minutes.

Ingestion

Obtain medical attention if ill effects occur.

4.2 Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction. Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

5. SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable Extinguishing media

As appropriate for surrounding fire. Extinguish with carbon dioxide, dry chemical, foam or waterspray.

Unsuitable extinguishing media

Do not use water jet. Direct water jet may spread the fire.

5.2 Special hazards arising from the substance or mixture

Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silica, Carbon oxides and traces of incompletely burned carbon compounds, Formaldehyde, Sulphur products, Nitrogen products. Product may emit formaldehyde vapour at temperatures above 180°C in the presence of air. Formaldehyde vapour is a suspected carcinogen, toxic by inhalation and irritating to eyes and the respiratory system. Exposure limits should be strictly respected.

5.3 Advice for fire-fighters

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Do not breathe fumes. Keep containers cool by spraying with water if exposed to fire. Avoid run off to waterways and sewers.

SAFETY DATA SHEET

Revision: 1.1 Date: 23.07.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vishaypg.com

6. SECTION 6: ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation. Shut off leaks if without risk. Avoid breathing vapours. Use personal protective equipment as required. See Section: 8.
- 6.2 Environmental precautions** Avoid release to the environment. Do not allow to enter drains, sewers or watercourses.
- 6.3 Methods and material for containment and cleaning up** Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a container for disposal. The spilled product produces an extremely slippery surface. Dispose of contents in accordance with local, state or national legislation.
- 6.4 Reference to other sections** See Section: 8, 13

7. SECTION 7: HANDLING AND STORAGE

- 7.1 Precautions for safe handling** Ensure adequate ventilation. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. See Section: 8. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work.
- 7.2 Conditions for safe storage, including any incompatibilities**
Storage temperature: Store in a well-ventilated place. Keep away from heat, sources of ignition and direct sunlight. Protect from moisture.
Storage life: Keep at temperature not exceeding (°C): 32°C
Incompatible materials: Stable under normal conditions.
Keep away from: Oxidizing agents and Water. Contact with water or humid air will form methanol.
- 7.3 Specific end use(s)** PC1 Adhesives, sealants. See Section: 1.2

8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

- 8.1 Control parameters**
8.1.1 Occupational Exposure Limits

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m³)	STEL (ppm)	STEL (mg/m³)	Note
Methanol	67-56-1	200	266	250	333	WEL

Note: WEL: Workplace Exposure Limit (UK HSE EH40)

- 8.1.2 Biological limit value** Not established.
- 8.1.3 PNECs and DNELs** Not established.
- 8.2 Exposure controls**
8.2.1 Appropriate engineering controls Ensure adequate ventilation or use appropriate containment. Atmospheric levels should be controlled in compliance with the occupational exposure limit.
- 8.2.2 Individual protection measures, such as personal protective equipment (PPE)** General hygiene measures for the handling of chemicals are applicable. Avoid contact with skin, eyes or clothing. Wash hands before breaks and after work. Keep work clothes separately. Contaminated clothing should be thoroughly cleaned. Do not eat, drink or smoke at the work place.

Eye/ face protection



Wear goggles giving complete protection to eyes to protect against liquid splashes (EN166).

Skin protection



Hand protection: Wear impervious gloves (EN374). Gloves should be changed regularly to avoid permeation problems. Breakthrough time of the glove material: refer to the information provided by the gloves' producer.

Body protection: Wear impervious protective clothing, including boots, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

SAFETY DATA SHEET

Revision: 1.1 Date: 23.07.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vishaypg.com

Respiratory protection



In case of inadequate ventilation wear respiratory protection. Open system(s):
Wear suitable respiratory protective equipment. A suitable mask with filter type A
may be appropriate.

Thermal hazards

Not applicable.

8.2.3 Environmental Exposure Controls

Avoid release to the environment.

9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	Milky white Liquid
Odour	Slight
Odour threshold	Not available.
pH	Not established.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	>65°C
Flash point	>101°C [Closed cup]
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	1.05
Solubility(ies)	Not available.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity	300 Poise at 25°C.
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.

9.2 Other information

None.

10. SECTION 10: STABILITY AND REACTIVITY

10.1 Stability and reactivity	This product releases methanol.
10.2 Chemical stability	Stable under normal conditions.
10.3 Possibility of hazardous reactions	Contact with water or humid air will form methanol.
10.4 Conditions to avoid	Protect from moisture. Keep at temperature not exceeding (°C): 32.
10.5 Incompatible materials	Keep away from: Oxidizing agents and Water.
10.6 Hazardous decomposition product(s)	Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silica, Carbon oxides and traces of incompletely burned carbon compounds, Formaldehyde, Sulphur products, Nitrogen products.

11. SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects (Substances in preparations / mixtures)

Acute toxicity

Ingestion

Based upon the available data, the classification criteria are not met.
Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg
bw/day.

Inhalation

Based upon the available data, the classification criteria are not met.
Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 20.0 mg/l.

Skin Contact

Based upon the available data, the classification criteria are not met.
Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg
bw/day.

SAFETY DATA SHEET

Revision: 1.1 Date: 23.07.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vishaypg.com

	Skin corrosion/irritation	EUH066: Repeated exposure may cause skin dryness or cracking.
	Serious eye damage/irritation	Based upon the available data, the classification criteria are not met.
	Respiratory or skin sensitization	Skin Sens. 1: May cause an allergic skin reaction.
	Germ cell mutagenicity	Based upon the available data, the classification criteria are not met.
	Carcinogenicity	Based upon the available data, the classification criteria are not met.
	Reproductive toxicity	Based upon the available data, the classification criteria are not met.
	STOT - single exposure	Based upon the available data, the classification criteria are not met.
	STOT - repeated exposure	Based upon the available data, the classification criteria are not met.
	Aspiration hazard	Based upon the available data, the classification criteria are not met.
11.2	Other information	None.

12. SECTION 12: ECOLOGICAL INFORMATION

12.1	Toxicity	Based upon the available data, the classification criteria are not met. Estimated Mixture LC50 >100 mg/l (Fish). No adverse effects on bacteria are predicted.
12.2	Persistence and degradability	Siloxanes are removed from water by sedimentation or binding to sewage sludge. Removed > 90% by binding onto sewage sludge. The siloxanes in this product do not contribute to the BOD. In soil, siloxanes are degraded. This product hydrolyses in water or moist air, releasing methanol and organosilicons.
12.3	Bioaccumulative potential	The product has low potential for bioaccumulation.
12.4	Mobility in soil	The product is predicted to have high mobility in soil.
12.5	Results of PBT and vPvB assessment	Not classified as PBT or vPvB.
12.6	Other adverse effects	None known.

13. SECTION 13: DISPOSAL CONSIDERATIONS

13.1	Waste treatment methods	Dispose of contents in accordance with local, state or national legislation.
13.2	Additional Information	None.

14. SECTION 14: TRANSPORT INFORMATION

Not classified according to the United Nations 'Recommendations on the Transport of Dangerous Goods'.

		ADR/RID / IMDG / IATA
14.1	UN number	Not classified as dangerous for transport.
14.2	UN proper shipping name	Not classified
14.3	Transport hazard class(es)	Not classified
14.4	Packing group	Not classified
14.5	Environmental hazards	Not classified as a Marine Pollutant /Environmentally hazardous substance.
14.6	Special precautions for user	See Section: 2
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
14.8	Additional Information	None.

15. SECTION 15: REGULATORY INFORMATION

15.1	Safety, health and environmental regulations/legislation specific for the substance or mixture	
15.1.1	EU regulations	
	Substance(s) of Very High Concern (SVHCs)	None
15.1.2	National regulations	
	Germany	Water hazard class: 1
15.2	Chemical Safety Assessment	Not available.

SAFETY DATA SHEET

Revision: 1.1 Date: 23.07.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vishaypg.com

16. SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

References: Existing Safety Data Sheet (SDS), Harmonised Classification(s) for Methanol (CAS# 67-58-1) and Existing ECHA registration(s) for Trimethoxy(methyl)silane (CAS# 1185-55-3) and Methanol (CAS# 67-58-1).

Classification of the substance or mixture According to Regulation (EC) No. 1272/2008 (CLP)	Classification Procedure
Skin Sens. 1; H317	Threshold Calculation
EUH066	Existing Safety Data Sheet (SDS)

LEGEND

LTEL	Long Term Exposure Limit
STEL	Short Term Exposure Limit
DNEL	Derived No Effect Level
PNEC	Predicted No Effect Concentration
PBT	PBT: Persistent, Bioaccumulative and Toxic
vPvB	very Persistent and very Bioaccumulative

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Vishay Precision Group gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Vishay Precision Group accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Annex to the extended Safety Data Sheet (eSDS)

No information available.