Revision: 3.1 Date: 29.07.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypq.com

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product Name Epoxylite 813 Part A

Chemical Name Mixture
CAS No. Mixture
EINECS No. Mixture
REACH Registration No. None assigned.

1.2 Relevant identified uses of the substance or mixture

and uses advised against

Identified Use(s) PC14 Metal surface treatment products, including galvanic and electroplating

products.

Uses Advised Against None known.

1.3 Details of the supplier of the safety data sheet

Company Identification VISHAY MEASUREMENTS GROUP UK LTD

Stroudley Road Basingstoke Hampshire RG24 8FW United Kingdom

 Telephone
 +44 (0) 1256 462131

 Fax
 +44 (0) 1256 471441

 E-Mail (competent person)
 mm.uk@vishaypg.com

1.4 Emergency telephone number (00-1) 703-527-3887

CHEMTREC

2. SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

2.1.1 Regulation (EC) No. 1272/2008 (CLP) Skin Irrit. 2; H315

Skin Sens. 1; H317 Eye Irrit. 2; H319 STOT RE 1; H372 Aquatic Chronic 2; H411

2.2 Label elements Regulation (EC) No. 1272/2008 (CLP)

Product Name Epoxylite 813 Part A

Hazard Pictogram(s)







Signal Word(s) Danger

Contains: Phenol, polymer with formaldehyde, glycidyl ether, Crystalline silica and

Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average

molecular weight ≤ 700).

Hazard Statement(s) H315: Causes skin irritation.

H317: May cause an allergic skin reaction. H319: Causes serious eye irritation.

H372: Causes damage to organs through prolonged or repeated exposure:

Lungs.

H411: Toxic to aquatic life with long lasting effects.

Revision: 3.1 Date: 29.07.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypq.com

Precautionary Statement(s)

P260: Do not breathe vapour.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of water.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313: If eye irritation persists: Get medical advice/attention.

Additional Information None.

2.3 Other hazards Susceptible to polymerisation initiated by prolonged heating or the presence of

catalyst. Bulk: May undergo autopolymerisation.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS 3.

3.2 Mixtures

Regulation (EC) No. 1272/2008 (CLP)

Chemical identity of the substance	%W/W	CAS No.	EC No.	REACH Registration No.	Hazard Statement(s)
Phenol, polymer with formaldehyde, glycidyl ether	65 - 75	28064-14-4	-	None assigned.	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411
Crystalline silica	10 - 20	14808-60-7	238-878-4	None assigned.	STOT RE 1; H372
Magnesium silicate	10 - 20	14807-96-6	238-877-9	None assigned.	Not classified
Reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	< 5	25068-38-6	500-033-5	None assigned.	Skin Irrit. 2; H315 (SCL: ≥ 5%) Eye Irrit. 2; H319 (SCL: ≥ 5%) Skin Sens. 1; H317 Aquatic Chronic 2; H411

H315: Causes skin irritation. H317: May cause an allergic skin reaction. H319: Causes serious eye irritation. H372: Causes damage to organs through prolonged or repeated exposure. H411: Toxic to aquatic life with long lasting effects. SCL: Specific Concentration Limit.

SECTION 4: FIRST AID MEASURES 4.



Description of first aid measures 4.1

Inhalation

Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical advice/attention if you feel unwell. If exposed or concerned: Get medical attention/advice.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Skin Contact IF ON SKIN: Remove contaminated clothing and wash all affected areas with plenty of water. Contaminated clothing should be thoroughly cleaned. If skin

irritation or rash occurs: Get medical advice/attention.

Eye Contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if eye

irritation develops or persists.

Ingestion Rinse mouth. Do not induce vomiting. Do not give anything by mouth to an unconscious person. If exposed or concerned: Get medical attention/advice. 4.2 Most important symptoms and effects, both acute and Causes skin irritation. May cause an allergic skin reaction. Causes serious eye delayed irritation. Causes damage to organs through prolonged or repeated exposure:

Lungs.

Revision: 3.1 Date: 29.07.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypq.com

4.3 Indication of any immediate medical attention and

special treatment needed

Treat symptomatically.

5. **SECTION 5: FIREFIGHTING MEASURES**

5.1 **Extinguishing media**

> Suitable Extinguishing media As appropriate for surrounding fire. Extinguish with carbon dioxide, dry chemical,

> > foam or waterspray.

Unsuitable extinguishing media

Do not use water jet. Direct water jet may spread the fire.

5.2 Special hazards arising from the substance or mixture

May decompose in a fire giving off toxic fumes. Carbon monoxide, carbon dioxide and phenolic. Susceptible to polymerisation initiated by prolonged

heating or the presence of catalyst.

5.3 Advice for fire-fighters

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Do not breathe fumes. Keep containers cool by spraying

with water if exposed to fire. Avoid run off to waterways and sewers.

6. SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and

> emergency procedures **Environmental precautions**

Reference to other sections

Ensure adequate ventilation. Stop leak if safe to do so. Use personal protective

equipment as required. See Section: 8. Avoid breathing vapours.

Avoid release to the environment. Do not allow to enter drains, sewers or

6.3 Methods and material for containment and cleaning

6.2

6.4

Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a container for disposal. Ventilate the area and wash spill site after material pick-

up is complete. Dispose of this material and its container as hazardous waste

(2008/98/EEC).

See Section: 8, 13

7. **SECTION 7: HANDLING AND STORAGE**

7.1 Precautions for safe handling Avoid contact with skin, eyes or clothing. Do not breathe vapour. Ensure

> adequate ventilation. Use personal protective equipment as required. See Section: 8. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Susceptible to polymerisation initiated by prolonged heating or the presence of catalyst. Bulk: May undergo

autopolymerisation.

Conditions for safe storage, including any 7.2

incompatibilities

Storage temperature

Storage life

Incompatible materials

Store in a well-ventilated place. Keep container tightly closed. Keep away from

heat, sources of ignition and direct sunlight.

Ambient

Stable under normal conditions.

Keep away from: Acids, strong bases, Strong Oxidizing agents and halogenated

compounds.

7.3 PC14 Metal surface treatment products, including galvanic and electroplating Specific end use(s)

products.

8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

8.1.1 **Occupational Exposure Limits**

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m³)	STEL (ppm)	STEL (mg/m³)	Note:
Crystalline silica	14808-60-7	-	0.1 (1)	-	-	WEL
Magnesium silicate talc	14807-96-6	-	1 (2)	-	-	WEL

Note: WEL: Workplace Exposure Limit (UK HSE EH40)

(1): Silica, respirable crystalline.

(2): Respirable aerosol

Revision: 3.1 Date: 29.07.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypq.com

8.1.2 Biological limit value Not established.

8.1.3 **PNECs and DNELs** Not established.

8.2 **Exposure controls**

8.2.1 Appropriate engineering controls

8.2.2 Individual protection measures, such as personal protective equipment (PPE)

Ensure adequate ventilation or use appropriate containment. Atmospheric levels should be controlled in compliance with the occupational exposure limit. General hygiene measures for the handling of chemicals are applicable. Avoid contact with skin, eyes or clothing. Do not breathe vapour. Wash hands before breaks and after work. Keep work clothes separately. Contaminated clothing should be thoroughly cleaned. Do not eat, drink or smoke at the work place.

Eye/ face protection



Wear protective eye glasses for protection against liquid splashes. Wear eye protection with side protection (EN166).

Skin protection



Hand protection: Wear impervious gloves (EN374). Gloves should be changed regularly to avoid permeation problems. The gloves type used must be chosen based on the work activity and duration as well as concentration/quantity of material being handled.

Body protection: Wear impervious protective clothing, including boots, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection



In case of inadequate ventilation wear respiratory protection. Open system(s): Wear suitable respiratory protective equipment. Unlikely to present a dust hazard under normal handling conditions. Wear suitable respiratory protective equipment if processing involves working in areas where dusts or vapours are likely to be evolved.

Thermal hazards Not applicable.

Environmental Exposure Controls 8.2.3

Avoid release to the environment.

9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance Liquid Odour Not available. Odour threshold Not available. рΗ Not established. Melting point/freezing point Not established.

Initial boiling point and boiling range Not established. Flash point >94°C (Estimated) Evaporation rate Not applicable. Flammability (solid, gas) Not applicable - Liquid

Upper/lower flammability or explosive limits Not available.

Vapour pressure Not available. Vapour density Not established. Relative density 1.41 (H2O = 1) @ 25°C Solubility(ies) Not available.

Partition coefficient: n-octanol/water Not available. Auto-ignition temperature Not available. **Decomposition Temperature** Not available. >22 mm²/s @ 40°C Viscosity Explosive properties Not explosive. Oxidising properties Not oxidising.

Revision: 3.1 Date: 29.07.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypq.com

9.2 Other information None known.

10.	SECTION 10: STABILITY AND REACTIVITY	
10.1	Reactivity	Stable under normal conditions.
10.2	Chemical stability	Stable under normal conditions.
10.3	Possibility of hazardous reactions	Susceptible to polymerisation initiated by prolonged heating or the presence of catalyst. Bulk: May undergo autopolymerisation.
10.4	Conditions to avoid	Keep away from heat, sources of ignition and direct sunlight.
10.5	Incompatible materials	Keep away from: Acids, strong bases, Strong Oxidizing agents and halogenated compounds.
10.6	Hazardous decomposition product(s)	May decompose in a fire giving off toxic fumes. Carbon monoxide, Carbon dioxide and phenolic.

11. SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects (Substances in preparations / mixtures)

Acute toxicity

Skin Contact

Ingestion Based upon the available data, the classification criteria are not met.

Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg

bw/day.

Inhalation Based upon the available data, the classification criteria are not met.

Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 20.0 mg/l. Based upon the available data, the classification criteria are not met.

Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg

w/dav.

Skin corrosion/irritationSkin Irrit. 2: Causes skin irritation.Serious eye damage/irritationEye Irrit. 2: Causes serious eye irritation.

Serious eye damage/irritation Eye Irrit. 2. Causes serious eye irritation.

Respiratory or skin sensitizationSkin Sens. 1: May cause an allergic skin reaction. **Germ cell mutagenicity**Based upon the available data, the classification criteria are not met.

Carcinogenicity

Based upon the available data, the classification criteria are not met.

Reproductive toxicity

Based upon the available data, the classification criteria are not met.

Based upon the available data, the classification criteria are not met.

Based upon the available data, the classification criteria are not met.

Based upon the available data, the classification criteria are not met.

STOT - repeated exposure

STOT RE 1: Causes damage to organs through prolonged or repeated

exposure: Lungs.

Aspiration hazard Based upon the available data, the classification criteria are not met.

11.2 Other information None.

12. SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity	Aquatic Chronic 2: Toxic to aquatic life with long lasting effects.
---------------	---

Estimated Mixture LC50 > 1 ≤ 10 mg/l (Fish)

12.2 Persistence and degradability
 12.3 Bioaccumulative potential
 No data for the mixture as a whole.
 No data for the mixture as a whole.

12.4 Mobility in soil The product is predicted to have low mobility in soil. The product is essentially

insoluble in water.

12.5 Results of PBT and vPvB assessment Not classified as PBT or vPvB.

12.6 Other adverse effects None known.

13. SECTION 13: DISPOSAL CONSIDERATIONS

13.1	waste treatment methods	Do not release undiluted and unneutralised to the sewer. Dispose of this

material and its container as hazardous waste (2008/98/EEC). Send after pretreatment to a appropriate hazardous waste incinerator facility according to

egislation.

13.2 Additional Information Dispose of contents in accordance with local, state or national legislation.

Containers of this material may be hazardous when empty since they retain

product residue.

Revision: 3.1 Date: 29.07.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypg.com

14. SECTION 14: TRANSPORT INFORMATION

14.1 14.2	UN number UN proper shipping name	ADR/RID / IMDG / IATA UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S (Phenol, polymer with formaldehyde, glycidyl ether and Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700))
14.3	Transport hazard class(es)	9
14.4	Packing group	III
14.5	Environmental hazards	Classified as a Marine Pollutant/ Environmentally hazardous substance
14.6	Special precautions for user	See Section: 2
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.

15. SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental

Additional Information

regulations/legislation specific for the substance or

mixture

15.1.1 EU regulations

14.8

Substance(s) of Very High Concern (SVHCs)

None

None.

15.1.2 National regulations

Wassergefährdungsklasse (Germany)

Water hazard class: 2

15.2 Chemical Safety Assessment Not available.

16. SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

References: Existing Safety Data Sheet (SDS), Harmonised Classification(s) for Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700) (CAS# 25068-38-6), Existing ECHA registration(s) for Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700) (CAS# 25068-38-6), and the Classification and Labelling Inventory for Phenol, polymer with formaldehyde, glycidyl ether (CAS# 28064-14-4), Cyrstalline silica (CAS# 14808-60-7) and Magnesium silicate talc (CAS# 14807-96-6).

Classification of the substance or mixture According to Regulation (EC) No. 1272/2008 (CLP)	Classification Procedure
Skin Irrit. 2; H315	Threshold Calculation
Skin Sens. 1; H317	Threshold Calculation
Eye Irrit. 2; H319	Threshold Calculation
STOT RE 1; H372	Threshold Calculation
Aquatic Chronic 2; H411	Summation Calculation

LEGEND

LTEL Long Term Exposure Limit
STEL Short Term Exposure Limit
DNEL Derived No Effect Level

PNEC Predicted No Effect Concentration

PBT PBT: Persistent, Bioaccumulative and Toxic vPvB very Persistent and very Bioaccumulative

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Vishay Precision Group gives no warranty as to the fitness of

Revision: 3.1 Date: 29.07.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypg.com

the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Vishay Precision Group accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Annex to the extended Safety Data Sheet (eSDS)

No information available.