

Revision: 3.0 Date: 23 January 2017


ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vishaypg.com

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1	Product identifier Product Name	M-Bond 600 Adhesive
1.2	Relevant identified uses of the substance or mixture and uses advised against Identified Use(s) Uses Advised Against	Adhesives. Anything other than the above.
1.3	Details of the supplier of the safety data sheet Company Identification Telephone Fax E-Mail (competent person)	VISHAY MEASUREMENTS GROUP UK LTD Stroudley Road Basingstoke Hampshire RG24 8FW United Kingdom +44 (0) 1256 462131 +44 (0) 1256 471441 mm.uk@vishaypg.com
1.4	Emergency telephone number Emergency Phone No. Languages spoken	(00-1) 703-527-3887 All official European languages.
		CHEMTREC (24 hours)

SECTION 2: HAZARDS IDENTIFICATION

2.1	Classification of the substance or mixture	
2.1.1	Regulation (EC) No. 1272/2008 (CLP)	Flam. Liq. 2; H225 Acute Tox. 4; H302 Skin Irrit. 2; H315 Skin Sens. 1; H317 Eye Irrit. 2; H319 STOT SE 3; H335 Carc. 2; H351 Aquatic Chronic 2; H411
2.2	Label elements Product Name Contains: Hazard Pictogram(s)	According to Regulation (EC) No. 1272/2008 (CLP) M-Bond 600 Adhesive Tetrahydrofuran and Polyglycidyl Ether of Phenol-Formaldehyde 
	Signal Word(s)	DANGER
	Hazard Statement(s)	H225: Highly flammable liquid and vapour. H302: Harmful if swallowed. H315: Causes skin irritation. H317: May cause an allergic skin reaction. H319: Causes serious eye irritation. H335: May cause respiratory irritation. H351: Suspected of causing cancer. H411: Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

Revision: 3.0 Date: 23 January 2017

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vishaypg.com

Precautionary Statement(s)

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P201: Obtain special instructions before use.
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313: IF exposed or concerned: Get medical advice/attention.

Supplemental information

EUH019: May form explosive peroxides.

2.3 Other hazards

None known.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances Not applicable

3.2 Mixtures

EC Classification Regulation (EC) No. 1272/2008 (CLP)

Chemical identity of the substance	%W/W	CAS No.	EC No.	REACH Registration No.	Hazard Statement(s)
Tetrahydrofuran ^{^*}	45 – 55	109-99-9	203-726-8	Not yet assigned in the supply chain	Flam. Liq. 2; H225 Acute Tox. 4; H302 Eye Irrit. 2; H319 (SCL ≥ 25%) STOT SE 3; H335 (SCL ≥ 25%) Carc. 2; H351 EUH019
Polyglycidyl Ether of Phenol-Formaldehyde	30 – 40	28064-14-4	608-164-0	Not yet assigned in the supply chain	Skin Irrit. 2; H315 Skin Sens. 1; H317 Eye Irrit. 2; H319 Aquatic Chronic 2; H411
Ethyl methyl ketone ^{^*}	12-18	78-93-3	201-159-0	Not yet assigned in the supply chain	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066

For full text of H/P Statements see section 16. [^]Substance with a national exposure limit. *Substance with a community exposure limit

SECTION 4: FIRST AID MEASURES



4.1 Description of first aid measures

Self-protection of the first aider

Use personal protective equipment as required. Wear appropriate personal protective equipment, avoid direct contact. Ensure adequate ventilation. Avoid breathing vapours. Avoid all contact. Contaminated clothing should be laundered before reuse.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. IF exposed or concerned: Get medical advice/attention.

Skin Contact

IF ON SKIN: Remove contaminated clothing and wash all affected areas with plenty of water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention.

Revision: 3.0 Date: 23 January 2017

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vishaypg.com

Eye Contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention.
Ingestion	IF SWALLOWED: Rinse mouth. Make victim drink plenty of water. Do not give anything by mouth to an unconscious person. Do not induce vomiting unless instructed to do so by medical personnel. Call a POISON CENTER/doctor if you feel unwell. IF exposed or concerned: Get medical advice/attention.
4.2 Most important symptoms and effects, both acute and delayed	Harmful if swallowed. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. Suspected of causing cancer.
4.3 Indication of any immediate medical attention and special treatment needed	Treat symptomatically.
Notes to a physician:	IF INHALED: Respiratory symptoms, including pulmonary edema, may be delayed. IF IN EYES: After rinsing affected eyes must be seen by an ophthalmologist

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media	As appropriate for surrounding fire. Extinguish with carbon dioxide, dry chemical, foam or waterspray.
Suitable Extinguishing media	Do not use water jet. Direct water jet may spread the fire.
5.2 Special hazards arising from the substance or mixture	Highly flammable liquid and vapour. May decompose in a fire giving off toxic fumes. Carbon monoxide, Carbon dioxide, Phenolic and Explosive Peroxides. Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback. Prevent liquid entering sewers, basements and workpits; vapour may create explosive atmosphere. May form explosive peroxides.
Unsuitable extinguishing media	
5.3 Advice for fire-fighters	Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Do not breathe fumes. Keep containers cool by spraying with water if exposed to fire. Avoid run off to waterways and sewers.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures	Ensure adequate ventilation. Stop leak if safe to do so. Eliminate all ignition sources if safe to do so. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use personal protective equipment as required. See Section: 8. Avoid breathing vapours.
6.2 Environmental precautions	Avoid release to the environment. Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body.
6.3 Methods and material for containment and cleaning up	Use non-sparking equipment when picking up flammable spill. Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a container for disposal. Ventilate the area and wash spill site after material pick-up is complete. Dispose of this material and its container as hazardous waste
6.4 Reference to other sections	See Section: 8, 13

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling	Ensure operatives are trained to minimise exposures. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid all contact. Do not breathe vapour. Ensure adequate ventilation. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. May form explosive peroxides. Take precautionary measures against static discharges. Use personal protective equipment as required. See Section: 8. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work.
7.2 Conditions for safe storage, including any	Ground/bond container and receiving equipment. Keep only in original container.

Revision: 3.0 Date: 23 January 2017

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vishaypg.com

incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. May form explosive peroxides. Keep away from direct sunlight.

Storage temperature

Ambient. Keep at temperature not exceeding (°C): 32

Storage life

Stable under normal conditions.

Incompatible materials

Keep away from: Oxidizing agents, Corrosive Substances, Reducing agent, Strong Acids and Alkalis.

7.3 Specific end use(s)

See Section: 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters**8.1.1 Occupational Exposure Limits**

Users are advised to consider national Occupational Exposure Limits or other equivalent values.

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m ³)	STEL (ppm)	STEL (mg/m ³)	Note
Tetrahydrofuran	109-99-9	50	150	100	300	WEL, IOELV, Sk
Methyl ethyl ketone	78-93-3	200	600	300	899	WEL, Sk, BMGV
		200	600	300	900	IOELV

Source: WEL: Workplace Exposure Limit (UK HSE EH40), Sk - Can be absorbed through skin., Bmgv: Biological monitoring guidance value (UK HSE EH40), IOELV: Indicative Occupational Exposure Limit Value

8.1.2 Biological limit value

SUBSTANCE	CAS No.	Biological monitoring guidance value	Sampling Time
Methyl ethyl ketone	78-93-3	70 µmol butan-2-one/L in urine	Post shift

Note: Bmgv: Biological monitoring guidance value (UK HSE EH40)

8.1.3 PNECs and DNELs

None assigned.

8.2 Exposure controls**8.2.1 Appropriate engineering controls**

Ensure operatives are trained to minimise exposures. Ensure adequate ventilation. Atmospheric levels should be controlled in compliance with the occupational exposure limit.

8.2.2 Individual protection measures, such as personal protective equipment (PPE)

General hygiene measures for the handling of chemicals are applicable. Keep good industrial hygiene. Avoid all contact. Avoid breathing vapours. Wash hands before breaks and after work. Keep work clothes separately. Do not eat, drink or smoke at the work place.

IF exposed: Flush with fresh water if contact with skin or eyes.

Eye/ face protection



Wear protective eye glasses for protection against liquid splashes. Wear eye protection with side protection (EN166).

Skin protection

**Hand protection:**

Wear impervious gloves (EN374). Protective index 6, corresponding > 480 minutes of permeation time according to EN 374 Gloves should be changed regularly to avoid permeation problems. Breakthrough time of the glove material: refer to the information provided by the gloves' producer.

Suitable materials: Polyethylene-Laminate (Minimum thickness 0.1mm)

Revision: 3.0 Date: 23 January 2017

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vishaypg.com

Respiratory protection

**Body protection:**

Wear impervious protective clothing, including boots, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

In case of inadequate ventilation wear respiratory protection. A suitable mask with filter type A (EN141 or EN405) may be appropriate. A suitable mask with filter type A (EN141 or EN405) may be appropriate.

Thermal hazards

Not applicable

8.2.3 Environmental Exposure Controls

Avoid release to the environment.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	Almost colourless Liquid
Odour	Ether-like Odour
Odour threshold	Not available.
pH	Not established.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	66°C
Flash point	-14 °C (Mixture)
Evaporation rate	8 (BuAc = 1)
Flammability (solid, gas)	Not applicable - Liquid
Upper/lower flammability or explosive limits	Flammable Limits (Lower) (%v/v): 1.8 Flammable Limits (Upper) (%v/v): 11.8
Vapour pressure	129 (mmHg) @ 20°C
Vapour density	2.4 (Air = 1)
Relative density	0.9 (H ₂ O = 1)
Solubility(ies)	Water: >50%
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature	320 °C
Decomposition Temperature	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidising properties	Not oxidising.

9.2 Other information

VOC 598 g/L

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity	Stable under normal conditions. May form peroxides on prolonged storage if air is present.
10.2 Chemical stability	Stable under normal conditions.
10.3 Possibility of hazardous reactions	Highly flammable liquid and vapour. The vapour may be invisible, heavier than air and spread along ground. May form explosive peroxides. Contact with aliphatic amines will cause irreversible polymerization with considerable heat build-up.
10.4 Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from direct sunlight. Keep at a temperature not exceeding (°C): 32. Avoid contact with air. Avoid contact with heat and ignition sources and oxidizers. Avoid distillation to dryness, which can form explosive peroxides.
10.5 Incompatible materials	Oxidizing agents, Corrosive Substances, Reducing agent, Strong Acids and Alkalis.
10.6 Hazardous decomposition product(s)	May decompose in a fire giving off toxic fumes. Carbon monoxide, Carbon dioxide, Phenolic and Explosive Peroxides.

Revision: 3.0 Date: 23 January 2017

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vishaypg.com

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects	All test data taken from existing ECHA registrations for the substances mentioned.
Acute toxicity - Ingestion	Acute Tox. 4: Harmful if swallowed. Acute Toxicity Estimate Mixture Calculation: Estimated LC50 >750 mg/kg bw/day.
Tetrahydrofuran: Acute toxicity - Inhalation	Test Result LD50 <1 ml/kg bw (Standard acute method) Based upon the available data, the classification criteria are not met.
Acute toxicity - Skin Contact	Acute Toxicity Estimate Mixture Calculation: Estimated LC50 >20.0 mg/l. Based upon the available data, the classification criteria are not met. Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg bw/day.
Skin corrosion/irritation Polyglycidyl Ether of Phenol-Formaldehyde: Ethyl methyl ketone:	Skin Irrit. 2: Causes skin irritation. No data. EU classification and labelling inventory Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis. (Smith R & Mayers MR, 1944)
Serious eye damage/irritation Tetrahydrofuran: Polyglycidyl Ether of Phenol-Formaldehyde: Ethyl methyl ketone:	Eye Irrit. 2: Causes serious eye irritation. No data. Harmonised Classification No data. EU classification and labelling inventory Test Result: Irritating to eyes. (OECD 405)
Respiratory or skin sensitization Polyglycidyl Ether of Phenol-Formaldehyde:	Skin Sens. 1: May cause an allergic skin reaction. Allergic contact dermatitis (Pontén, A et al, 1999)
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity Tetrahydrofuran:	Carc. 2: Suspected of causing cancer. Test Result: NOAEC 1800 ppm Suspected carcinogen (Unnamed, 1998)
Reproductive toxicity	Based on available data, the classification criteria are not met.
STOT - single exposure Tetrahydrofuran: Ethyl methyl ketone:	STOT SE 3: May cause respiratory irritation. Test Result: Central nervous depression (Malley, L.A. et al, 2001) Rats at all dose levels: gait and/or posture abnormalities. Higher dose groups some rats were comatose or prostrate within a few hours of dosing, with some animals being unconscious for 24 hours. (OECD 423)
STOT - repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met.
11.2 Other information	None known.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity	Aquatic Chronic 2; Toxic to aquatic life with long lasting effects. Estimated Mixture LC50 > 1 to ≤ 10 mg/l. (Fish)
Polyglycidyl Ether of Phenol-Formaldehyde:	EC50 1.6 mg/l 48hr (Daphnia magna) (Wyness LE et al, 1993)
12.2 Persistence and degradability	Part of the components are poorly biodegradable.
12.3 Bioaccumulative potential	The product has low potential for bioaccumulation.
12.4 Mobility in soil	The product is predicted to have high mobility in soil.
12.5 Results of PBT and vPvB assessment	Not classified as PBT or vPvB.
12.6 Other adverse effects	None known.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods	Dispose of this material and its container as hazardous waste. Send after pre-treatment to a appropriate hazardous waste incinerator facility according to legislation. Send after pre-treatment to a appropriate hazardous waste incinerator facility according to legislation.
13.2 Additional Information	Dispose of contents in accordance with local, state or national legislation.

SECTION 14: TRANSPORT INFORMATION

14.1 UN number	ADR/RID UN 1133	IMDG UN 1133	IATA/ICAO UN 1133
-----------------------	---------------------------	------------------------	-----------------------------

SAFETY DATA SHEET

Revision: 3.0 Date: 23 January 2017

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vishaypg.com

14.2	UN proper shipping name	ADHESIVES containing flammable liquid	ADHESIVES containing flammable liquid	ADHESIVES containing flammable liquid
14.3	Transport hazard class(es)	3	3	3
14.4	Packing group	II	II	II
14.5	Environmental hazards	Environmentally hazardous substance	Classified as a Marine Pollutant.	Environmentally hazardous substance
14.6	Special precautions for user	See Section: 2		
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.		

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1 EU regulations

Authorisations and/or Restrictions On Use
CoRAP Substance Evaluation

Not restricted

Tetrahydrofuran:

Substance evaluated in 2013; evaluating Member State has proposed to ask the registrants to provide further information

Ethyl methyl ketone:

Substance identified for evaluation in 2018

15.1.2 National regulations

Germany

Water hazard class: 2

15.2 Chemical Safety Assessment

A chemical safety assessment is not required under REACH.

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: New SDS Regulation 2015/830 format, all sections have been updated to include new information. Please review SDS with care.

References:

Existing Safety Data Sheet (SDS), Harmonised Classification(s) for Tetrahydrofuran (CAS No. 109-99-9) and Ethyl methyl ketone (CAS No. 78-93-3). Existing ECHA registration(s) for Tetrahydrofuran (CAS No. 109-99-9), Ethyl methyl ketone (CAS No. 78-93-3) the Classification and Labelling Inventory for Polyglycidyl Ether of Phenol-Formaldehyde (CAS No. 28064-14-4).

Literature References:

- Smith R & Mayers MR, 1944, Study of poisoning and fire hazards of butanone and acetone, Industrial Hygiene: 23, 174-176
- Pontén, A. and Bruze, M. (1999), Occupational allergic contact dermatitis from epoxy resins based on bisphenol F. Contact Dermatitis, 41: 235. doi:10.1111/j.1600-0536.1999.tb06149.x
- Malley, L.A., Christoph G.R., Stadler, J.C., Hansen, J.F., Biesemeir, J.A. and Jasti, S., 2001, Acute and subchronic neurotoxicology evaluation of tetrahydrofuran by inhalation in rats, Drug Chem. Toxicol., 24(3): 201-219
- Wyness LE, Cheeman H, Lad DD and Baldwin MK (1993), EPIKOTE 862: Acute toxicity to *Oncorhynchus mykiss*, *Daphnia magna* and *Selenastrum capricornutum*; SBGR.92.237

EU Classification: This Safety Data Sheet was prepared in accordance with EC Regulation (EC) 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830.

Classification of the substance or mixture According to Regulation (EC) No. 1272/2008 (CLP)	Classification Procedure
Flam. Liq. 2; H225	Flash Point [Closed cup] Test Result/ Boiling Point (°C) Test Result
Acute Tox. 4; H302	Acute Toxicity Estimate (ATE) Calculation.
Skin Irrit. 2; H315	Threshold Calculation
Skin Sens. 1; H317	Threshold Calculation
Eye Irrit. 2; H319	Threshold Calculation
STOT SE 3; H335	Threshold Calculation
Carc. 2; H351	Threshold Calculation
Aquatic Chronic 2	Summation Calculation

SAFETY DATA SHEET

Revision: 3.0 Date: 23 January 2017

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vishaypg.com

LEGEND

LTEL: Long Term Exposure Limit

DNEL: Derived No Effect Level

PBT: PBT: Persistent, Bioaccumulative and Toxic

STEL: Short Term Exposure Limit

PNEC: Predicted No Effect Concentration

vPvB: very Persistent and very Bioaccumulative

Hazard classification / Classification code:

Flam. Liq. 2; Flammable Liquid, Category 2

Acute Tox. 4; Acute toxicity, Category 4

Skin Irrit. 2; Skin corrosion/irritation, Category 2

Skin Sens. 1; Skin Sensitisation, Category 1

Eye Irrit. 2; Eye Irritation, Category 2

STOT SE 3; Specific target organ toxicity — single exposure, Category 3

STOT SE 3; Specific target organ toxicity — single exposure, Category 3

Carc. 2; Carcinogenicity, Category 2

Aquatic Chronic 2; Hazardous to the aquatic environment, Chronic ,
Category 2

EUH066: Repeated exposure may cause skin dryness or cracking.

EUH019: May form explosive peroxides.

Hazard Statement(s)

H225: Highly flammable liquid and vapour.

H302: Harmful if swallowed.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H351: Suspected of causing cancer.

H411: Toxic to aquatic life with long lasting effects.

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Vishay Precision Group gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Vishay Precision Group accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.