Revision: 2.2 Date: 29.07.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypg.com

# 1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product Name M-BOND GA-61 Part A

Chemical Name Mixture
CAS No. Mixture
EINECS No. Mixture
REACH Registration No. None assigned.

1.2 Relevant identified uses of the substance or mixture

and uses advised against

Identified Use(s) PC14 Metal surface treatment products, including galvanic and electroplating

products.

Uses Advised Against None known.

1.3 Details of the supplier of the safety data sheet

Company Identification VISHAY MEASUREMENTS GROUP UK LTD

Stroudley Road Basingstoke Hampshire RG24 8FW United Kingdom

 Telephone
 +44 (0) 1256 462131

 Fax
 +44 (0) 1256 471441

 E-Mail (competent person)
 mm.uk@vishaypg.com

**1.4 Emergency telephone number** (00-1) 703-527-3887

CHEMTREC

# 2. SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

**2.1.1 Regulation (EC) No. 1272/2008 (CLP)** Skin Irrit. 2; H315

Skin Sens. 1; H317 Eye Irrit. 2; H319 Aquatic Chronic 2; H411

2.2 Label elements According to Regulation (EC) No. 1272/2008 (CLP)

Product Name EPY-500 Part A

Hazard Pictogram(s)





Signal Word(s) Warning

Contains: Phenol, polymer with formaldehyde, glycidyl ether and Reaction product:

Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤

700)

Hazard Statement(s) H315: Causes skin irritation.

H317: May cause an allergic skin reaction. H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

Precautionary Statement(s) P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of water.

Revision: 2.2 Date: 29.07.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypq.com

P333+P313: If skin irritation or rash occurs: Get medical advice/attention. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313: If eye irritation persists: Get medical advice/attention.

P273: Avoid release to the environment.

**Additional Information** None.

2.3 Other hazards Susceptible to polymerisation initiated by prolonged heating or the presence of

catalyst. Bulk: May undergo autopolymerisation.

#### 3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.2 **Mixtures**

EC Classification Regulation (EC) No. 1272/2008 (CLP)

Chemical identity of the substance	%W/W	CAS No.	EC No.	REACH Registration No.	Hazard Statement(s)
Polyglycidyl Ether of Phenol- Formaldehyde	< 87	28064-14-4	-	None assigned	Eye Irrit. 2; H319 Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 2; H411
Magnesium silicate talc	5 - 10	14807-96-6	238-877-9	None assigned	Not classified
Reaction product: <b>B</b> isphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	< 5	25068-38-6	500-033-5	None assigned	Skin Irrit. 2; H315 (SCL: ≥ 5%) Eye Irrit. 2; H319 (SCL: ≥ 5%) Skin Sens. 1; H317 Aquatic Chronic 2; H411

H315: Causes skin irritation. H317: May cause an allergic skin reaction. H319: Causes serious eye irritation. H411: Toxic to aquatic life with long lasting effects. SCL: Specific Concentration Limit.

#### **SECTION 4: FIRST AID MEASURES** 4.



4.2

### Description of first aid measures

Inhalation If breathing is difficult, remove victim to fresh air and keep at rest in a position

comfortable for breathing.

Skin Contact IF ON SKIN: Remove contaminated clothing and wash all affected areas with

plenty of water. Contaminated clothing should be thoroughly cleaned. If skin

irritation or rash occurs: Get medical advice/attention.

Eye Contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get

medical advice/attention.

Ingestion Do not give milk or alcoholic beverages. Do not give anything by mouth to an

unconscious person. Obtain medical attention if ill effects occur. Most important symptoms and effects, both acute and

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Overexposure may aggravate existing eye, skin, and/or respiratory

disorders.

4.3 Indication of any immediate medical attention and

special treatment needed

Treat symptomatically.

#### 5. **SECTION 5: FIREFIGHTING MEASURES**

#### 5.1 **Extinguishing media**

Suitable Extinguishing media

As appropriate for surrounding fire. Extinguish with carbon dioxide, dry chemical,

DOCUMENT NO. 14177 **REVISION O** Page: 2 of 6

Revision: 2.2 Date: 29.07.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypq.com

foam or waterspray. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may

Do not use water jet. Direct water jet may spread the fire.

function, but will be less effective.

Unsuitable extinguishing media
Special hazards arising from the substance or mixture

May decompose in a fire giving off toxic fumes. Carbon monoxide, Carbon dioxide and phenolic. Dense smoke is emitted when burned without sufficient oxygen. Susceptible to polymerisation initiated by prolonged heating or the

presence of catalyst.

5.3 Advice for fire-fighters

5.2

6.4

7.3

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Do not breathe fumes. Keep containers cool by spraying

with water if exposed to fire. Avoid run off to waterways and sewers.

### 6. SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

6.2 Environmental precautions

Ensure adequate ventilation. Stop leak if safe to do so. Avoid breathing vapours. Use personal protective equipment as required. See Section: 8.

Avoid release to the environment. Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body.

6.3 Methods and material for containment and cleaning up

Reference to other sections

Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a container for disposal. Dispose of this material and its container as hazardous waste (2008/98/EEC).

See Section: 8. 13

## 7. SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Ensure adequate ventilation. Avoid breathing vapours. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. See Section: 8. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Susceptible to polymerisation initiated by prolonged heating or the presence of catalyst. Bulk: May undergo autopolymerisation.

7.2 Conditions for safe storage, including any

incompatibilities

Storage temperature

Storage life

Incompatible materials

Specific end use(s)

Ambient.

Stable under normal conditions.

Keep away from: Polymerisation catalysts such as peroxy or azo compounds,

strong acids, alkalis, oxidising agents and metal salts.

Keep away from heat, sources of ignition and direct sunlight.

PC14 Metal surface treatment products, including galvanic and electroplating

products. See Section: 1.2

# 8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

# 8.1.1 Occupational Exposure Limits

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m³)	STEL (ppm)	STEL (mg/m³)	Note:
Magnesium silicate talc	14807-96-6	-	1*	-	-	WEL

Note: WEL: Workplace Exposure Limit (UK HSE EH40)

\*Respirable aerosol

8.1.2 Biological limit value Not established.

8.1.3 PNECs and DNELs Not established.

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure adequate ventilation or use appropriate containment. Atmospheric levels

Revision: 2.2 Date: 29.07.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypq.com

# 8.2.2 Individual protection measures, such as personal protective equipment (PPE)

should be controlled in compliance with the occupational exposure limit. General hygiene measures for the handling of chemicals are applicable. Avoid breathing vapours. Avoid contact with skin, eyes or clothing. Wash hands before breaks and after work. Keep work clothes separately. Contaminated clothing should be thoroughly cleaned. Do not eat, drink or smoke at the work place.

Eye/ face protection



Wear protective eye glasses for protection against liquid splashes. Wear eye protection with side protection (EN166).



Hand protection: Wear impervious gloves (EN374). Gloves should be changed regularly to avoid permeation problems. Breakthrough time of the glove material: refer to the information provided by the gloves' producer. The gloves type used must be chosen based on the work activity and duration as well as concentration/quantity of material being handled.

Body protection: Wear impervious protective clothing, including boots, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection



Thermal hazards

In case of inadequate ventilation wear respiratory protection. Open system(s): Wear suitable respiratory protective equipment.

Not applicable.

8.2.3 Environmental Exposure Controls

Avoid release to the environment.

### 9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

Appearance Liquid Not available. Odour Not available. Odour threshold Not available. Melting point/freezing point Not available. Initial boiling point and boiling range Not available. >94°C Flash point Evaporation rate Not applicable. Flammability (solid, gas) Not applicable - liquid Not applicable.

Upper/lower flammability or explosive limits Vapour pressure Not available. Vapour density Not available. 1.27 @ 25°C Relative density Solubility(ies) Not established. Partition coefficient: n-octanol/water Not available. Auto-ignition temperature Not available. **Decomposition Temperature** Not available. Viscosity >22 mm<sup>2</sup>/s @ 40°C Explosive properties Not explosive. Oxidising properties Not oxidising.

9.2 Other information None.

# 10. SECTION 10: STABILITY AND REACTIVITY

10.1 Stability and reactivity
 10.2 Chemical stability
 Stable under normal conditions.
 Stable under normal conditions.

Revision: 2.2 Date: 29.07.2015

Incompatible materials

10.5

10.6

12.2

12.3

12.4



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypq.com

10.3 Possibility of hazardous reactions Susceptible to polymerisation initiated by prolonged heating or the presence of

catalyst. Bulk: May undergo autopolymerisation.

10.4 Conditions to avoid Keep away from heat, sources of ignition and direct sunlight.

Polymerisation catalysts such as peroxy or azo compounds, strong acids,

alkalis, oxidising agents and metal salts.

May decompose in a fire giving off toxic fumes. Carbon monoxide, Carbon

dioxide and phenolic.

#### 11. SECTION 11: TOXICOLOGICAL INFORMATION

Hazardous decomposition product(s)

#### 11.1 Information on toxicological effects (Substances in preparations / mixtures)

**Acute toxicity** 

Skin Contact

Ingestion Based upon the available data, the classification criteria are not met.

Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg

bw/day.

Inhalation Based upon the available data, the classification criteria are not met.

> Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 20.0 mg/l. Based upon the available data, the classification criteria are not met.

Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg

bw/day.

Skin corrosion/irritation Skin Irrit. 2: Causes skin irritation. Serious eye damage/irritation Eye Irrit. 2: Causes serious eye irritation.

Respiratory or skin sensitization Skin Sens. 1: May cause an allergic skin reaction.

Germ cell mutagenicity Based upon the available data, the classification criteria are not met. Carcinogenicity Based upon the available data, the classification criteria are not met. Reproductive toxicity Based upon the available data, the classification criteria are not met. STOT - single exposure Based upon the available data, the classification criteria are not met. STOT - repeated exposure Based upon the available data, the classification criteria are not met. Aspiration hazard Based upon the available data, the classification criteria are not met.

11.2 Other information

#### SECTION 12: ECOLOGICAL INFORMATION 12.

**Bioaccumulative potential** 

Mobility in soil

12.1 **Toxicity** Aquatic Chronic 2: Toxic to aquatic life with long lasting effects.

Estimated Mixture LC50 >1 ≤ 10 mg/l (Fish) Persistence and degradability Part of the components are poorly biodegradable. The product has low potential for bioaccumulation. The product is predicted to have low mobility in soil.

12.5 Results of PBT and vPvB assessment Not classified as PBT or vPvB.

12.6 Other adverse effects None known.

#### 13. SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods This material and its container must be disposed of as hazardous waste

> (2008/98/EEC). Containers of this material may be hazardous when empty since they retain product residue. Send after pre-treatment to a appropriate hazardous

waste incinerator facility according to legislation.

13.2 **Additional Information** Dispose of contents in accordance with local, state or national legislation.

#### 14. SECTION 14: TRANSPORT INFORMATION

ADR/RID / IMDG / IATA

14.1 **UN number** UN 3082

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Phenol, 14.2 UN proper shipping name

polymer with formaldehyde, glycidyl ether and Reaction product: bisphenol-A-

(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700))

14.3 Transport hazard class(es)

Revision: 2.2 Date: 29.07.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypq.com

14.4 Packing group III

**14.5 Environmental hazards** Classified as a Marine Pollutant/ Environmentally hazardous substance.

14.6 Special precautions for user See Section: 2
 14.7 Transport in bulk according to Annex II of MARPOL Not applicable.

73/78 and the IBC Code

14.8 Additional Information None.

### 15. SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental

regulations/legislation specific for the substance or

mixture

15.1.1 EU regulations

Substance(s) of Very High Concern (SVHCs)

None

15.1.2 National regulations

Wassergefährdungsklasse (Germany) Water hazard class: 2

15.2 Chemical Safety Assessment Not available.

### 16. SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

References: Existing Safety Data Sheet (SDS), Harmonised Classification(s) for Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq$  700) (CAS# 25068-38-6), Existing ECHA registration(s) for Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq$  700) (CAS#25068-38-6) and the Classification and Labelling Inventory for Phenol, polymer with formaldehyde, glycidyl ether (CAS# 28064-14-4) and Magnesium silicate talc (CAS# 14807-96-6).

Classification of the substance or mixture According to	Classification Procedure		
Regulation (EC) No. 1272/2008 (CLP)			
Skin Irrit. 2; H315	Threshold Calculation		
Skin Sens. 1; H317	Threshold Calculation		
Eye Irrit. 2; H19	Threshold Calculation		
Aquatic Chronic 2; H411	Summation Calculation		

### **LEGEND**

LTEL Long Term Exposure Limit
STEL Short Term Exposure Limit
DNEL Derived No Effect Level

PNEC Predicted No Effect Concentration

PBT PBT: Persistent, Bioaccumulative and Toxic vPvB very Persistent and very Bioaccumulative

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

### **Disclaimers**

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Vishay Precision Group gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Vishay Precision Group accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

### Annex to the extended Safety Data Sheet (eSDS)

No information available.