

SAFETY DATA SHEET

Revision: 1.1 Date: 28.08.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vpgsensors.com

1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier**
Product Name RS-200-CK Cement (Grip Cement Liquid)
Chemical Name Mixture
CAS No. Mixture
EINECS No. Mixture
REACH Registration No. None assigned.
- 1.2 Relevant identified uses of the substance or mixture and uses advised against**
Identified Use(s) Adhesives
Uses Advised Against None known.
- 1.3 Details of the supplier of the safety data sheet**
Company Identification VISHAY MEASUREMENTS GROUP UK LTD
Stroudley Road
Basingstoke
Hampshire
United Kingdom
RG24 8FW
Telephone +44 (0) 1256 462131
Fax +44 (0) 1256 471441
E-Mail (competent person) mm.uk@vishaypg.com
- 1.4 Emergency telephone number** (00-1) 703-527-3887
CHEMTREC

2. SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture**
2.1.1 Regulation (EC) No. 1272/2008 (CLP) Flam. Liq. 2; H225
Skin Irrit. 2; H315
Skin Sens. 1; H317
STOT SE 3; H335
- 2.2 Label elements**
Product Name According to Regulation (EC) No. 1272/2008 (CLP)
RS-200-CK Cement (Grip Cement Liquid)
- Hazard Pictogram(s)
- 
- Signal Word(s) Danger
Contains: Methyl methacrylate
- Hazard Statement(s)
H225: Highly flammable liquid and vapour.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H335: May cause respiratory irritation.
- Precautionary Statement(s)
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261: Avoid breathing vapours.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352: IF ON SKIN: Wash with plenty of water.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
P312: Call a POISON CENTER/doctor if you feel unwell.

SAFETY DATA SHEET

Revision: 1.1 Date: 28.08.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vpgsensors.com

Additional Information

None.

2.3 Other hazards

Susceptible to violent exothermic polymerisation, initiated by heating or the presence of catalysts.

3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances Not applicable.

3.2 Mixtures

EC Classification Regulation (EC) No. 1272/2008 (CLP)

| Chemical identity of the substance | %W/W | CAS No. | EC No. | REACH Registration No. | Hazard Statement(s) |
|------------------------------------|------|---------|-----------|------------------------|--|
| Methyl methacrylate | 99 | 80-62-6 | 201-297-1 | None assigned | Flam. Liq. 2; H225 Skin Irrit. 2; H315 Skin Sens. 1; H317 STOT SE 3; H335 |
| N,N-Dimethyl-p-toluidine | 1 | 99-97-8 | 202-805-4 | None assigned | Acute Tox. 3; H301 Acute Tox. 3; H311 Acute Tox. 3; H331 STOT RE 2; H373 Aquatic Chronic 3; H412 |

H225: Highly flammable liquid and vapour. H301: Toxic if swallowed. H311: Toxic in contact with skin. H315: Causes skin irritation. H317: May cause an allergic skin reaction. H331: Toxic if inhaled. H335: May cause respiratory irritation. H373: May cause damage to organs through prolonged or repeated exposure. H412: Harmful to aquatic life with long lasting effects.

4. SECTION 4: FIRST AID MEASURES



4.1 Description of first aid measures

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Call a POISON CENTER/doctor if you feel unwell.

Skin Contact

IF ON SKIN (or hair): Remove contaminated clothing and wash all affected areas with plenty of water. Contaminated clothing should be thoroughly cleaned. If skin irritation or rash occurs: Get medical advice/attention.

Eye Contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion

IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Do not give anything by mouth to an unconscious person. If symptoms occur obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

5. SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable Extinguishing media

As appropriate for surrounding fire. Use CO₂, dry chemical, or foam.

Unsuitable extinguishing media

Do not use water.

SAFETY DATA SHEET

Revision: 1.1 Date: 28.08.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vpgsensors.com

- 5.2 Special hazards arising from the substance or mixture** Highly flammable liquid and vapour. Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback. May polymerise on exposure to heat. Sealed containers may rupture explosively if hot. May decompose in a fire giving off toxic fumes. Oxides of carbon.
- 5.3 Advice for fire-fighters** Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Do not breathe fumes. Keep containers cool by spraying with water if exposed to fire. Avoid run off to waterways and sewers.

6. SECTION 6: ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation. Stop leak if safe to do so. Eliminate all ignition sources if safe to do so. Avoid breathing vapours. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. See Section: 8.
- 6.2 Environmental precautions** Avoid release to the environment. Prevent liquid entering sewers, basements and workpits; vapour may create explosive atmosphere.
- 6.3 Methods and material for containment and cleaning up** Ensure suitable personal protection (including respiratory protection) during removal of spillages. Use non-sparking equipment when picking up flammable spill.
Small spillages: Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a container for disposal.
Large spillages: Contain spillages. Collect mechanically and dispose of according to Section 13.
Ventilate the area and wash spill site after material pick-up is complete. Dispose of this material and its container as hazardous waste (2008/98/EEC).
- 6.4 Reference to other sections** See Section: 8, 13

7. SECTION 7: HANDLING AND STORAGE

- 7.1 Precautions for safe handling** Ensure adequate ventilation. Avoid breathing vapours. Avoid contact with skin, eyes or clothing. In case of inadequate ventilation wear respiratory protection. Use personal protective equipment as required. See Section: 8. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Do not eat, drink or smoke when using this product. Take precautionary measures against static discharge. Protect from light.
- 7.2 Conditions for safe storage, including any incompatibilities** Ground/bond container and receiving equipment. Keep container tightly closed, in a cool, well ventilated place. Keep only in original container. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from light.
Storage temperature Keep at a temperature not exceeding (°C): 30
Storage life Stable under normal conditions.
Incompatible materials Keep away from: Acids, strong bases, Strong oxidising agents, Reducing agent, Amines and UV light.
- 7.3 Specific end use(s)** Adhesives

8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

- 8.1 Control parameters**
8.1.1 Occupational Exposure Limits

| SUBSTANCE | CAS No. | LTEL (8 hr TWA ppm) | LTEL (8 hr TWA mg/m ³) | STEL (ppm) | STEL (mg/m ³) | Note |
|---------------------|---------|---------------------|------------------------------------|------------|---------------------------|------|
| Methyl methacrylate | 80-62-6 | 50 | 208 | 100 | 416 | WEL |

Note: WEL: Workplace Exposure Limit (UK HSE EH40)

- 8.1.2 Biological limit value** Not established.
- 8.1.3 PNECs and DNELs** Not established.

SAFETY DATA SHEET

Revision: 1.1 Date: 28.08.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vpgsensors.com

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure adequate ventilation or use appropriate containment. Atmospheric levels should be controlled in compliance with the occupational exposure limit. Use non-sparking ventilation systems, approved explosion-proof equipment, and intrinsically safe electrical systems. Guarantee that the eye flushing systems and safety showers are located close to the working place.

8.2.2 Individual protection measures, such as personal protective equipment (PPE)

General hygiene measures for the handling of chemicals are applicable. Avoid breathing vapours. Avoid contact with skin, eyes or clothing. Wash hands before breaks and after work. Keep work clothes separately. Do not eat, drink or smoke at the work place.

Eye/ face protection



Wear goggles giving complete protection to eyes to protect against liquid splashes (EN166).

Skin protection



Hand protection: Wear impervious gloves (EN374). Gloves should be changed regularly to avoid permeation problems. Breakthrough time of the glove material: refer to the information provided by the gloves' producer.

Body protection: Wear impervious protective clothing, including boots, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection



In case of inadequate ventilation wear respiratory protection. Open system(s): Wear suitable respiratory protective equipment.

Thermal hazards

Not applicable.

8.2.3 Environmental Exposure Controls

Avoid release to the environment.

9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

| | |
|--|---|
| Appearance | Colourless liquid |
| Odour | Strong acrid acrylic odour |
| Odour threshold | Not available. |
| pH | Not established. |
| Melting point/freezing point | - 48°C |
| Initial boiling point and boiling range | 100.36°C (Methylmethacrylate (CAS# 80-62-6)) |
| Flash point | 9°C [Closed cup] |
| Evaporation rate | >1 (BuAc = 1) |
| Flammability (solid, gas) | Not applicable - Liquid |
| Upper/lower flammability or explosive limits | Flammable Limits (Lower) (%v/v): 2.1 Flammable Limits (Upper) (%v/v): 12.5 |
| Vapour pressure | 29 mm Hg |
| Vapour density | 3.5 (Air = 1) |
| Relative density | 0.94 (H2O = 1) |
| Solubility(ies) | 15.3 g/L (Water @ 20°C) (Methylmethacrylate (CAS# 80-62-6)) |
| Partition coefficient: n-octanol/water | 1.24 Log Pow (Methylmethacrylate (CAS# 80-62-6)) |
| Auto-ignition temperature | 320 °C (Mixture) |
| Decomposition Temperature | Not available. |
| Viscosity | 0.6 mPa s (20°C) |
| Explosive properties | Not explosive. |
| Oxidising properties | Not oxidising. |

9.2 Other information

None.

SAFETY DATA SHEET

Revision: 1.1 Date: 28.08.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vpgsensors.com

10. SECTION 10: STABILITY AND REACTIVITY

| | | |
|------|------------------------------------|---|
| 10.1 | Stability and reactivity | Stable under normal conditions. |
| 10.2 | Chemical stability | Stable under normal conditions. |
| 10.3 | Possibility of hazardous reactions | Highly flammable liquid and vapour. The vapour may be invisible, heavier than air and spread along ground. Susceptible to violent exothermic polymerisation, initiated by heating or the presence of catalysts. |
| 10.4 | Conditions to avoid | Keep away from heat, sources of ignition and direct sunlight. |
| 10.5 | Incompatible materials | Keep away from: Acids, strong bases, Strong oxidising agents, Reducing agent, Amines and UV light. |
| 10.6 | Hazardous decomposition product(s) | May decompose in a fire giving off toxic fumes. Carbon monoxide, Carbon dioxide and Acrid smoke. |

11. SECTION 11: TOXICOLOGICAL INFORMATION

| | | |
|------|--|---|
| 11.1 | Information on toxicological effects (Substances in preparations / mixtures) | |
| | Acute toxicity | |
| | Ingestion | Based upon the available data, the classification criteria are not met. Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg bw/day. |
| | Inhalation | Based upon the available data, the classification criteria are not met. Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 20 mg/l. |
| | Skin Contact | Based upon the available data, the classification criteria are not met. Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg bw/day. |
| | Skin corrosion/irritation | Skin Irrit. 2: Causes skin irritation. |
| | Serious eye damage/irritation | Based upon the available data, the classification criteria are not met. |
| | Respiratory or skin sensitization | Skin Sens. 1: May cause an allergic skin reaction. |
| | Germ cell mutagenicity | Based upon the available data, the classification criteria are not met. |
| | Carcinogenicity | Based upon the available data, the classification criteria are not met. |
| | Reproductive toxicity | Based upon the available data, the classification criteria are not met. |
| | STOT - single exposure | STOT SE 3: May cause respiratory irritation. |
| | STOT - repeated exposure | Based upon the available data, the classification criteria are not met. |
| | Aspiration hazard | Based upon the available data, the classification criteria are not met. |
| 11.2 | Other information | None. |

12. SECTION 12: ECOLOGICAL INFORMATION

| | | |
|------|------------------------------------|---|
| 12.1 | Toxicity | Based upon the available data, the classification criteria are not met. Estimated Mixture LC50 > 100 mg/l (Fish) |
| 12.2 | Persistence and degradability | This product is readily biodegradable in water. |
| 12.3 | Bioaccumulative potential | The product has no potential for bioaccumulation. |
| 12.4 | Mobility in soil | The product is predicted to have high mobility in soil. Water Soluble / Highly volatile. |
| 12.5 | Results of PBT and vPvB assessment | Not classified as PBT or vPvB. |
| 12.6 | Other adverse effects | None known. |

13. SECTION 13: DISPOSAL CONSIDERATIONS

| | | |
|------|-------------------------|---|
| 13.1 | Waste treatment methods | Do not release undiluted and unneutralised to the sewer. Containers of this material may be hazardous when empty since they retain product residue. This material and its container must be disposed of as hazardous waste (2008/98/EEC). |
| 13.2 | Additional Information | Disposal should be in accordance with local, state or national legislation. |

SAFETY DATA SHEET

Revision: 1.1 Date: 28.08.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vpgsensors.com

14. SECTION 14: TRANSPORT INFORMATION

| | ADR/RID / IMDG / IATA |
|---|---|
| 14.1 UN number | UN 1247 |
| 14.2 UN proper shipping name | METHYL METHACRYLATE MONOMER, STABILIZED |
| 14.3 Transport hazard class(es) | 3 |
| 14.4 Packing group | II |
| 14.5 Environmental hazards | Not classified as a Marine Pollutant./Environmentally hazardous substance |
| 14.6 Special precautions for user | See Section: 2 |
| 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | Not applicable. |
| 14.8 Additional Information | None. |

15. SECTION 15: REGULATORY INFORMATION

| | |
|---|-----------------------|
| 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture | |
| 15.1.1 EU regulations | |
| Substances of Very High Concern (SVHCs) | None. |
| Authorisations and/or Restrictions On Use | None. |
| 15.1.2 National regulations | |
| Wassergefährdungsklasse (Germany) | Water hazard class: 1 |
| 15.2 Chemical Safety Assessment | Not available. |

16. SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

References: Existing Safety Data Sheet (SDS). Harmonised Classification(s) for Methylmethacrylate (CAS# 80-62-6) and N,N-Dimethyl-p-toluidine (CAS# 99-97-8). Existing ECHA registration(s) for Harmonised Classification(s) for Methylmethacrylate (CAS# 80-62-6) and N,N-Dimethyl-p-toluidine (CAS# 99-97-8).

| Classification of the substance or mixture According to Regulation (EC) No. 1272/2008 (CLP) | Classification Procedure |
|---|--|
| Flam. Liq. 2; H225 | Flash Point [Closed cup] Test Result/ Estimated Boiling Point (°C) |
| Skin Irrit. 2; H315 | Threshold Calculation |
| Skin Sens. 1; H317 | Threshold Calculation |
| STOT SE 3; H335 | Threshold Calculation |

LEGEND

| | |
|------|--|
| LTEL | Long Term Exposure Limit |
| STEL | Short Term Exposure Limit |
| DNEL | Derived No Effect Level |
| PNEC | Predicted No Effect Concentration |
| PBT | PBT: Persistent, Bioaccumulative and Toxic |
| vPvB | very Persistent and very Bioaccumulative |

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Vishay Precision Group gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is

SAFETY DATA SHEET



Revision: 1.1 Date: 28.08.2015

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),
1272/2008 (CLP) & 2015/830

www.vpgsensors.com

prevented by law. Vishay Precision Group accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Annex to the extended Safety Data Sheet (eSDS)

No information available.