Revision: 2.0 Date: 26.08.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypq.com

1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product Name RS-200-CK Cement (Grip Cement Powder)

Chemical Name Mixture
CAS No. Mixture
EINECS No. Mixture
REACH Registration No. None assigned.

1.2 Relevant identified uses of the substance or mixture

and uses advised against

Identified Use(s) Adhesives.
Uses Advised Against None known.

1.3 Details of the supplier of the safety data sheet

Company Identification VISHAY MEASUREMENTS GROUP UK LTD

Stroudley Road Basingstoke Hampshire RG24 8FW United Kingdom

 Telephone
 +44 (0) 1256 462131

 Fax
 +44 (0) 1256 471441

 E-Mail (competent person)
 mm.uk@vishaypg.com

1.4 Emergency telephone number (00-1) 703-527-3887

CHEMTREC

2. SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

2.1.1 Regulation (EC) No. 1272/2008 (CLP) Skin Irrit. 2; H315 Skin Sens. 1; H317

Eye Irrit. 2; H319 Aquatic Acute 1; H400

2.2 Label elements According to Regulation (EC) No. 1272/2008 (CLP)

Product Name RS-200-CK (Grip Cement Powder)

Hazard Pictogram(s)





Signal Word(s) Warning

Contains: Dibenzoyl Peroxide

Hazard Statement(s) H315: Causes skin irritation.

H317: May cause an allergic skin reaction. H319: Causes serious eye irritation. H400: Very toxic to aquatic life.

Precautionary Statement(s) P261: Avoid breathing dust.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of water.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes.

Revision: 2.0 Date: 26.08.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypq.com

Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313: If eye irritation persists: Get medical advice/attention.

2.3 Other hazards

May form explosive dust/air mixtures.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS Direct water jet may spread the fire.

3.1 Substances Not applicable

3.2 Mixtures

EC Classification Regulation (EC) No. 1272/2008 (CLP)

| Chemical identity of the substance | %W/W | CAS No. | EC No. | REACH Registration No. | Hazard Statement(s) |
|---|---------|-----------|-----------|------------------------|---|
| Calcium Tungstate | 60 - 70 | 7790-75-2 | 232-219-4 | None assigned. | Not classified |
| 2-Propenoic acid, 2-methyl-, methyl ester, homopolymer | < 25 | 9011-14-7 | 618-466-4 | None assigned. | Not classified |
| 2-Butenedioic acid (2Z)-, polymer with chloroethene and ethenyl acetate | 5 - 15 | 9005-09-8 | - | None assigned. | Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 |
| Dibenzoyl Peroxide | < 10 | 94-36-0 | 202-327-6 | None assigned. | Org. Perox. B; H241 Skin Sens. 1; H317 Eye Irrit. 2; H319 Aquatic Acute 1; H400 (M-factor = 10) |

H241: Heating may cause a fire or explosion. H315: Causes skin irritation. H317: May cause an allergic skin reaction. H319: Causes serious eye irritation. H335: May cause respiratory irritation. H400: Very toxic to aquatic life. M-factor: multiplying factor.

4. SECTION 4: FIRST AID MEASURES



4.1 Description of first aid measures

Inhalation

Skin Contact

Eye Contact

Ingestion

ingestion

4.2 Most important symptoms and effects, both acute and delayed

4.3 Indication of any immediate medical attention and special treatment needed

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Apply artificial respiration only if patient is not breathing or under medical supervision. Get medical advice/attention if you feel unwell.

IF ON SKIN: Brush off loose particles from skin. Remove contaminated clothing and wash affected skin with water. Contaminated clothing should be thoroughly cleaned. If skin irritation or rash occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Do not give anything by mouth to an unconscious person. Get medical advice/attention if you feel

unwell.

Causes serious eye irritation. Irritation of the skin and eyes. May cause an allergic skin reaction. Mechanical irritation of the respiratory tract.

Treat symptomatically.

5. SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable Extinguishing media

As appropriate for surrounding fire. Extinguish with carbon dioxide, dry chemical, foam or waterspray.

Unsuitable extinguishing media

Direct water jet may spread the fire. Avoid dust generation.

Revision: 2.0 Date: 26.08.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypq.com

5.2 Special hazards arising from the substance or

mixture

Methylmethacrylate.

5.3 Advice for fire-fighters

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Do not breathe fumes. Keep containers cool by spraying with water if exposed to fire. Avoid run off to waterways and sewers.

May form explosive dust/air mixtures. May decompose in a fire giving off toxic

fumes. Carbon monoxide, Carbon dioxide, Acrid smoke and

6. SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation. Eliminate all ignition sources if safe to do so. Stop leak if safe to do so. Avoid breathing dust. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. See Section: 8.

Do NOT wash away into sewer. Spillages or uncontrolled discharges into

6.2 Environmental precautions

Do NOT wash away into sewer. Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate

regulatory body.

6.3 Methods and material for containment and cleaning

up

Wet the material with water to limit dust emission or explosion. Sweep spilled substances into containers if appropriate moisten first to prevent dusting. Caution - spillages may be slippery. Use only non-sparking tools. Clean up spill with a detergent. Transfer to a container for disposal. Dispose of this material and its container as hazardous waste (2008/98/EEC).

6.4 Reference to other sections

See Section: 8, 13

7. SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling Ensure adequate ventilation. Avoid breathing dust. In case of inadequate

ventilation wear respiratory protection. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. See Section: 8. Do not eat, drink or smoke when using this product. Take precautionary measures against

static discharge. Protect from light.

7.2 Conditions for safe storage, including any

incompatibilities

Keep container tightly closed and in a well-ventilated place. Keep away from heat, sources of ignition and direct sunlight. Take precautionary measures

against static discharge.

Storage temperature

5 - 25°C

Storage life

7.3

Stable under normal conditions.

Incompatible materials

Specific end use(s)

Keep away from: Reducing agent (Amines) and Polymerisation catalysts such as peroxy or azo compounds, strong acids, alkalis, oxidising agents and metal

salts.

Adhesives.

8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

8.1.1 Occupational Exposure Limits

| SUBSTANCE | CAS No. | LTEL (8 hr TWA ppm) | LTEL (8 hr TWA mg/m³) | STEL (ppm) | STEL (mg/m³) | Note |
|--------------------|---------|---------------------|--------------------------|------------|--------------|------|
| Dibenzoyl peroxide | 94-36-0 | - | 5 | - | - | WEL |

Note WEL: Workplace Exposure Limit (UK HSE EH40).

8.1.2 Biological limit value Not established.

8.1.3 PNECs and DNELs Not established.

8.2 Exposure controls

8.2.1 Appropriate engineering controls Ensure adequate ventilation or use appropriate containment. Atmospheric levels

should be controlled in compliance with the occupational exposure limit. The

Revision: 2.0 Date: 26.08.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypq.com

electrical system should be spark-free. Guarantee that the eye flushing systems and safety showers are located close to the working place.

8.2.2 Individual protection measures, such as personal protective equipment (PPE)

General hygiene measures for the handling of chemicals are applicable. Avoid contact with skin, eyes or clothing. Avoid breathing dust. Wash hands before breaks and after work. Keep work clothes separately. Contaminated clothing should be thoroughly cleaned. Do not eat, drink or smoke at the work place.

Eye/ face protection Wear eye protection with side protection (EN166).



Skin protection



Hand protection: Wear impervious gloves (EN374). Gloves should be changed regularly to avoid permeation problems. Breakthrough time of the glove material: refer to the information provided by the gloves' producer. The gloves type used must be chosen based on the work activity and duration as well as concentration/quantity of material being handled.

Body protection: Wear dustproof working clothes. Recommended: Wear work clothes with long sleeves.

Respiratory protection



9.2

In case of inadequate ventilation wear respiratory protection. An approved dust mask should be worn if dust is generated during processing or handling.

Thermal hazards Not applicable.

8.2.3 Environmental Exposure Controls

Avoid release to the environment.

9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance White Powder Odour Characteristic Odour threshold Not available. рH Not established. Melting point/freezing point Not available. Initial boiling point and boiling range Not applicable. Flash point Not applicable. Evaporation rate Not applicable. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits Not available. Vapour pressure Not applicable. Vapour density Not applicable. Relative density 5 (H2O = 1)

Solubility(ies) Slightly soluble in: Water

Partition coefficient: n-octanol/water

Auto-ignition temperature

Decomposition Temperature

Dynamic viscosity

Explosive properties

Oxidising properties

Other information

Not applicable.

Not available.

Not available.

Not available.

Not oxidising.

None.

Revision: 2.0 Date: 26.08.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypq.com

| 10.1 | Reactivity | Stable under normal conditions. |
|------|------------------------------------|---|
| 10.2 | Chemical stability | May polymerise on exposure to light. |
| 10.3 | Possibility of hazardous reactions | May form flammable dust clouds in air. Reacts with oxidizing substances. |
| 10.4 | Conditions to avoid | Keep away from heat, sources of ignition and direct sunlight. |
| 10.5 | Incompatible materials | Keep away from: Reducing agent (Amines) and Polymerisation catalysts such |
| | | as peroxy or azo compounds, strong acids, alkalis, oxidising agents and metal |
| | | salts. |
| 10.6 | Hazardous decomposition product(s) | May decompose in a fire, giving off toxic and irritant vapours. Acrid smoke, |

11. SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects (Substances in preparations / mixtures)

Acute toxicity

121

Toxicity

Ingestion Based upon the available data, the classification criteria are not met.

LC50 > 2000 mg/kg bw/day

Inhalation Based upon the available data, the classification criteria are not met.

LC50 (Dusts) > 5 mg/kg bw/day

Aquatic Acute 1: Very toxic to aquatic life

Carbon monoxide, Carbon dioxide and Methylmethacrylate.

Dermal Based upon the available data, the classification criteria are not met.

LC50 > 2000 mg/kg bw/day

Skin corrosion/irritationSkin Irrit. 2: Irritation of the skin and eyes.Serious eye damage/irritationEye Irrit. 2: Causes serious eye irritation.

Respiratory or skin sensitization Skin Sens. 1: May cause sensitization by skin contact.

Germ cell mutagenicityBased upon the available data, the classification criteria are not met.CarcinogenicityBased upon the available data, the classification criteria are not met.Reproductive toxicityBased upon the available data, the classification criteria are not met.STOT - single exposureBased upon the available data, the classification criteria are not met.STOT - repeated exposureBased upon the available data, the classification criteria are not met.Aspiration hazardBased upon the available data, the classification criteria are not met.

11.2 Other information None.

12. SECTION 12: ECOLOGICAL INFORMATION

| | ioxioity | riquatio ricato 1. Voly toxio to aquatio ino. |
|------|------------------------------------|--|
| | | Estimated Mixture LC50 < 1 mg/l (Fish). |
| 12.2 | Persistence and degradability | No information available. |
| 12.3 | Bioaccumulative potential | The product has low potential for bioaccumulation. |
| 12.4 | Mobility in soil | No information available (Slightly soluble). |
| 12.5 | Results of PBT and vPvB assessment | Not classified as PBT or vPvB. |
| 400 | | N 1 1 |

12.6 Other adverse effects None known.

13. SECTION 13: DISPOSAL CONSIDERATIONS

| 13.1 | Waste treatment methods | Do not release undiluted and unneutralised to the sewer. This material and its |
|------|-------------------------|--|
| | | container must be disposed of as hazardous waste (2008/98/EEC). |
| 13.2 | Additional Information | Dispose of contents in accordance with local, state or national legislation. |

14. SECTION 14: TRANSPORT INFORMATION

| 14.1 14.2 | UN number Proper Shipping Name | ADR/RID / IMDG / IATA UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S (Dibenzoyl Peroxide) |
|--------------|--|--|
| 14.3 14.4 | Transport hazard class(es) Packing group | 9 III |

Revision: 2.0 Date: 26.08.2015



ACCORDING TO EC-REGULATIONS 1907/2006 (REACH),

1272/2008 (CLP) & 2015/830

www.vishaypq.com

14.5 Environmental hazards Classified as a Marine Pollutant/Environmentally hazardous substance.

14.6 Special precautions for user See Section: 2
 14.7 Transport in bulk according to Annex II of MARPOL Not applicable.

73/78 and the IBC Code Additional Information

None.

15. SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental

regulations/legislation specific for the substance or

mixture

15.1.1 EU regulations

14.8

15.1.2

Substance(s) of Very High Concern (SVHCs)
Authorisations and/or Restrictions On Use
National regulations
None known.

Wassergefährdungsklasse (Germany) Water hazard class: 1

15.2 Chemical Safety Assessment Not available.

16. SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

References: Existing Safety Data Sheet (SDS), Harmonised Classification(s) for Dibenzoyl Peroxide (CAS No.94-36-0), Existing ECHA registration(s) for Dibenzoyl Peroxide (CAS No.94-36-0), and the Classification and Labelling Inventory for Calcium Tungstate (CAS No.7790-75-2), 2-Propenoic acid, 2-methyl-, methyl ester, homopolymer (CAS No.9011-14-7) and 2-Butenedioic acid (2Z)-, polymer with chloroethene and ethenyl acetate (CAS No.9005-09-8).

| Classification of the substance or mixture According to Regulation (EC) No. 1272/2008 (CLP) | Classification Procedure |
|---|--------------------------|
| Skin Irrit. 2; H315 | Threshold Calculation |
| Skin Sens. 1; H317 | Threshold Calculation |
| Eye Irrit. 2; H319 | Threshold Calculation |
| Aquatic Acute 1; H400 | Summation Calculation |

LEGEND

LTEL Long Term Exposure Limit
STEL Short Term Exposure Limit
DNEL Derived No Effect Level

PNEC Predicted No Effect Concentration

PBT PBT: Persistent, Bioaccumulative and Toxic PvB PBT: very Persistent and very Toxic

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Vishay Precision Group gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Vishay Precision Group accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Annex to the extended Safety Data Sheet (eSDS)

No information available.