Revision: 1.0 Date: 21.10.2015



ACCORDING TO OSHA HCS (29 CFR 1910.1200)

www.vishaypq.com

SECTION 1: IDENTIFICATION

1.1 Product identifier

Product Name PL-10
Chemical Name Mixture
CAS No. Mixture
EINECS No. Mixture
REACH Registration No. None assigned.

1.2 Relevant identified uses of the substance or mixture

and uses advised against

Identified Use(s) Photostress® measurements.

Uses Advised Against None known.

1.3 Details of the supplier of the safety data sheet

Company Identification VISHAY MEASUREMENTS GROUP, INC.

Post Office Box 27777 Raleigh, NC 27611

USA

Telephone 919-365-3800 Fax 919-365-3945

E-Mail (competent person) mm.us@vishaypg.com

1.4 Emergency telephone number 1-800-424-9300 CHEMTREC

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

2.1.1 GHS Classification Skin Irrit. 2; H315

Skin Sens. 1; H317 Eye Irrit. 2; H319 Aquatic Chronic 2; H411

2.2 Label elements GHS Classification

Product Name PL-10

Hazard Pictogram(s)





Signal Word(s) Warning

Contains: Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average

molecular weight ≤ 700)

Hazard Statement(s) H315: Causes skin irritation.

H317: May cause an allergic skin reaction. H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

Precautionary Statement(s) P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of water.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313: If eye irritation persists: Get medical advice/attention.

P273: Avoid release to the environment.

Revision: 1.0 Date: 21.10.2015



ACCORDING TO OSHA HCS (29 CFR 1910.1200)

www.vishaypq.com

OSHA Defined Hazards None.

2.3 Other hazards None.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances Not applicable

3.2 Mixtures Substances in preparations / mixtures

GHS Classification

Chemical identity of the substance	%W/W	CAS No.	EC No.	Hazard classification
Reaction product: Bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	60 - 100	25068-38-6	500-033-5	Skin Irrit. 2; H315 (SCL: ≥ 5%) Skin Sens. 1; H317 Eye Irrit. 2; H319 (SCL: ≥ 5%) Aquatic Chronic 2; H411
Diethyl phthalate	13 - 30	84-66-2	201-550-6	Not classified

For full text of H/P Statements see section 16.

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Inhalation IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or

waistband.

Skin Contact IF ON SKIN: Remove contaminated clothing and wash all affected areas with

plenty of water. Contaminated clothing should be thoroughly cleaned. If skin

irritation or rash occurs: Get medical advice/attention.

Eye Contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. Get medical attention if eye

irritation develops or persists.

Ingestion Rinse mouth. Do not induce vomiting. Do not give anything by mouth to an

unconscious person. If symptoms develop, obtain medical attention.

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye

Most important symptoms and effects, both acute and

4.2

4.3

delaved irritation.

Indication of any immediate medical attention and

special treatment needed

Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable Extinguishing media As appropriate for surrounding fire. Extinguish with carbon dioxide, dry

chemical, foam or waterspray. Alcohol resistant foams (ATC type) are preferred.

General purpose synthetic foams (including AFFF) or protein foams may

function, but will be less effective.

Unsuitable extinguishing media Do not use water jet. Direct water jet may spread the fire.

Special hazards arising from the substance or mixture 5.2 May decompose in a fire giving off toxic fumes. Carbon monoxide, carbon

dioxide and halogenated compounds.

Advice for fire-fighters 5.3 Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Do not breathe fumes. Keep containers cool by spraying

with water if exposed to fire. Avoid run off to waterways and sewers.

Revision: 1.0 Date: 21.10.2015



ACCORDING TO OSHA HCS (29 CFR 1910.1200)

www.vishaypg.com

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

6.2 Environmental precautions

6.3 Methods and material for containment and cleaning

6.4 Reference to other sections

Ensure adequate ventilation. Stop leak if safe to do so. Eliminate all ignition sources if safe to do so. Avoid breathing vapours. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. See Section: 8. Avoid release to the environment. Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body. Stop leak if safe to do so. Keep upwind. Ensure suitable personal protection during removal of spillages. Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a lidded container for disposal or recovery. Ventilate the area and wash spill site after material pick-up is complete. Dispose of this material and its container as hazardous waste.

See Section: 8, 13

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Ensure adequate ventilation. Avoid contact with skin, eyes or clothing. Avoid breathing vapours. Use personal protective equipment as required. See Section: 8. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work.

7.2 Conditions for safe storage, including any incompatibilities

Storage temperature Storage life

Incompatible materials7.3 Specific end use(s)

Store in a well-ventilated place. Keep container tightly closed. Keep away from heat, sources of ignition and direct sunlight. Opened containers should be carefully resealed and stored in an upright position.

Ambient. (2 - 40°C)

Stable under normal conditions.

Keep away from: Acids, strong bases, Amines and mercaptans.

See Section: 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

8.1.1 Occupational Exposure Limits

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m³)	STEL (ppm)	STEL (mg/m³)	Note
Diethyl phthalate	84-66-2	-	5	-	-	NIOSH, ACGIH

Note: NIOSH RELs / ACGIH TLVs. OSHA PELs have not been established for the substances listed in Section 3.

Occupational exposure limits have not been established for the other components listed in Section 3.

8.1.2 Biological limit value

Not established.

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure adequate ventilation or use appropriate containment. Atmospheric levels should be controlled in compliance with the occupational exposure limit. Have available eyewash bottle with clean water.

8.2.2 Individual protection measures, such as personal protective equipment (PPE)

General hygiene measures for the handling of chemicals are applicable. Avoid contact with skin, eyes or clothing. Avoid breathing vapours. Wash hands before breaks and after work. Keep work clothes separately. Contaminated clothing should be thoroughly cleaned. Contaminated leather articles should be discarded (e.g. shoes). Do not eat, drink or smoke at the work place.

Eye/ face protection

Wear protective eye glasses for protection against liquid splashes. Wear eye protection with side protection.

Revision: 1.0 Date: 21.10.2015



ACCORDING TO OSHA HCS (29 CFR 1910.1200)

www.vishaypq.com



Skin protection



Hand protection: Wear impervious gloves. Gloves should be changed regularly to avoid permeation problems. The gloves type used must be chosen based on the work activity and duration as well as concentration/quantity of material being

Body protection: Wear impervious protective clothing, including boots, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Respiratory protection Use only in well-ventilated areas. In case of inadequate ventilation wear respiratory protection. Open system(s): Wear suitable respiratory protective

equipment. Use NIOSH approved respiratory protection.

Not applicable. Thermal hazards

8.2.3 **Environmental Exposure Controls** Avoid release to the environment.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Yellowish liquid Appearance Odour Slight Odour Odour threshold Not available. Not established. рΗ

Melting point/freezing point Not available. Initial boiling point and boiling range >200°C (> 392°F)

Flash point 160°C (320°F) [Closed cup]

Evaporation rate Not available.

Flammability (solid, gas) Not applicable - Liquid.

Upper/lower flammability or explosive limits Not available. Vapour pressure Not available. Vapour density Not available.

Relative density 1.1 - 1.2 (H2O = 1) @ 25°C (77°F)

The product is essentially insoluble in water. Solubility(ies)

Partition coefficient: n-octanol/water Not available. Auto-ignition temperature Not available. **Decomposition Temperature** >200°C (> 392°F) Viscosity Not available. Explosive properties Not explosive. Oxidising properties Not oxidising.

9.2 Other information None.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity Stable under normal conditions. 10.2 Chemical stability Stable under normal conditions.

Possibility of hazardous reactions 10.3 Hazardous Polymerization: No hazard expected under normal conditions of use.

10.4 Conditions to avoid Keep away from heat, sources of ignition and direct sunlight. 10.5 Incompatible materials Keep away from: Acids, strong bases, Amines and mercaptans.

10.6 Hazardous decomposition product(s) May decompose in a fire giving off toxic fumes. Carbon monoxide, carbon

dioxide and halogenated compounds.

Revision: 1.0 Date: 21.10.2015



ACCORDING TO OSHA HCS (29 CFR 1910.1200)

www.vishaypg.com

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects (Substances in preparations / mixtures)

Acute toxicity

Ingestion Based upon the available data, the classification criteria are not met.

Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg

bw/day.

Inhalation Based upon the available data, the classification criteria are not met.

Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 20.0 mg/l. Based upon the available data, the classification criteria are not met.

Skin Contact

Based upon the available data, the classification criteria are not met.

Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg

bw/day.

Skin corrosion/irritationSkin Irrit. 2: Causes skin irritation.Serious eye damage/irritationEye Irrit. 2: Causes serious eye irritation.

Respiratory or skin sensitizationSkin Sens. 1: May cause an allergic skin reaction.

Germ cell mutagenicity
Based upon the available data, the classification criteria are not met.

Reproductive toxicity
Based upon the available data, the classification criteria are not met.

Based upon the available data, the classification criteria are not met.

Based upon the available data, the classification criteria are not met.

Based upon the available data, the classification criteria are not met.

Based upon the available data, the classification criteria are not met.

Based upon the available data, the classification criteria are not met.

Based upon the available data, the classification criteria are not met.

Based upon the available data, the classification criteria are not met.

11.2 Other information

Information on likely routes of exposure

Inhalation Yes
Ingestion Accidental
Skin Contact Yes

Further Carcinogenicity Information

NTP Report on Carcinogens None of the components are listed.

IARC Monographs None of the components listed in Groups 1 or 2.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Ecotoxicity Aquatic Chronic 2: Toxic to aquatic life with long lasting effects.

Estimated Mixture LC50 > 1 ≤ 10 mg/l (Fish)

12.2 Persistence and degradability
 12.3 Bioaccumulative potential
 Part of the components are poorly biodegradable.
 The product has low potential for bioaccumulation.

12.4 Mobility in soil The product is predicted to have low mobility in soil (The product is essentially

insoluble in water).

12.5 Other adverse effects Not classified as PBT or vPvB. None of the substances in this product fulfil the

criteria for being regarded as a PBT or vPvB substance.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods Dispose of this material and its container as hazardous waste. Containers of this

material may be hazardous when empty since they retain product residue. Dispose of wastes in an approved waste disposal facility. Dispose of contents in

accordance with local, state or national legislation.

SECTION 14: TRANSPORT INFORMATION

ADR/RID / IMDG / IATA

14.1 UN number UN 3082

14.2 UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S (Reaction

product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular

weight ≤ 700))

14.3 Transport hazard class(es)

9

DOCUMENT NO. 15477 Page: 5 of 7 REVISION A

Revision: 1.0 Date: 21.10.2015



ACCORDING TO OSHA HCS (29 CFR 1910.1200)

www.vishaypq.com

14.4 Packing group Ш

14.5 **Environmental hazards** Classified as a Marine Pollutant/ Environmentally hazardous substance

14.6 Special precautions for user Transport in bulk according to Annex II of MARPOL Not applicable. 14.7

73/78 and the IBC Code

14.8 Additional Information None.

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental

regulations/legislation specific for the substance or

mixture

15.1.1 **U.S. Federal Regulations**

> All components of this product are listed in the Toxic Substance Control Act TSCA Inventory Status

Chemical Substance Inventory (TSCA).

US State Regulations 15.1.2 None known.

European regulations 15.1.3

> Authorisations and/or Restrictions On Use None Substance(s) of Very High Concern (SVHCs) None

Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average Community Rolling Action Plan (CoRAP)

molecular weight ≤ 700) (CAS# 25068-38-6): Substance identified for evaluation

in 2015.

Wassergefährdungsklasse (Germany) Water hazard class: 2

15.2 **Chemical Safety Assessment** Not available.

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

Version 1.0 Date of preparation 21.10.15

References: Existing Safety Data Sheet (SDS), Harmonised Classification(s) for Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) (CAS# 25068-38-6). Existing ECHA registration(s) for Reaction product: Bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) (CAS# 25068-38-6) and Diethyl phthalate (CAS# 84-66-2).

GHS Classification of the substance or mixture	Classification Procedure
Skin Irrit. 2; H315	Threshold Calculation
Skin Sens. 1; H317	Threshold Calculation
Eye Irrit. 2; H19	Threshold Calculation
Aquatic Chronic 2; H411	Summation Calculation

LEGEND

ACGIH: American Conference of Governmental Industrial Hygienists PELs: Permissible Exposure Limits

IARC: International Agency for Research on Cancer **RELs: Recommended Exposure Limits** LTEL: Long Term Exposure Limit STEL: Short Term Exposure Limit

NTP: National Toxicology Program TLVs: Threshold limit values

OSHA: The Occupational Safety & Health Administration vPvB: very Persistent and very Bioaccumulative

PBT: Persistent, Bioaccumulative and Toxic

Hazard Statement(s)

H315: Causes skin irritation. H411: Toxic to aquatic life with long lasting effects.

H317: May cause an allergic skin reaction. SCL: Specific Concentration Limit

H319: Causes serious eye irritation.

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

Disclaimers

DOCUMENT NO. 15477 Page: 6 of 7 **REVISION A**

Revision: 1.0 Date: 21.10.2015



ACCORDING TO OSHA HCS (29 CFR 1910.1200)

www.vishaypg.com

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Vishay Precision Group gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Vishay Precision Group accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Annex to the extended Safety Data Sheet (eSDS)

No information available.