Version: 1.0

Date of Issue: 10-May-2017 Date of First Issue: 10-May-2017 MICROE MEASUREMENTS AVPG Brand

www.vishaypg.com

#### ACCORDING TO OSHA HCS (29 CFR 1910.1200)

# **SECTION 1: IDENTIFICATION**

Product identifier used on the label RTC-2 Epoxy Part A

Other means of identification

Chemical Name Bisphenol A Diglycidyl Ether

CAS No. 25085-99-8 EINECS No. 607-537-5

Recommended use of the chemical and restrictions

on use

Recommended use PC14 Metal surface treatment products, including galvanic and electroplating

products

Restrictions on use Anything other than the above.

Details of the supplier of the safety data sheet

Supplier VISHAY MEASUREMENTS GROUP, INC.

Address of Supplier Post Office Box 27777
Raleigh, NC 27611

USA

 Telephone
 +1 919-365-3800

 Fax
 +1 919-365-3945

 E-Mail (competent person)
 mm.us@vishaypg.com

Emergency telephone number 1-800-424-9300 CHEMTREC (24 hours)

## SECTION 2: HAZARD(S) IDENTIFICATION

Classification of the substance or mixture in accordance with paragraph (d) of 29 CFR 1910.1200

Physical hazards Not classified

Health hazards Skin corrosion/irritation, Category 2
Skin Sensitisation, Category 1

Skin Sensitisation, Category Eye Irritation, Category 2

Environmental hazards Hazardous to the aquatic environment, Chronic, Category 2

Hazard Symbol





Signal Word(s) Warning

Hazard Statement(s)

Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

Toxic to aquatic life with long lasting effects.

Precautionary Statement(s) Wash hands and exposed skin thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

Avoid breathing dust/fume/gas/mist/vapours/spray. Take off contaminated clothing and wash it before reuse.

IF ON SKIN: Wash with plenty of water.

If skin irritation occurs, get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

15569 Page: 1 of 6

Version: 1.0

Date of Issue: 10-May-2017 Date of First Issue: 10-May-2017



www.vishaypg.com

# ACCORDING TO OSHA HCS (29 CFR 1910.1200)

If eye irritation persists, get medical advice/attention.

Other hazards None known.

Percent of the mixture consists of ingredient(s) of

unknown acute toxicity:

0%

#### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### Substances

Chemical identity of the substance	%W/W	CAS No.	EC No.	Hazard classification
Bisphenol A Diglycidyl Ether	100	25085-99-8	607-537-5	Skin corrosion/irritation, Category 2 Skin Sensitisation, Category 1 Eye Irritation, Category 2 Hazardous to the aquatic environment, Chronic, Category 2

### **SECTION 4: FIRST AID MEASURES**



Description of first aid measures

Self-protection of the first aider

Inhalation

Skin Contact

**Eye Contact** 

Ingestion

Most important symptoms and effects, both acute and delayed

Indication of any immediate medical attention and special treatment needed

Notes to a physician:

Use personal protective equipment as required. Wear appropriate personal

protective equipment, avoid direct contact.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms occur obtain medical attention.

IF ON SKIN: Remove contaminated clothing immediately and wash affected skin with soap and water. Wash contaminated clothing before reuse. If irritation develops and persists, get medical attention.

IF IN EYES:Rinse cautiously with water for several minutes. Remove contact lenses, if present, after the first five minutes, then continue rinsing eye. Get medical attention if eye irritation develops or persists.

Unlikely route of exposure. IF SWALLOWED: rinse mouth. Do NOT induce

vomiting. If symptoms occur obtain medical attention.

Causes irritation to eyes and skin. May cause sensitization by skin contact.

Treat symptomatically.

Repeated or prolonged contact may cause defatting of the skin resulting in dryness, cracking and dermatitis.

# **SECTION 5: FIRE-FIGHTING MEASURES**

#### **Extinguishing media**

Suitable Extinguishing Media Unsuitable extinguishing Media

Special hazards arising from the substance or

Special protective equipment and precautions for fire fighters

Extinguish with carbon dioxide, dry chemical, foam or waterspray.

Do not use water jet.

Not flammable. May decompose in a fire giving off toxic fumes. Epoxy resins release phenolics, carbon monoxide, and water.

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Do not breathe fumes. Keep containers cool by spraying with water if exposed to fire. Avoid run off to waterways and sewers.

15569 Page: 2 of 6

Version: 1.0

Date of Issue: 10-May-2017 Date of First Issue: 10-May-2017 MICROE MEASUREMENTS

www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures

Methods and material for containment and cleaning

Ensure adequate ventilation. Do not breathe fumes/vapour from heated product. Stop leak if safe to do so. Use personal protective equipment as required. See Section: 8. Avoid breathing vapours. Avoid contact with skin and eyes.

Contain spillages. Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a container for disposal. Dispose of this material and its container as hazardous waste. Residual resin may be removed using steam or hot soapy water.

## **SECTION 7: HANDLING AND STORAGE**

Precautions for safe handling

Conditions for safe storage, including any incompatibilities
Storage temperature
Incompatible materials

Ensure operatives are trained to minimise exposures. Ensure adequate ventilation. Do not breathe fumes/vapour from heated product. Avoid breathing vapours. In case of inadequate ventilation wear respiratory protection. Wear protective gloves/protective clothing/eye protection/face protection. Avoid contact with skin and eyes. Do not eat, drink or smoke when using this product. Keep only in original container. Keep container tightly closed and in a well-ventilated place. Keep away from naked flames and hot surfaces. Ambient.

None known.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

Not established

**Biological Exposure Indices** 

Not established

Appropriate engineering controls

Ensure operatives are trained to minimise exposures. Ensure adequate ventilation.

Individual protection measures, such as personal protective equipment (PPE)

General hygiene measures for the handling of chemicals are applicable. Keep good industrial hygiene. Avoid contact with skin and eyes. Do not breathe fumes/vapour from heated product. Avoid breathing vapours. Wash hands before breaks and after work. Keep work clothes separately. Do not eat, drink or smoke at the work place. IF exposed: Flush with fresh water if contact with skin or eyes.

Eye/face protection



Wear protective eye glasses for protection against liquid splashes. Wear eye protection with side protection.

Skin protection



Wear suitable chemical resistant protective gloves for frequent or prolonged operations tested with an acceptable permeation test. Contaminated gloves should be carefully rinsed with water before reuse. Breakthrough time of the glove material: refer to the information provided by the gloves' producer.

Respiratory protection



Normally no personal respiratory protection is necessary. In case of inadequate ventilation wear respiratory protection.

15569 Page: 3 of 6

Version: 1.0

Date of Issue: 10-May-2017 Date of First Issue: 10-May-2017



www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

#### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

**Appearance** Colourless to yellowish liquid.

Odor Faint Epoxy Odour Odor Threshold Not available. Not established. Melting Point/Freezing Point Not established. Initial boiling point and boiling range Not applicable.

Flash Point 252°C (Method: PMCC)

Evaporation rate (Butyl acetate = 1) Not known. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits Not applicable. Vapour pressure Not applicable. Vapour density Not applicable. Relative density 1.16 (H2O=1) Solubility(ies) Insoluble in water. Partition coefficient: n-octanol/water Not available. Auto-ignition temperature Not available. Not available. **Decomposition Temperature** Viscosity Not available.

## **SECTION 10: STABILITY AND REACTIVITY**

Reactivity Stable under normal conditions. Chemical stability Stable under normal conditions. Possibility of hazardous reactions Phenolics. Carbon monoxide and Water.

Temperature > 300°C. Decomposes at temperatures above (°C): 350. Conditions to avoid

Generation of gas during decomposition can cause pressure in closed systems.

Pressure buildup can be rapid.

Alkalis (strong bases). Acids. Amines and Oxidizing agents. Incompatible materials

Hazardous decomposition product(s) Will not occur by itself, but masses of more than 500 gramms of product plus an

aliphatic amine will cause irreversible polymerization with considerable heat

buildup.

#### SECTION 11: TOXICOLOGICAL INFORMATION

Acute toxicity - Skin Contact

Serious eye damage/irritation

Information on toxicological effects (Substances in preparations / mixtures)

Acute toxicity - Ingestion Based upon the available data, the classification criteria are not met.

Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg

bw/day.

Acute toxicity - Inhalation Based upon the available data, the classification criteria are not met.

Acute Toxicity Estimate Mixture Calculation: Estimated LC50 >20.0 mg/l. Based upon the available data, the classification criteria are not met.

Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg

bw/day.

Skin corrosion/irritation Skin corrosion/irritation, Category 2: Causes skin irritation.

> Test Result: Irritating to skin. (Jolanki R et al, 1986) Eye Irritation, Category 2: Causes serious eye irritation.

Test Result: Causes serious eye irritation. (EPA/OTS; Doc #878212416) Respiratory or skin sensitization

Skin Sensitisation, Category 1: May cause an allergic skin reaction.

Test Result: Skin sensitisation has been reported in studies with guinea pigs.

(EPA/OTS; Doc #878212421)

Germ cell mutagenicity Based upon the available data, the classification criteria are not met. Carcinogenicity Based upon the available data, the classification criteria are not met. Reproductive toxicity Based upon the available data, the classification criteria are not met. STOT - single exposure Based upon the available data, the classification criteria are not met. STOT - repeated exposure Based upon the available data, the classification criteria are not met.

15569 Page: 4 of 6

Version: 1.0

Date of Issue: 10-May-2017 Date of First Issue: 10-May-2017



www.vishaypg.com

## ACCORDING TO OSHA HCS (29 CFR 1910.1200)

**Aspiration hazard** Based upon the available data, the classification criteria are not met.

Information on likely routes of exposure

Possible - accidental exposure Inhalation Unlikely - accidental exposure Ingestion Skin Contact Possible - accidental exposure Eye Contact Unlikely - accidental exposure

Early onset symptoms related to exposure Causes irritation to eyes and skin.

Delayed health effects from exposure Allergic contact dermatitis

Other information

NTP Report on Carcinogens Not listed IARC Monographs Not listed **OSHA** Designated Carcinogen Not listed

# **SECTION 12: ECOLOGICAL INFORMATION**

**Ecotoxicity** Hazardous to the aquatic environment, Chronic, Category 2; Toxic to aquatic life

with long lasting effects.

Estimated Mixture LC50 > 1 to ≤ 10 mg/l (Fish)

Readily biodegradable. Persistence and degradability

Bioaccumulative potential The product has low potential for bioaccumulation. Mobility in soil The product is predicted to have low mobility in soil.

Other adverse effects None known.

#### SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods Dispose of this material and its container as hazardous waste. Send after

pre-treatment to a appropriate hazardous waste incinerator facility according

substance

Additional Information Dispose of contents in accordance with local, state or national legislation.

# **SECTION 14: TRANSPORT INFORMATION**

ADR/RID **IMDG** IATA/ICAO **UN** number UN 3077 UN 3077 UN 3077

UN proper shipping name ENVIRONMENTALLY **ENVIRONMENTALLY ENVIRONMENTALLY** HAZARDOUS SUBSTANCE. HAZARDOUS SUBSTANCE. HAZARDOUS SUBSTANCE. LIQUID, N.O.S. (BISPHENOL LIQUID, N.O.S. (BISPHENOL LIQUID, N.O.S. (BISPHENOL

> A DIGLYCIDYL ETHER) A DIGLYCIDYL ETHER) A DIGLYCIDYL ETHER)

Transport hazard class(es) Packing group Ш **Environmental hazards** 

Environmentally hazardous Classified as a Marine Environmentally hazardous

substance Pollutant.

Transport in bulk according to Annex Not applicable II of MARPOL 73/78 and the IBC Code

Special precautions for user See Section: 2

#### SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture **US Federal Regulations** 

TSCA (Toxic Substance Control Act) Not listed EPCRA/SARA Section 302 Extremely Hazardous Substances Not listed EPCRA Section 313 Toxics Release Inventory (TRI) Program Not listed NIOSH Occupational Carcinogen List Not listed

15569 Page: 5 of 6

Version: 1.0

Date of Issue: 10-May-2017 Date of First Issue: 10-May-2017



www.vishaypg.com

## ACCORDING TO OSHA HCS (29 CFR 1910.1200)

OSHA List of highly hazardous chemicals, toxics and Not listed reactives NTP Report on Carcinogens (RoC) List Not listed Not listed Poison Prevention Packaging Act **US State Regulations** Not listed California State, Proposition 65 List California State, Safer Consumer Products Regulations Not listed Maine State, Toxic Chemicals in Children's Products Act Not listed New Jersey State Worker and Community RTK Act Not listed Pennsylvania State, Worker and Community RTK Act Not listed Rhode Island State, Hazardous Substances RTK Act Not listed Non-Regional IARC Monographs, List of Classificationsonal Not listed

#### **SECTION 16: OTHER INFORMATION**

The following sections contain revisions or new statements: Not applicable – V1.0

Version 1.0

Revision Date 10-May-2017 Date of First Issue 10-May-2017

#### References:

Existing Safety Data Sheet (SDS) and the EU Classification and Labelling Inventory for Bisphenol A Diglycidyl Ether (CAS No. 25085-99-8)

#### Literature References:

"Bisphenol A Diglycidyl Ether". In TOXLINE®: Toxic Substances Control Act Test Submissions. ToxPlanet, a division of Timberlake Ventures, Inc.

Cornelius, NC. 2017

GHS Classification of the substance or mixture	Classification Procedure
Skin corrosion/irritation, Category 2	Threshold Classification
Skin Sensitisation, Category 1	Threshold Classification
Eye Irritation, Category 2	Threshold Classification
Hazardous to the aquatic environment, Chronic, Category 2	Threshold Classification

#### **LEGEND**

ACGIH: American Conference of Governmental Industrial Hygienists

REL: Recommended exposure limit

BEI: Biological Exposure Indices (ACGIH)

SCL: Specific Concentration Limit

IARC: International Agency for Research on Cancer Skin": Risk of overexposure via dermal contact

Irr: Irritation STEL: Short Term Exposure Limit

NIOSH: National Institute of Occupational Safety and Health

TLV: Threshold Limit value

NTP: National Toxicology Program

TSCA: Toxic Substance Control Act

OSHA: The Occupational Safety & Health Administration

TWA: Time Weighted Average

PBT: Persistent, Bioaccumulative and Toxic

URT: Upper respiratory tract

PEL: Permissible exposure limit vPvB: very Persistent and very Bioaccumulative

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

#### **Disclaimers**

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Vishay Precision Group gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Vishay Precision Group accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

15569 Page: 6 of 6