Version: 1.0

Date of Issue: 10-May-2017 Date of First Issue: 10-May-2017



www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

# **SECTION 1: IDENTIFICATION**

Product identifier used on the label RTC-2 Epoxy Part B

Other means of identification

Chemical Name Mixture
CAS No. Mixture
EINECS No. Mixture

Recommended use of the chemical and restrictions

on use

Recommended use PC14 Metal surface treatment products, including galvanic and electroplating

products.

Restrictions on use None known.

Details of the supplier of the safety data sheet

Supplier VISHAY MEASUREMENTS GROUP, INC.

Address of Supplier Post Office Box 27777
Raleigh, NC 27611

USA

 Telephone
 +1 919-365-3800

 Fax
 +1 919-365-3945

 E-Mail (competent person)
 mm.us@vishaypg.com

Emergency telephone number 1-800-424-9300 CHEMTREC (24 hours)

## SECTION 2: HAZARD(S) IDENTIFICATION

Classification of the substance or mixture in accordance with paragraph (d) of 29 CFR 1910.1200

Physical hazards Not Classified

Health hazards Skin corrosion/irritation, Category 1

Eye damage, category 1 Skin Sensitisation, Category 1

Specific target organ toxicity — single exposure, Category 3
Environmental hazards Hazardous to the aquatic environment, Chronic , Category 2

Hazard Symbol







Signal Word(s) Danger

Hazard Statement(s) Causes severe skin burns and eye damage.

May cause an allergic skin reaction. May cause respiratory irritation.

Toxic to aquatic life with long lasting effects.

Precautionary Statement(s) Do not breathe vapour.

Wash hands and exposed skin thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.

Rinse skin with water/shower.

Wash contaminated clothing before reuse.

15581 Page: 1 of 7

Version: 1.0

Date of Issue: 10-May-2017 Date of First Issue: 10-May-2017



www.vishaypg.com

## ACCORDING TO OSHA HCS (29 CFR 1910.1200)

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

Avoid release to the environment.

Store locked up.

Dispose of contents in accordance with local, state or national legislation.

Other hazards None known.

Percent of the mixture consists of ingredient(s) of

0%

unknown acute toxicity:

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substances Not applicable

Mixtures Substances in mixture

Chemical identity of the substance	%W/W	CAS No.	EC No.	Hazard classification
Liquid Diethoxymethane Polysulfide Polymer	< 100	68611-50-7	614-671-8	Skin corrosion/irritation, Category 2 Eye Irritation, Category 2 Specific target organ toxicity — single exposure, Category 3 Toxic to aquatic life with long lasting effects.
Tris-2,4,6- (Dimethylaminomethyl)	< 18	90-72-2	202-013-9	Skin corrosion/irritation, Category 1A  Eye damage, category 1  Skin Sensitisation, Category 1
Bis(dimethylaminomethyl)phenol	< 3	71074-89-0	275-162-0	Acute toxicity, Category 4 (Oral) Acute toxicity, Category 4 (Dermal) Skin corrosion/irritation, Category 1 Eye damage, category 1 Specific target organ toxicity — single exposure, Category 3

## **SECTION 4: FIRST AID MEASURES**



# Description of first aid measures

Self-protection of the first aider

Inhalation

Skin Contact

Eye Contact

Ingestion

Use personal protective equipment as required. Wear appropriate personal protective equipment, avoid direct contact. Ensure adequate ventilation. Avoid

all contact. Do not breathe vapour.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing has stopped, apply artificial respiration. If breathing is laboured, oxygen should be administered by qualified personnel. If vomiting occurs spontaneously, keep head below hips to prevent aspiration into the lungs. Get immediate medical attention.

IF ON SKIN: Remove contaminated clothing immediately and wash affected skin with plenty of water. Continue irrigation until medical attention can be obtained.

Wash contaminated clothing before reuse.

IF IN EYES:Rinse cautiously with water for several minutes. Remove contact lenses, if present, after the first five minutes, then continue rinsing eye. Get immediate medical attention.

IF SWALLOWED: rinse mouth. Do NOT induce vomiting. If vomiting occurs

15581 Page: 2 of 7

Version: 1.0

Date of Issue: 10-May-2017 Date of First Issue: 10-May-2017 MICROE MEASUREMENTS AVPG Brand

www.vishaypg.com

#### ACCORDING TO OSHA HCS (29 CFR 1910.1200)

medical attention.

Most important symptoms and effects, both acute medical attention.

Causes severe skin burns and eye damage

and delayed Indication of any immediate medical attention and special treatment needed

Notes to a physician:

Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause irritation to the respiratory system.

spontaneously, keep head below hips to prevent aspiration into the lungs. If the victim is conscious and alert, give 2-4 glasses of water or milk. Get immediate

IF ON SKIN: Cover the affected area with a sterile dressing or clean sheeting and transport for medical care. Do not apply greases or ointments.

IF IN EYES: Obtain prompt consultation, preferably from an ophthalmologist. IF INHALED: Initiate inhalative cortisone therapy (e.g. Auxiloson, Thomae).

## **SECTION 5: FIRE-FIGHTING MEASURES**

Extinguishing media

Suitable Extinguishing Media

Unsuitable extinguishing Media

Special hazards arising from the substance or mixture

Special protective equipment and precautions for fire fighters

Extinguish preferably with foam, carbon dioxide or dry chemical. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

None.

Combustion or thermal decomposition will evolve toxic and irritant vapours. (Carbon monoxide, Nitrogen oxides, Ammonia).

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Do not breathe fumes. Avoid run off to waterways and sewers. Do not allow run-off from fire fighting to enter drains or water courses.

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures

Methods and material for containment and cleaning

Ensure adequate ventilation. Do not breathe fumes/vapour from heated product. Wear protective gloves/protective clothing/eye protection/face protection.

Stop leak if safe to do so. Contain spillages. Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a container for disposal. Dispose of this material and its container as hazardous waste.

#### **SECTION 7: HANDLING AND STORAGE**

Precautions for safe handling

Do not breathe fumes/vapour from heated product. Ensure adequate ventilation. In case of inadequate ventilation wear respiratory protection. Avoid contact with skin, eyes or clothing. Wear protective gloves/protective clothing/eye protection/face protection. Do not eat, drink or smoke when using this product. Keep container tightly closed, in a cool, well ventilated place.

Conditions for safe storage, including any incompatibilities

Storage temperature Incompatible materials

Ambient.

Keep away from: Acids, Oxidizing agents.

#### **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

Occupational Exposure Limits No Occupational Exposure Limit assigned.

No OSHA permissible exposure limit (PEL).

No American Conference of Governmental Industrial Hygienists (ACGIH)

Threshold Limit Value (TLV)

Biological Exposure Indices Not established

Appropriate engineering controls Ensure adequate ventilation. Guarantee that the eye flushing systems and

safety showers are located close to the working place.

Individual protection measures, such as personal

protective equipment (PPE)

Use personal protective equipment as required. Wash contaminated clothing

before reuse. Avoid contact with skin and eyes.

Eye/face protection Wear goggles giving complete protection to eyes to protect against liquid

splashes.

15581 Page: 3 of 7

Version: 1.0

Date of Issue: 10-May-2017 Date of First Issue: 10-May-2017



www.vishaypg.com

## ACCORDING TO OSHA HCS (29 CFR 1910.1200)



Skin protection



Wear impervious gloves. Breakthrough time of the glove material: refer to the  $\ensuremath{\mathsf{T}}$ 

information provided by the gloves' producer.

Respiratory protection



Normally no personal respiratory protection is necessary. In case of inadequate ventilation wear respiratory protection.

#### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Information on basic physical and chemical properties

Appearance Straw Yellow Liquid
Odor Irritating odour
Odor Threshold Not available.
pH Not established.
Melting Point/Freezing Point Not established.
Initial boiling point and boiling range Not applicable.
Flash Point 93.3°C

Evaporation rate (Butyl acetate = 1) Not known.

Flammability (solid, gas)

Not applicable - Liquid.

Upper/lower flammability or explosive limits Not applicable. Vapour pressure Not applicable. Vapour density Not applicable. Relative density 0.97 (H2O=1) Solubility(ies) < 20% (Water) Partition coefficient: n-octanol/water Not available. Auto-ignition temperature Not available. **Decomposition Temperature** Not available. Viscosity Not available.

#### **SECTION 10: STABILITY AND REACTIVITY**

 Reactivity
 Stable under normal conditions.

 Chemical stability
 Stable under normal conditions.

Possibility of hazardous reactions May react vigorously with oxidizing agents creating explosion hazard.

Conditions to avoid Avoid contact with heat and ignition sources and oxidizers.

Incompatible materials Acids, Oxidizing agents, Sodium hypochlorite and calcium hyprochlorite.

Hazardous decomposition product(s) Carbon monoxide, Carbon dioxide, Nitrogen oxides, Ammonia.

# SECTION 11: TOXICOLOGICAL INFORMATION

Acute toxicity - Skin Contact

Information on toxicological effects (Substances in preparations / mixtures)

Acute toxicity - Ingestion Based upon the available data, the classification criteria are not met.

Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg

bw/day.

Acute toxicity - Inhalation

Based upon the available data, the classification criteria are not met.

Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 20.0 mg/l. Based upon the available data, the classification criteria are not met.

Acute Toxicity Estimate Mixture Calculation: Estimated LC50 > 2000 mg/kg

15581 Page: 4 of 7

Version: 1.0

Date of Issue: 10-May-2017 Date of First Issue: 10-May-2017



www.vishaypg.com

## ACCORDING TO OSHA HCS (29 CFR 1910.1200)

bw/dav.

Skin corrosion/irritation Skin corrosion/irritation, Category 1: Causes severe skin burns and eye

damage.

**Serious eye damage/irritation** Eye damage, category 1: Causes serious eye damage...

Respiratory or skin sensitizationSkin Sensitisation, Category 1: May cause an allergic skin reaction.Germ cell mutagenicityBased upon the available data, the classification criteria are not met.CarcinogenicityBased upon the available data, the classification criteria are not met.Reproductive toxicityBased upon the available data, the classification criteria are not met.

STOT - single exposure Specific target organ toxicity — single exposure, Category 3: May cause

respiratory irritation.

**STOT - repeated exposure**Based upon the available data, the classification criteria are not met. **Aspiration hazard**Based upon the available data, the classification criteria are not met.

Information on likely routes of exposure

InhalationPossible – accidental exposureIngestionUnlikely – accidental exposureSkin ContactPossible – accidental exposureEye ContactUnlikely – accidental exposure

Early onset symptoms related to exposure Causes severe burns to skin, eyes and respiratory system.

**Delayed health effects from exposure**May cause an allergic skin reaction. May cause respiratory irritation.

Other information

NTP Report on Carcinogens

IARC Monographs

OSHA Designated Carcinogen

Not listed.

Not listed.

#### **SECTION 12: ECOLOGICAL INFORMATION**

EcotoxicityToxic to aquatic life with long lasting effects.Persistence and degradabilityPart of the components are poorly biodegradable.Bioaccumulative potentialThe product has no potential for bioaccumulation.

**Mobility in soil** The product has moderate mobility in soil.

Other adverse effects None known.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

Waste treatment methods This material and its container must be disposed of as hazardous waste. Send

after pre-treatment to an appropriate hazardous waste incinerator facility

according to legislation.

#### **SECTION 14: TRANSPORT INFORMATION**

 ADR/RID
 IMDG
 IATA

 UN number
 UN 2735
 UN 2735
 UN 2735

 UN proper shipping name
 AMINES, LIQUID,
 AMINES, LIQUID,
 AMINES, LIQUID,

CORROSIVE, N.O.S (Tris-2,4,6-(Dimethylaminomethyl)) CORROSIVE, N.O.S (Tris-2,4,6-(Dimethylaminomethyl)) 2,4,6-(Dimethylaminomethyl))

Transport hazard class(es) 8 8 8
Packing group III III III

Environmental hazards Environmentally hazardous Classified as a Marine Environmentally hazardous

substance Pollutant substance

nsport in bulk according to Annex II Not applicable.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Special precautions for user See Section: 2

15581 Page: 5 of 7

Version: 1.0

Date of Issue: 10-May-2017 Date of First Issue: 10-May-2017



www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

#### **SECTION 15: REGULATORY INFORMATION**

# Safety, health and environmental regulations/legislation specific for the substance or mixture US Federal Regulations

TSCA (Toxic Substance Control Act)

Tris-2,4,6-(Dimethylaminomethyl): Subject to 25,000 lb reporting threshold

EPCRA/SARA Section 302 Extremely Hazardous Not listed.

Substances

EPCRA Section 313 Toxics Release Inventory (TRI) Not listed.

Program

NIOSH Occupational Carcinogen List Not listed.

OSHA List of highly hazardous chemicals, toxics and Not listed.

reactives

NTP Report on Carcinogens (RoC) List Not listed.

Poison Prevention Packaging Act Not listed.

**US State Regulations** 

California State, Proposition 65 List

California State, Safer Consumer Products Regulations

Maine State, Toxic Chemicals in Children's Products Act

New Jersey State Worker and Community RTK Act

Pennsylvania State, Worker and Community RTK Act

Not listed.

Not listed.

Not listed.

Not listed.

Not listed.

Not listed.

Non-Regional

IARC Monographs, List of Classificationsonal Not listed.

#### **SECTION 16: OTHER INFORMATION**

The following sections contain revisions or new statements: V1.0 – Not applicable

Version 1.0

Revision Date 10-May-2017 Date of First Issue 10-May-2017

#### References:

Existing Safety Data Sheet (SDS)

EU Classification and Labelling Inventory for Liquid Diethoxymethane Polysulfide Polymer (CAS# 68611-50-7) and Bis(dimethylaminomethyl)phenol (CAS# 71074-89-0)

Existing ECHA registration(s) for Tris-2,4,6-(Dimethylaminomethyl) (CAS #90-72-2)

GHS Classification of the substance or mixture	Classification Procedure
Skin corrosion/irritation, Category 1	Threshold Calculation
Eye damage, category 1	Threshold Calculation
Skin Sensitisation, Category 1	Threshold Calculation
Specific target organ toxicity — single exposure, Category 3	Threshold Calculation
Hazardous to the aquatic environment, Chronic , Category 2	Summation Calculation

#### **LEGEND**

ACGIH: American Conference of Governmental Industrial Hygienists

REL: Recommended exposure limit

BEI: Biological Exposure Indices (ACGIH)

REL: Recommended exposure limit

SCL: Specific Concentration Limit

IARC: International Agency for Research on Cancer Skin": Risk of overexposure via dermal contact

Irr: Irritation STEL: Short Term Exposure Limit

NIOSH: National Institute of Occupational Safety and Health
NTP: National Toxicology Program
OSHA: The Occupational Safety & Health Administration
TLV: Threshold Limit value
TSCA: Toxic Substance Control Act
TWA: Time Weighted Average

PBT: Persistent, Bioaccumulative and Toxic URT: Upper respiratory tract

PEL: Permissible exposure limit vPvB: very Persistent and very Bioaccumulative

Training advice: Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

15581 Page: 6 of 7

Version: 1.0

Date of Issue: 10-May-2017 Date of First Issue: 10-May-2017



www.vishaypg.com

ACCORDING TO OSHA HCS (29 CFR 1910.1200)

#### **Disclaimers**

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Vishay Precision Group gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Vishay Precision Group accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

15581 Page: 7 of 7