

Strain Gage Adhesive

OTHER ACCESSORIES USED IN A DENEX #3 INSTALLATION:

- CSM Degreaser or GC-6 Isopropyl Alcohol
- Silicon-Carbide Paper
- M-Prep Conditioner A
- M-Prep Neutralizer 5A
- MJG-2 Mylar® Tape
- TFE-1 Teflon® Film
- HSC Spring Clamp
- GT-14 Pressure Pads and Backup Plates



RoHS
COMPLIANT

DESCRIPTION

Single-component, solvent thinned epoxy adhesive used in laboratory and transducer applications where negligible creep can be tolerated. Can be solvent

thinned (acetone) for easy application. Lower creep at elevated temperatures. Can be B-staged or dried prior to clamped curing.

CHARACTERISTICS	
PARAMETER	DETAILS
OPERATING TEMPERATURE RANGE	-452° to +400°F (-269°C to +204°C)
ELONGATION CAPABILITY	1% at +75°F (+24°C)
SHELF LIFE	Minimum 3 months @ +75°F (+24°C); minimum 6 months @ +40°F (+5°C). Refer to produce label for most recent information.
CLAMPING PRESSURE	30 to 50 psi (200 to 350 kN/m ²)
CURE REQUIREMENTS*	<p>Recommended Cure:</p> <p>Laboratory Use: 1 hour at +250°F (+120°C), followed by 1 hr at +350°F (+175°C)</p> <p>Transducers: 4 hours at +325°F (+163°C)</p> <p>Postcure (Unclamped):</p> <p>Laboratory Use: 1 hour at 75°F (40°C) above maximum operating temperature</p> <p>Transducers: 4 hours at +350°F (+175°C)</p>

PACKAGING
1 brush cap bottle (1/2 oz/15 ml) of premixed adhesive
1 brush cap bottle (1 oz/30 ml) of premixed adhesive
4 brush cap bottles (1 oz/30 ml each) premixed adhesive
1 bottle (32 oz/950 ml) premixed adhesive

* **Reference:** Instruction Bulletin B-173 for complete details.

Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase. **To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.**

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.