

NOTES:

- ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED.
- 2. DIMENSIONING & TOLERANCING CONFORM TO ASME Y14.5M-1994.
- 3. N IS THE TOTAL NUMBER OF TERMINALS.

 4. THE TERMINAL #1 IDENTIFIER AND TERMINAL NUMBERING CONVENTION SHALL CONFORM TO JESD 95-1 SPP-012. DETAILS

 1. THE TERMINAL #1 IDENTIFIER AND TERMINAL NUMBERING CONVENTION SHALL CONFORM TO JESD 95-1 SPP-012. DETAILS

 1. THE TERMINAL #1 IDENTIFIER AND TERMINAL #1 IDENTIFIER MAY BE EITHER A MOLD OR MARKED FEATURE.
- DIMENSION & APPLIES TO METALLIZED TERMINAL AND IS MEASURED BETWEEN 0.25mm AND 0.30mm FROM TERMINAL TIP. ${\mathscr E}$. ND AND NE REFER TO THE NUMBER OF TERMINALS ON EACH D AND E SIDE, RESPECTIVELY.
- DEPOPULATION IS POSSIBLE IN A SYMMETRICAL FASHION.
- $^{eta\!S\!N}$ coplanarity applies to the exposed heat sink slug as well as the terminals.
- 9. DRAWING CONFORMS TO JEDEC MO-220.
- 10. WARPAGE SHALL NOT EXCEED 0.10mm.
- 11 MARKING IS FOR PACKAGE ORIENTATION REFERENCE ONLY.
- 12. NUMBER OF LEADS SHOWN ARE FOR REFERENCE ONLY.
- 13. MATERIAL MUST COMPLY WITH BANNED AND RESTRICTED SUBSTANCES SPEC# 10-0131
- 14. ALL DIMENSIONS APPLY TO BOTH LEADED (-) AND POFREE (+) PKG. CODES.

PKG	68	N T E		
REF.	MIN.	N□M.	MAX.	T E
А	0.70	0.75	0.80	
A1	0.00	0.01	0.05	
A2	C			
b	0.20	0.25	0.30	
D	9.90	10.00	10.10	
E	9.90	10.00	10.10	
е	0			
k	0,25	_	-	
L	0.45	0.55	0.65	
N				
ND				
NE				
JEDEC	,			

EXPOSED PAD VARIATIONS									
PKG. CDDE	D2			E2					
	MIN.	N□M.	MAX.	MIN.	N□M.	MAX.			
T6800-2	7.60	7.70	7.80	7.60	7.70	7.80			
T6800-3	7.60	7.70	7.80	7.60	7.70	7.80			
T6800-4	7.60	7.70	7.80	7.60	7.70	7.80			
T6800-5	5.70	5.80	5.90	5.70	5.80	5.90			



TITLE:

PACKAGE DUTLINE, 68L THIN QFN, 10×10×0.8mm

APPROVAL DOCUMENT CONTROL NO.

G 21-0142

REV.